



# FRONWAY

## TBR CATALOGUE



### HD158



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
9.00R20	16	7.0	2800	2575	144/141	K	259	1019	900	131	15	320
10.00R20	18	7.5	3250	3000	149/146	K	278	1058	930	135	16.5	286
11.00R20	18	8.0	3550	3250	152/149	K	293	1082	930	135	16	266
11R22.5	16	8.25	3000	2725	146/143	M	279	1052	830	120	14.5	288
12.00R20	20	8.5	4000	3650	156/153	K	315	1125	900	131	16	228
12R22.5	18	9.0	3550	3250	152/149	M	300	1084	930	135	14.5	245
12.00R24	20	8.5	4500	4125	160/157	K	315	1220	900	131	15	194
13R22.5	20	9.75	4000	3350	156/150	L	320	1120	875	127	15	228
295/80R22.5	18	9.0	3550	3250	152/149	M	298	1044	900	131	15.5	264
315/80R22.5	20	9.0	4000	3350	156/150	M	312	1076	850	123	14.5	240

### HD168



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
11.00R20	18	8.0	3550	3250	152/149	K	293	1082	930	135	16.3	266
12.00R20	20	8.5	4000	3650	156/153	K	315	1125	900	131	16	228
12.00R24	20	8.5	4500	4125	160/157	K	315	1220	900	131	15	194

### HD202



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
11.00R20	18	8.0	3550	3250	152/149	K	293	1085	930	135	17	24

### HD118



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
12.00R24	20	8.5	4500	4125	160/157	K	315	1220	900	131	15	194

### HD580



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
12.00R24	20	8.5	4500	4125	160/157	K	313	1266	900	131	15	194

### HD200



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
12.00R24	20	8.5	4500	4125	160/157	K	315	1220	900	131	15	194

### HD757



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
11R22.5	16	8.25	3000	2725	146/143	M	279	1052	830	120	13	288
12R22.5	18	9.0	3550	3250	152/149	M	300	1084	930	135	14.5	245
295/80R22.5	18	9.0	3550	3250	152/149	M	298	1044	900	131	14.5	264
315/80R22.5	20	9.0	4000	3350	156/150	M	312	1078	850	123	14.5	240

### HD758



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
385/65R22.5	20	11.75	4500	4500	160	L	380	1073	900	131	15	196

### HD768



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
385/65R22.5	20	11.75	4500	4500	160	L	380	1073	900	131	15	196
275/70R22.5	16	8.25	3150	2900	148/145	M	272	952	900	131	14.5	-

### HD709



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
11R22.5	14	8.25	2800	2650	144/142	M	279	1048	720	104	11	288
11R22.5	16	8.25	3000	2725	146/143	M	279	1048	830	120	11	288
295/75R22.5	14	9.0	2800	2575	144/141	M	288	1011	760	110	11	292
295/75R22.5	16	9.0	3000	2725	146/143	M	288	1011	830	120	11	292
11R24.5	14	8.25	3000	2725	146/143	M	279	1088	720	104	11	260
11R24.5	16	8.25	3250	3000	149/146	M	279	1088	830	120	11	260

### HD609



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
11R22.5	14	8.25	2800	2650	144/142	M	279	1052	720	104	14.5	288
11R22.5	16	8.25	3000	2725	146/143	M	279	1052	830	120	14.5	288
11R24.5	14	8.25	3250	3000	146/143	M	279	1104	720	104	14.5	260
11R24.5	16	8.25	3250	3000	149/146	M	279	1104	830	120	14.5	260
295/75R22.5	14	9.0	2800	2575	144/141	M	298	1016	760	110	14.5	292
295/75R22.5	16	9.0	3000	2725	146/143	M	298	1016	830	120	14.5	292

### HD909



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
11R22.5	14	8.25	2800	2650	144/142	K	279	1058	720	104	20	276
11R22.5	16	8.25	3000	2725	146/143	K	279	1058	830	120	20	276
11R24.5	14	8.25	3000	2725	146/143	K	279	1104	720	104	20	257
11R24.5	16	8.25	3250	3000	149/146	K	279	1104	830	120	20	257
295/75R22.5	14	9.0	2800	2575	144/141	K	290	1022	760	110	20	288
295/75R22.5	16	9.0	3000	2725	146/143	K	290	1022	830	120	20	288

# HD797



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
215/75R17.5	16	6.0	1750	1600	127/124	M	210	766	830	120	12	680
215/75R17.5	18	6.0	2180	2060	135/133J	J	210	766	850	123	15	680
235/75R17.5	16	6.75	2000	1850	132/129	M	230	789	830	120	12.5	600
235/75R17.5	18	6.75	2725	2575	143/141	J	230	789	875	127	12.5	600
275/70R22.5	16	8.25	3150	2900	148/145	M	272	952	900	131	14.5	294
295/80R22.5	18	9.0	3550	3250	152/149	M	298	1044	900	131	15.5	264
315/80R22.5	20	9.0	4000	3350	156/150	M	312	1078	850	123	18	240
315/70R22.5	20	9.0	3750	3350	154/150	M	312	1010	900	131	15	260

# HD686



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
9.00R20	16	7.0	2800	2575	144/141	J	259	1019	900	131	15	320
10.00R20	18	7.5	3250	3000	149/146	J	278	1058	930	135	16	286
11.00R20	18	8.0	3550	3250	152/149	J	293	1086	930	135	18.3	256
12.00R20	20	8.5	4000	3650	156/153	J	315	1126	900	131	19	228

# HD888



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
11.00R20	18	8.0	3550	3250	152/149	G	293	1092	930	135	23	256
12.00R20	20	8.5	4000	3650	156/153	G	315	1132	900	131	23	228

# HD727



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
315/80R22.5	20	9.0	4000	3350	156/150	K	312	1078	850	123	18	240

# HD969



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
12.00R20	20	8.5	4000	3650	156/153	K	315	1128	900	131	19	228
11R22.5	16	8.25	3000	2725	146/143	K	279	1058	830	120	20	276
13R22.5	20	9.75	4000	3350	156/150	K	320	1124	875	127	20	228
295/80R22.5	18	9.0	3550	3250	152/149	K	298	1050	900	131	20	260
315/80R22.5	20	9.0	4000	3350	156/150	K	312	1082	850	123	20	240

# HD919



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
215/75R17.5	16	6.0	1750	1600	127/124	M	210	766	830	120	15	680
215/75R17.5	18	6.0	2180	2060	135/133J	J	210	766	850	123	15	680
235/75R17.5	16	6.75	2000	1850	132/129	M	230	789	830	120	15.5	600
235/75R17.5	18	6.75	2000	1850	143/141	J	230	789	875	127	15.5	600
275/70R22.5	16	8.25	3150	2900	148/145	M	272	962	900	131	18	294
275/70R22.5	18	8.25	3550	3150	152/148	M	272	962	930	135	18	294
11R22.5	16	8.25	3000	2725	146/143	M	279	1058	830	120	20	276
12R22.5	18	9.0	3550	3250	152/149	M	300	1090	930	135	20	244
295/80R22.5	18	9.0	3550	3250	152/149	L	298	1050	900	131	20	260
315/70R22.5	20	9.0	3750	3350	154/150	L	312	1020	900	131	20	260
315/80R22.5	20	9.0	4000	3350	156/150	K	312	1082	850	123	20	240

# HD868



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
11.00R20	18	8.0	3550	3250	152/149	G	293	1092	930	135	23	256
12.00R20	20	8.5	4000	3650	156/153	G	315	1132	900	131	23	228

# HD898



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
10.00R20	18	7.5	3250	3000	149/146	G	278	1060	930	135	20	286
11.00R20	18	8.0	3550	3250	152/149	G	293	1092	930	135	23	256
12.00R20	20	8.5	4000	3650	156/153	G	315	1132	900	131	23	228

# HD777



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
315/80R22.5	20	9.0	4000	3350	156/150	K	312	1078	850	123	18	240

# HD989



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
11.00R20	18	8.0	3550	3250	152/149	G	293	1086	930	135	20	256
12.00R20	20	8.5	4000	3650	156/153	G	315	1128	900	131	21	228
11R22.5	16	8.25	3000	2725	146/143	G	279	1058	830	120	20	276
12R22.5	18	9.0	3550	3250	152/149	G	300	1090	930	135	20	240
13R22.5	20	9.75	4000	3350	156/150	G	320	1124	875	127	20	228

# HD717



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
295/80R22.5	18	9.0	3550	3250	152/149	L	298	1044	900	131	18	260
315/80R22.5	20	9.0	4000	3350	156/150	K	312	1078	850	123	18	240

# HD939



Size	Ply Rating	Rim	Max load/kg		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			SINGLE	DUAL			SW(MM)	OD(MM)	KPA	PSI		
12.00R20	20	8.5	4000	3650	156/153	G	315	1125	900	131	20	228
295/80R22.5	18	9.0	3550	3250	152/148	G	298	1050	850	123	20	260



WEIFANG GOLDSHIELD TIRE CO.,LTD

www.goldshieldtire.com

