



FRONWAY



FRONWAY

PRODUCT GUIDE

TRUCK & BUS TIRE

WEIFANG GOLDSHIELD TIRE CO.,LTD
www.zodotire.cn

ALWAYS WITH YOU

FRONWAY



LEADING THE WAYS OF BEARING AND CARRYING

TBR TIRE





LONG HAUL

HD 158



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
9.00R20	16PR	7.0	2800	2575	144/142	K	259	1019	900	131	15	320
10.00R20	18PR	7.5	3250	3000	149/146	K	278	1054	930	135	15	286
11.00R20	18PR	8.0	3550	3250	152/149	K	293	1085	930	135	16	266
11R22.5	16PR	8.25	3000	2725	146/143	M	279	1054	830	120	14.5	288
12.00R20	20PR	8.5	4000	3650	156/153	K	315	1120	900	131	16	230
12.00R24	20PR	8.5	4500	4125	160/157	K	315	1226	900	131	15	194
12R22.5	18PR	9.00	3550	3250	152/149	M	300	1085	930	135	14.5	246
13R22.5	20PR	9.75	4000	3350	156/150	L	320	1124	875	127	15	228
295/80R22.5	18PR	9.00	3550	3250	152/149	M	298	1044	900	131	14.5	264
315/80R22.5	20PR	9.00	4000	3350	156/150	M	312	1076	850	123	14.5	240

LONG HAUL

HD202



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
11.00R20	18PR	8.0	3550	3250	152/149	K	293	1085	930	135	16.5	266

LONG HAUL

HD609



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
11R22.5	16PR	8.25	3000	2725	146/143	M	279	1054	830	120	14.5	288
11R24.5	16PR	8.25	3250	3000	149/146	M	279	1104	830	120	14.5	260
295/75R22.5	16PR	9.00	3000	2725	146/143	M	298	1014	830	120	14.5	292

LONG HAUL

HD709



Load performance

Wear performance

Speed performance

Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
11R22.5	16PR	8.25	3000	2725	146/143	M	279	1048	830	120	11	288
11R24.5	16PR	8.25	3250	3000	149/146	M	279	1104	830	120	11	260
295/75R22.5	16PR	9.00	3000	2725	146/143	M	298	1014	830	120	11	292

LONG HAUL

HD757



Load performance

Wear performance

Speed performance

Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
11R22.5	16PR	8.25	3000	2725	146/143	M	279	1054	830	120	14.5	288
12R22.5	18PR	9.00	3550	3250	152/149	M	300	1085	930	135	14.5	246
295/80R22.5	18PR	9.00	3550	3250	152/149	M	298	1044	900	131	14.5	264
315/80R22.5	20PR	9.00	4000	3350	156/150	M	312	1076	850	123	14.5	240

LONG HAUL

HD758



Load performance

Wear performance

Speed performance

Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
385/65R22.5	20PR	11.75	4500	-	160	L	389	1072	900	131	15.5	196

LONG HAUL

HD768



Load performance

Wear performance

Speed performance

Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
275/70R22.5	16PR	8.25	3150	2900	148/145	M	276	958	900	131	14.5	320
385/65R22.5	20PR	11.75	4500	-	160	L	389	1072	900	131	15.5	196

LONG HAUL

HD797



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
215/75R17.5	16PR	6.00	1750	1600	127/124	M	211	767	830	120	12	700
215/75R17.5	18PR	6.00	2180	2060	135/133	J	211	767	850	123	12	700
235/75R17.5	16PR	6.75	2000	1850	132/129	M	233	797	830	120	12.5	600
235/75R17.5	18PR	6.75	2725	2575	143/141	J	233	797	875	127	12.5	600
275/70R22.5	16PR	8.25	3150	2900	148/145	M	276	958	900	131	14.5	320
295/80R22.5	18PR	9.00	3550	3250	152/149	M	298	1044	900	131	15.5	264
315/70R22.5	20PR	9.00	3750	3350	154/150	M	312	1014	900	131	15	260
315/80R22.5	20PR	9.00	4000	3350	156/150	M	312	1076	850	123	15.5	240
385/65R22.5	20PR	11.75	4500	-	160	L	389	1072	900	131	15.5	196

LONG HAUL

HD958



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
11.00R20	18PR	8.0	3550	3250	152/149	K	293	1085	930	135	16.5	266
12.00R20	20PR	8.5	4000	3650	156/153	K	315	1120	900	131	16.5	230
12R22.5	18PR	9.00	3550	3250	152/149	K	300	1085	930	135	14.5	246

REGIONAL

HD168



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
9.00R20	16PR	7.0	2800	2650	144/142	K	259	1019	900	131	15	320
10.00R20	18PR	7.5	3250	3000	149/146	K	278	1054	930	135	15	286
11.00R20	18PR	8.0	3550	3250	152/149	K	293	1085	930	135	16.5	266
12.00R20	20PR	8.5	4000	3650	156/153	K	315	1120	900	131	16.5	230
12.00R24	20PR	8.5	4500	4125	160/157	K	315	1226	900	131	15.5	194

REGIONAL

HD178



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
12R22.5	18PR	9.00	3550	3250	152/149	L	300	1085	930	135	16.5	246

REGIONAL

HD200



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
12.00R24	20PR	8.5	4500	4125	160/157	K	315	1226	900	131	15.5	194

REGIONAL

HD399



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
12.00R24	20PR	8.5	4500	4125	160/157	K	315	1226	900	131	15.5	194

REGIONAL

HD580



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
12.00R24	20PR	8.5	4500	4125	160/157	K	315	1226	900	131	15.5	194

REGIONAL

HD628



Load performance  Wear performance 
Speed performance  Transport distance 

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
11.00R20	18PR	8.0	3550	3250	152/149	G	293	1096	930	135	19	256
12.00R20	20PR	8.5	4000	3650	156/153	G	315	1125	900	131	21	230

REGIONAL

HD686



Load performance  Wear performance 
Speed performance  Transport distance 

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
9.00R20	16PR	7.0	2800	2650	144/142	J	259	1019	900	131	15	320
10.00R20	18PR	7.5	3250	3000	149/146	J	278	1054	930	135	15	286
11.00R20	18PR	8.0	3550	3250	152/149	J	293	1096	930	135	18.5	256
12.00R20	20PR	8.5	4000	3650	156/153	J	315	1125	900	131	20	230

REGIONAL

HD717



Load performance  Wear performance 
Speed performance  Transport distance 

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
11R22.5	16PR	8.25	3000	2725	146/143	K	279	1054	830	120	18	276
12R22.5	18PR	9.00	3550	3250	152/149	K	300	1085	930	135	18	245
295/80R22.5	18PR	9.00	3550	3250	152/149	L	298	1050	900	131	18	264
315/80R22.5	20PR	9.00	4000	3350	156/150	M	312	1082	850	123	18	240

REGIONAL

HD727



Load performance  Wear performance 
Speed performance  Transport distance 

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
315/80R22.5	20PR	9.0	4000	3350	156/150	K	312	1082	850	123	18	240

REGIONAL

HD777



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
315/80R22.5	20PR	9.0	4000	3350	156/150	K	312	1082	850	123	18	240

REGIONAL

HD909



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
11R22.5	16PR	8.25	3000	2725	146/143	K	279	1065	830	120	20	276
11R24.5	16PR	8.25	3250	3000	149/146	K	279	1116	830	120	20	257
295/75R22.5	16PR	9.00	3000	2725	146/143	K	298	1020	830	120	20	288

REGIONAL

HD919



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
11R22.5	16PR	8.25	3000	2725	146/143	M	279	1065	830	120	20	276
12R22.5	18PR	9.00	3550	3250	152/149	M	300	1096	930	135	20	244
215/75R17.5	16PR	6.00	1750	1600	127/124	M	211	767	830	120	15	700
215/75R17.5	18PR	6.00	2180	2060	135/133	J	211	767	850	123	15	700
235/75R17.5	16PR	6.75	2000	1850	132/129	M	233	797	875	127	15.5	600
235/75R17.5	18PR	6.75	2725	2575	143/141	J	233	797	875	127	15.5	600
275/70R22.5	16PR	8.25	3150	2900	148/145	M	276	964	900	131	18	320
295/80R22.5	18PR	9.00	3550	3250	152/149	L	298	1054	900	131	20	262
315/70R22.5	20PR	9.00	3750	3350	154/150	L	312	1020	900	131	20	260
315/80R22.5	20PR	9.00	4000	3350	156/150	K	312	1082	850	123	20	240

REGIONAL

HD969



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
11R22.5	16PR	8.25	3000	2725	146/143	K	279	1065	830	120	20	276
12.00R20	20PR	8.5	4000	3650	156/153	K	315	1125	900	131	20	230
12R22.5	18PR	9.00	3550	3250	152/149	K	300	1096	930	135	20	246
13R22.5	20PR	9.75	4000	3350	156/150	K	320	1136	875	127	20	228
295/80R22.5	18PR	9.00	3550	3250	152/149	K	298	1054	900	131	20	260
315/80R22.5	20PR	9.00	4000	3350	156/150	K	312	1082	850	123	20	240

MINING

HD868



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
11.00R20	18PR	8.0	3550	3250	152/149	G	293	1096	930	135	23	256
12.00R20	20PR	8.5	4000	3650	156/153	G	315	1125	900	131	23	230

MINING

HD888



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
11.00R20	18PR	8.0	3550	3250	152/149	G	293	1096	930	135	23	256
12.00R20	20PR	8.5	4000	3650	156/153	G	315	1125	900	131	23	230

MINING

HD898



Load performance Wear performance
Speed performance Transport distance

Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY PCS/40HQ
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		
9.00R20	16PR	7.0	2800	2650	144/142	G	259	1030	900	131	20	320
10.00R20	18PR	7.5	3250	3000	149/146	G	278	1065	930	135	20	286
11.00R20	18PR	8.0	3550	3250	152/149	G	293	1096	930	135	23	256
12.00R20	20PR	8.5	4000	3650	156/153	G	315	1136	900	131	23	230

HD939



Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		PCS/40HQ
12.00R20	20PR	8.5	4000	3650	156/153	G	315	1125	900	131	20	230
12.00R24	20PR	8.5	4500	4125	160/157	G	315	1126	900	131	20	194
295/80R22.5	18PR	9.00	3550	3250	152/149	G	298	1054	900	131	20	260

HD989



Size	Ply Rating	Rim	Max load(kg)		Load Index	Speed Rating	Inflated Size		A.P.		Tread Depth (mm)	QTY
			Single	Dual			SW(mm)	OD(mm)	kPa	psi		PCS/40HQ
11.00R20	18PR	8.0	3550	3250	152/149	G	293	1096	930	135	20	256
11R22.5	16PR	8.25	3000	2725	146/143	G	279	1065	830	120	20	276
12.00R20	20PR	8.5	4000	3650	156/153	G	315	1125	900	131	21	230
12R22.5	18PR	9.00	3550	3250	152/149	G	300	1096	930	135	20	240
13R22.5	20PR	9.75	4000	3350	156/150	G	320	1136	875	127	20	228

* MEETING MINUTES *

This image shows a full page of white paper with horizontal red dashed lines. The lines are evenly spaced and run across the width of the page, providing a guide for handwriting practice. There are no margins, text, or other markings on the page.