

fileking®

G TIRES
U.S.A.

EJECUTIVO DE CUENTAS
Juan Carlos Burgos

 +57 312 8675625

fileking®



2025
product manual



CONTENTS

- GROUP PROFILE [P01](#)
- CERTIFICATES [P03](#)
- INTERNATIONAL EXHIBITIONS AND EVENTS [P04](#)
- WORLD-CLASS EQUIPMENT [P05](#)

 UHP	MK937 P07	MK927 P09	MK927SP P11	MK921 P12
 HP	EX-COMFORT P13	Runspirit P14		
 4*4 / SUV	MK869 P15	MK868 P17	MK878 P18	MK877 P19 NEW
	MK828 P21	MK818 P22	MK837 P23	MK829 P20
 ST TYRES	MK825 P24			
 LIGHT TRUCK	MK737 P25	MK717 P26		
 MINI	MK501 P27	MK506 P28		
 ECONOMY PCR	MK668 P29	MK667 P31		
 TAXI TIRE	MK665 P33			
 ALL SEASON	MK725 P34 NEW	MK625 P35 NEW		
 STUDDABLY WINTER	MK677 P37	MK657 P38 NEW		
 WINTER	MK687 P39	MK617 P41	MK697 P43 NEW	MK617SUV P44
	MK627 P45			
 EV	MK858 P46 NEW	MK317 P47 NEW	MK302 P48	

GROUP PROFILE



Sichuan HAIDA Rubber Group Co., Ltd. (hereinafter referred to as HAIDA GROUP) was founded in 1970 and is a wholly owned subsidiary of WULIANGYE GROUP. It is a nationally appointed and exclusive large-scale backbone enterprise in Sichuan Province, committed itself to R&D, manufacturing and marketing of TBR, PCR and TBB tires. It is also the largest demonstration base of research and development and production for tires in western China.

HAIDA GROUP is located in Jianyang, Chengdu, Sichuan Province, nearby TIANFU International Airport and high-speed train and railway station. Transportation is very convenient by road, river and air. Its famous brands include "HAIDA", "KALEVEI", "MILEKING", "COPARTNER", "LIGHTEN", "YINLU", "TIANFU" etc. These brands cover three categories of tires: TBR, PCR and TBB tires, with twenty-five series and more than 1000 varieties of sizes. These tires are applied in construction machinery, heavy-duty trucks, light trucks, large-scale buses, medium-sized buses, cars, SUVs and other commercial vehicles and passenger cars of all most popular vehicles. HAIDA is a world-renowned brand, a recommended PCR brand by China's rubber industry, and a famous brand in Sichuan Province. The "TIANFU" trademark is a well-known trademark in China.

HAIDA GROUP has been awarded the titles of "National Green Design Demonstration Enterprise for Industrial Products," "Top 100 Enterprises in Sichuan Province," and "Sichuan Province Integrity Model Enterprise." It is a national high-tech enterprise with the Sichuan Green Rubber Tire Engineering Technology Research Center. The company is certificated by ISO/TS16949 and ISO9001, ISO14001, GBT28001, CCC, DOT, ECE, GCC, GSO etc. Obtained over 270 national invention patents, utility model patents and design patents, including nearly 30 invention patents, its brands are enjoyed and favored by domestic and international customers for their excellent and stable quality.


HAIDA GROUP's marketing segments consist of local maintenance, OEM and overseas marketing, which exports to more than 100 countries or regions including North America, South America, Europe, the Middle East, Oceania, Africa and Southeast Asia. Its import and export revenue reached USD 230 million. HAIDA GROUP has established long-term strategic partnerships with SAIC General Motors, Hyundai Motor, Beiben North Benz, Changan Automobile, Chery Automobile, Geely Automobile, Seres Automobile and other vehicle factories. It also has over 300 mainstream dealers in the local maintenance market across all provinces, autonomous regions and municipalities in China.

HAIDA GROUP's main subsidiaries include Sichuan Tire & Rubber Co., Ltd., which mainly produces PCR and TBB tires, and Sichuan Kalevei Technology Co., Ltd., which primarily produces TBR tires. Its secondary business subsidiaries are Sichuan Jianyang Tianhai Engineering Co., Ltd., Sichuan Haihong Rubber Products Co., Ltd., Sichuan Jianyang Tianli Special Rubber Products Co., Ltd., and Sichuan Jianyang Chuangxiang Tianfa Logistics Co., Ltd. Their business scopes involve rubber and electronics, special rubber products, logistics and transport, etc. The group has achieved diversified development.


Haide Group adheres to green development and innovation, accelerating the pace of capacity enhancement and focusing on building a 4.0 digital factory. It is committed to fostering new quality productivity and empowering high-quality development through technological innovation. The goal is to become a highly competitive professional green intelligent tire manufacturer and service provider both domestically and internationally, steadily moving forward to becoming a 10 billion RMB enterprise.




CERTIFICATES



E4



DOT




e4




GCC



OHSAS 18001 2007



INMETRO



IATF16949



ISO9001



ISO14001 2015



INTERNATIONAL EXHIBITIONS AND EVENTS



WORLD-CLASS EQUIPMENT



1. Automatic chemical powder weighing system for mixer
2. Steel cord calendar made by Comerio Ercole of Italy
3. Steel Cord Calendar of COMERIO ERCOLE S.p.A Italy
4. Small angle steel cord cutting line of Slovakia
5. Single tire building machine of HOLLAND VMI



WORLD-CLASS EQUIPMENT



6. Steel-belted radial tyre hydraulic dual-mould curing press
7. Dynamic Balance Machine of Japan
8. ALPHA Curemeter Without Rotator
9. High-Speed Testing Machine
10. Rolling Resistance Testing Machine

PRODUCT FEATURES



The water modules with design of 3D drifting simulation provides better braking performance on wet/slippy road.

The straight slots and blocks in the outer of the tread reduce the road noise and improve the grasp force when making a turn.

The design with strengthening rib in inner of tire shoulder increases the rigidity of the pattern blocks, ensures better steerability of the tire.

UHP TYRES
MK937

mileking

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
205/55R16	91	V	6 1/2J	214	632	615	300
205/60R16	92	H	6J	209	652	630	300
205/65R16	95	H	6J	209	672	690	300
215/45R16	90XL	V	7J	213	600	600	340
215/65R16	98	H	6 1/2J	221	686	750	300
215/40ZR17	87XL	W	7 1/2J	218	604	545	340
225/50ZR17	98XL	W	7J	233	658	750	340
215/55R17	98XL	V	7J	226	668	750	340
215/60R17	96	H	6 1/2J	221	690	710	300
225/60R17	99	H	6 1/2J	228	702	775	300
225/65R17	102	H	6 1/2J	228	724	850	300
255/45ZR17	102XL	Y	8 1/2J	255	662	850	340
215/50R18	92	V	7J	226	673	630	300
225/50ZR18	99XL	W	7J	233	683	775	340
215/55R18	99XL	V	7J	226	693	775	340
225/55R18	102XL	V	7J	233	705	850	340
225/55R18	98	V	7J	233	705	750	300
225/60R18	100	V	6 1/2J	228	727	800	300
235/45ZR18	98XL	W	8J	236	669	750	340
235/50R18	101XL	V	7 1/2J	245	693	825	340
255/40ZR18	99XL	W	9J	260	661	775	340
205/55R19	97XL	V	6 1/2J	214	709	730	340
225/45ZR19	96XL	W	7 1/2J	225	685	710	340
225/55R19	99	V	7J	233	731	775	300

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
235/40ZR19	96XL	W	8 1/2J	241	671	710	340
235/45ZR19	99XL	W	8J	236	695	775	340
235/50R19	103XL	V	7 1/2J	245	719	875	340
235/50R19	99	V	7 1/2J	245	719	775	300
235/60R19	107XL	H	7J	240	765	975	340
245/45R19	102XL	V	8J	243	703	850	340
245/55R19	107XL	V	7 1/2J	253	753	975	340
255/40ZR19	100XL	Y	9J	260	687	800	340
255/45ZR19	104XL	Y	8 1/2J	255	713	900	340
255/50R19	107XL	V	8J	265	739	975	340
255/60R19	109	V	7 1/2J	260	789	1030	300
235/30ZR20	88XL	W	8 1/2J	242	650	560	340
235/45ZR20	100XL	W	8J	236	720	800	340
235/50ZR20	104XL	W	7 1/2J	245	744	900	340
235/55ZR20	105XL	W	7 1/2J	245	766	925	340
245/30ZR20	90XL	W	8 1/2J	248	656	600	340
245/45ZR20	103XL	W	8J	243	728	875	340
245/50R20	102	V	7 1/2J	253	754	850	300
255/40ZR20	101XL	W	9J	260	712	825	340
255/45ZR20	105XL	W	8 1/2J	255	738	925	340
255/50ZR20	109XL	W	8J	265	764	1030	340
255/55R20	110XL	V	8J	265	788	1060	340
265/45ZR20	108XL	W	9J	266	746	1000	340
275/45ZR20	110XL	W	9J	273	756	1060	340
275/50ZR20	109	W	8 1/2J	284	784	1030	300
235/45ZR21	101XL	Y	8J	236	745	825	340
245/40ZR21	100XL	W	8 1/2J	248	729	800	340
245/45ZR21	104XL	W	8J	243	753	900	340
255/40ZR21	102XL	Y	9J	260	737	850	340
255/45ZR21	105XL	W	8 1/2J	255	763	925	340
275/35ZR21	103XL	W	9 1/2J	278	725	875	340
275/40ZR21	107XL	Y	9 1/2J	278	753	975	340
275/50R21	113XL	V	8 1/2J	284	809	1150	340
275/45ZR21	110XL	Y	9J	273	781	1060	340
285/40ZR21	109XL	W	10J	290	761	1030	340
285/45ZR21	113XL	Y	9 1/2J	285	789	1150	340
315/35ZR21	111XL	Y	11J	320	753	1090	340
265/40ZR22	106XL	W	9 1/2J	271	771	950	340
265/45ZR22	109XL	W	9J	266	797	1030	340
285/40ZR22	110XL	W	10J	290	787	1060	340
325/35ZR22	114XL	Y	11 1/2J	331	787	1180	340
275/35ZR23	104XL	W	9 1/2J	278	776	900	340
285/40ZR23	111XL	W	10J	290	812	1090	340
315/30ZR23	108XL	W	11J	320	774	1000	340
325/35ZR23	111	W	11 1/2J	331	812	1090	300
305/30ZR26	109XL	W	11J	313	844	1030	340
275/25ZR28	100XL	W	10J	283	849	800	340
295/25ZR28	103XL	W	10 1/2J	301	859	875	340
255/30ZR30	102XL	W	9J	260	916	850	340
265/30ZR30	105XL	W	9 1/2J	271	922	925	340
275/25ZR30	101XL	W	10J	283	900	825	340



UHP TYRES MK927

UHP Asymmetric Pattern Tyre Series
3D asymmetric pattern design takes superior grip performance and shorter braking distances.



PRODUCT FEATURES



Outside strong blocks design enables the tyre to follow the road's surface contours more closely, helps to reduce blocks deformation while speed cornering, and enhances steering precision & better grip.

Inside wide rib grooves ensures effective water dispersion. Sequential blocks design improves tread rib hardness, enhances braking performance.

Wide rib grooves effectively removes water, provides shorter braking distances and safer handling on wet roads.

Racing compound technology provides superior grip performance on wet road surfaces.

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
205/45ZR16	87XL	W	7J	206	590	545	340
225/50R16	96XL	V	7J	233	632	710	340
205/50ZR17	93XL	W	6 1/2J	214	638	650	340
215/40ZR17	87XL	W	7 1/2J	218	604	545	340
215/45ZR17	91XL	W	7J	213	626	615	340
215/50ZR17	95XL	W	7J	226	648	690	340
225/45ZR17	94XL	W	7 1/2J	225	634	670	350
225/50ZR17	98XL	W	7J	233	658	750	340
235/55R17	103XL	V	7 1/2J	245	690	875	340
235/45ZR17	97XL	W	8J	236	644	730	340
235/50R17	100XL	V	7 1/2J	245	668	800	340
245/45ZR17	99XL	W	8J	243	652	775	340
215/40ZR18	89XL	W	7 1/2J	218	629	580	340
215/45ZR18	93XL	W	7J	213	651	650	340
215/55R18	99XL	V	7J	226	693	775	340
225/40ZR18	92XL	W	8J	230	637	630	350
225/45ZR18	95XL	W	7 1/2J	225	659	690	350
225/50R18	99XL	V	7J	233	683	775	340
235/40ZR18	95XL	W	8 1/2J	241	645	690	350
235/45ZR18	98XL	W	8J	236	669	750	340
235/50ZR18	101XL	W	7 1/2J	245	693	825	340
245/40ZR18	97XL	W	8 1/2J	248	653	730	340
235/55R18	104XL	V	7 1/2J	245	715	900	340
235/60R18	103	V	7J	240	739	875	300
245/45ZR18	100XL	W	8J	243	677	800	340
255/35ZR18	94XL	W	9J	260	635	670	340
255/55R18	109XL	V	8J	265	737	1030	340
255/50R18	106XL	V	8J	265	713	950	340
265/35ZR18	97XL	W	9 1/2J	271	643	730	340
265/60R18	110	H	8J	272	775	1060	300
215/35ZR19	85XL	W	7 1/2J	218	633	515	340
225/35ZR19	88XL	W	8J	230	641	560	340
225/40ZR19	93XL	W	8J	230	663	650	340
235/35ZR19	91XL	W	8 1/2J	241	647	615	340
235/50R19	103XL	V	7 1/2J	245	719	875	340
235/55R19	105XL	V	7 1/2J	245	741	925	340
245/35ZR19	93XL	W	8 1/2J	248	655	650	350
245/40ZR19	98XL	W	8 1/2J	248	679	750	340
245/50R19	105XL	V	7 1/2J	253	729	925	340
255/55R19	111XL	V	8J	265	763	1090	340
265/30ZR19	93XL	W	9 1/2J	271	643	650	340
275/40ZR19	105XL	W	9 1/2J	278	703	925	340
225/35ZR20	93XL	W	8J	230	666	650	350
235/30ZR20	88XL	W	8 1/2J	242	650	560	340
245/30ZR20	90XL	W	8 1/2J	248	656	600	340
245/35ZR20	95XL	W	8 1/2J	248	680	690	350
245/40ZR20	99XL	W	8 1/2J	248	704	775	340
255/35ZR20	97XL	Y	9J	260	686	730	350
255/35ZR20	102XL	Y	9J	260	686	850	350
265/50ZR20	111XL	W	8 1/2J	277	774	1090	340
315/35ZR20	110XL	W	11J	320	728	1060	340
265/45ZR21	104	W	9J	266	771	900	300
265/40ZR21	105XL	W	9 1/2J	271	745	925	340
295/35ZR21	107XL	W	10 1/2J	301	739	975	340
265/35ZR22	102XL	W	9 1/2J	271	745	850	350
275/40ZR22	107XL	W	9 1/2J	278	779	975	340
285/35ZR22	106XL	W	10J	290	759	950	340
285/45R22	114XL	V	9 1/2J	285	815	1180	340
295/30R24	105XL	V	10 1/2J	301	788	925	340
255/30ZR26	99XL	W	9J	260	814	775	340
275/25ZR26	98XL	W	10J	283	798	750	340
295/30ZR26	107XL	W	10 1/2J	301	838	975	340



UHP TYRES MK927SP

UHP Asymmetric Pattern Tyre Series
3D asymmetric pattern design takes superior grip performance and shorter braking distances.



PRODUCT FEATURES



Optimum water dispersion and steering on both sides and minimum rolling resistance with the four longitudinal transverse grooves and radial sipes.

Lower road noise level and tranquil ride with the extra long tread grooves and fuzzy pattern.

Maximum grip and road adhesion with the pattern block and rib pattern on shoulders.

Strong rim-protecting ring to avoid impact for safe driving at high speed.

UHP TYRES MK921

Action and fashion, elegance and nobility, quality racing tyre with unidirectional pattern.



PRODUCT FEATURES



Outside strong blocks design enables the tyre to follow the road's surface contours more closely, helps to reduce blocks deformation while speed cornering, and enhances steering precision & better grip.

Inside wide rib grooves ensures effective water dispersion. Sequential blocks design improves tread rib hardness, enhances braking performance.

Wide straight grooves coupled with fine slots can effectively drain the water, damage the water film, shorten the braking distance and provide better wet control performance.

Racing compound technology provides superior grip performance on wet road surfaces.

Size	Load Index	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
235/40ZR17	94XL	W	8 1/2J	241	620	670	340
245/40ZR17	95XL	W	8 1/2J	248	628	690	340
255/35ZR19	96XL	W	9J	260	661	710	340
275/35ZR19	100XL	W	9 1/2J	278	675	800	340
275/30ZR19	96XL	W	9 1/2J	278	649	710	340
245/45ZR20	103XL	W	8J	243	728	875	340
275/30ZR20	97XL	W	9 1/2J	278	674	730	340
275/35ZR20	102XL	W	9 1/2J	278	700	850	340
275/40ZR20	106XL	W	9 1/2J	278	728	950	340
285/30ZR20	99XL	W	10J	290	680	775	340

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
205/50R16	91XL	V	6 1/2J	214	612	615	320
215/55R16	97XL	V	7J	226	642	730	280
205/40ZR17	84XL	W	7 1/2J	212	596	500	350
205/45R17	88XL	H	7J	206	616	560	340
205/50ZR17	93XL	W	6 1/2J	214	638	650	350
215/35ZR18	84XL	W	7 1/2J	218	607	500	350
225/30ZR20	85XL	W	8J	230	644	515	350
245/45ZR20	103XL	W	8J	243	728	875	340
275/40ZR20	106XL	W	9 1/2J	278	728	950	350
275/45ZR20	110XL	W	9J	273	756	1060	350
275/55ZR20	117XL	V	8 1/2J	284	810	1285	340
225/30ZR22	87XL	W	8J	230	695	545	340
235/30ZR22	90XL	W	8 1/2J	241	701	600	340
265/30ZR22	97XL	W	9 1/2J	271	719	730	340
265/40ZR22	106XL	W	9 1/2J	271	771	950	340
295/25ZR22	97XL	W	10 1/2J	301	707	730	340
275/25ZR24	96XL	W	10J	283	748	710	340
245/30ZR24	94XL	W	8 1/2J	248	758	670	340

PRODUCT FEATURES



The four wide longitudinal drainage grooves provide excellent wetland performance of the tire, which effectively prevent the side sliding.

The coupling design with the crosswise arc grooves and fine arc slots effectively damaged the water film in the wet road, which provide better grasp force in the wetland.

The 3D slots design increased the braking and grounding area to provide bigger traction force. Meantime it effectively increased the heat radiation area and improved the endurance performance of the tire.

The green environment protection material with silicon material optimized the profile of tire tread with better oil consumption, it more quiet and comfort.




HP TYRES EX-COMFORT

UHP Asymmetric Pattern Tyre Series
3D asymmetric pattern design takes superior grip performance and shorter braking distances.



PRODUCT FEATURES



The four wide longitudinal drainage grooves provide excellent wetland performance of the tire.

The strong design of the shoulder resisted the irregular wearing of the tire.

The coupling design of longitudinal and crosswise arc grooves effectively damaged the water film on the wet road, which provide better grasp force on the wet road.

The green environment protection material with silicon material optimized the profile of tire tread with better oil consumption, it more quiet and comfort.



HP TYRES Runspirit

Action and fashion, elegance and nobility,
quality racing tyre with unidirectional pattern.



Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
165/65R13	77	T	5.00B	170	544	412	300
175/60R13	77	H	5.00B	177	540	412	300
175/70R13	82	T	5.00B	177	576	475	300
175/75R13	85	T	5.00B	177	592	515	300
175/65R14	82	H	5J	177	584	475	300
175/70R14	88 XL	T	5J	177	602	560	340
175/75R14	86	T	5J	177	618	530	300
185/65R14	86	H	5 1/2J	189	596	530	300
185/70R14	88	H	5 1/2J	189	616	560	300
195/70R14	91	H	6J	201	630	615	300
175/65R15	84	H	5J	177	609	500	300
185/60R15	88 XL	H	5 1/2J	189	603	560	340
185/65R15	88	H	5 1/2J	189	621	560	300
195/60R15	82	V	6J	201	577	475	300
195/55R15	85	V	6J	201	595	515	300
195/60R15	88	V	6J	201	615	560	300
195/65R15	91	V	6J	201	635	615	300
205/65R15	94	H	6J	209	647	670	300
195/45R16	84 XL	V	6 1/2J	195	582	500	340
195/50R16	84	V	6J	201	602	500	300
195/55R16	87	V	6J	201	620	545	300
205/55R16	91	V	6 1/2J	214	632	615	300
205/60R16	92	V	6J	209	652	630	300
215/55ZR16	97 XL	W	7J	226	642	730	340
215/60R16	95	H	6 1/2J	221	664	690	300
205/45ZR17	88 XL	W	7J	206	616	560	340
205/50ZR17	93 XL	W	6 1/2J	214	638	650	340
205/55R17	91	V	6 1/2J	214	658	615	300
215/45ZR17	91 XL	W	7J	213	626	615	300
215/50ZR17	95 XL	W	7J	226	648	690	340
215/55ZR17	93 XL	W	7J	226	668	750	340
225/45ZR17	94 XL	W	7 1/2J	235	634	670	340
225/50ZR17	98 XL	W	7J	233	658	750	340
225/55R17	97	V	7J	233	680	730	300
225/40ZR18	92 XL	W	8J	230	637	630	340
225/45ZR18	95 XL	W	7 1/2J	225	659	690	340
245/45ZR18	100 XL	W	8J	243	677	800	340
245/40ZR19	98 XL	W	8 1/2J	248	679	750	340

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
175/60R13	77	H	5.00B	177	540	412	300
175/70R13	82	T	5.00B	177	576	475	300
185/70R13	86	T	5.00B	189	590	530	300
175/70R14	88 XL	T	5J	177	602	560	340
175/65R14	82	H	5J	177	584	475	300
185/65R14	86	H	5 1/2J	189	596	530	300
185/70R14	88	T	5 1/2J	189	616	560	300
195/70R14	91	H	6J	201	630	615	300
185/60R15	88 XL	H	5 1/2J	189	603	560	340
185/65R15	88	H	5 1/2J	189	621	560	300
195/50R15	82	V	6J	201	577	475	300
195/55R15	85	V	6J	201	595	515	300
195/60R15	88	V	6J	201	615	560	300
195/65R15	91	V	6J	201	635	615	300
205/65R15	94	H	6J	209	647	670	300
195/55R16	87	V	6J	201	620	545	340
205/55R16	91	V	6 1/2J	214	632	615	300
205/60R16	92	V	6J	209	652	630	300
215/55ZR16	97 XL	W	7J	226	642	730	340
215/60R16	95	H	6 1/2J	221	664	690	300
265/70R16	112	T	8J	272	778	1120	300
205/45ZR17	88 XL	W	7J	206	616	560	340
205/50ZR17	93 XL	W	6 1/2J	214	638	650	340
215/45ZR17	91 XL	W	7J	213	626	615	340
215/50ZR17	95 XL	W	7J	226	648	690	340
215/55ZR17	98 XL	W	7J	226	668	750	340
225/45ZR17	94 XL	W	7 1/2J	225	634	670	340
225/50ZR17	98 XL	W	7J	233	658	750	340
235/65R17	104	H	7J	240	738	900	300
225/40ZR18	92 XL	W	8J	230	637	630	340
225/45ZR18	95 XL	W	7 1/2J	225	659	690	340
235/60R18	103	V	7J	240	739	875	300
245/45ZR18	100 XL	W	8J	243	677	800	340



PRODUCT FEATURES



The design with opened cross-grooves/shoulders provide better capability with self-cleaning and grasp force, improved the trafficability on mud/damaged road.

The utilization with wave-shape steel plates greatly improved the grasp force of the tire.

The design with tooth-mate pattern grooves makes the tires having better self-cleaning capability, and improved the grasp force and trafficability on damaged road.

The design with anti-collision rib improved the self-cleaning capability and avoid the stones clamped and improved the puncture resistance of the tire.

Size	Load Index	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
32 × 11.50R15LT 6PR	113	Q	9J	290	807	1150	350
33 × 12.50R15LT 6PR	108	Q	10J	318	832	1000	250
35 × 12.50R15LT 6PR	113	Q	10J	318	883	1150	250
LT235/85R16 10PR	120/116	Q	6 1/2J	235	812	1400/1250	550
LT245/75R16 10PR	120/116	Q	7J	248	780	1400/1250	550
LT265/75R16 10PR	123/120	Q	7 1/2J	267	810	1550/1400	550
LT285/75R16 10PR	126/123	Q	8J	286	840	1700/1550	550
LT305/70R16 10PR	124/121	Q	9J	311	834	1600/1450	450
LT315/75R16 10PR	127/124	Q	8 1/2J	313	878	1750/1600	450
LT235/80R17 10PR	120/117	Q	6 1/2J	235	808	1400/1285	550
LT245/75R17 10PR	121/118	Q	7J	248	800	1450/1320	550
LT255/75R17 6PR	111/108	Q	7J	255	814	1090/1000	350
33X12.50R17LT 10PR	120	Q	10J	318	832	1400	450
37X12.50R17LT 8PR	124	Q	10J	318	934	1600	350
33X12.50R18LT 10PR	118	Q	10J	318	832	1320	450
LT275/60R20 10PR	123/120	Q	8J	279	844	1550/1400	550
LT275/55R20 10PR	120/117	Q	8 1/2J	284	810	1400/1285	550
LT285/55R20 10PR	122/119	Q	9J	297	822	1500/1360	550
LT305/55R20 10PR	121/118	Q	9 1/2J	316	844	1450/1320	550
33X12.50R20LT 12PR	119	Q	10J	318	832	1360	550
35X12.50R20LT 12PR	125	Q	10J	318	883	1650	550
37X13.50R20LT 10PR	127	Q	11J	345	934	1750	450
33X12.50R22LT 12PR	114	Q	10J	318	832	1180	550
35X12.50R22LT 12PR	121	Q	10J	318	883	1450	550
33X14.50R22LT 12PR	117	Q	13J	372	832	1285	550
LT365/45R24 12PR	125	Q	11 1/2J	365	935	1650	550
33X12.50R24LT 10PR	104	Q	11 1/2J	318	832	900	450
35X12.50R24LT 10PR	117	Q	10J	318	883	1285	450
37X13.50R24LT 12PR	126	Q	11J	345	934	1700	550
33X12.50R26LT 10PR	114	Q	11 1/2J	318	832	1180	450
35X13.50R26LT 10PR	118	Q	12J	345	883	1320	450
37X13.50R26LT 12PR	117	Q	11J	345	934	1285	550
37X14.50R28LT 12PR	118	Q	11 1/2J	368	935	1320	550
40X15.50R28LT 10PR	126	Q	12J	389	1011	1700	450
42X13.50R30LT 12PR	125	Q	11J	343	1062	1650	550
42X16.50R30LT 10PR	127	Q	13 1/2J	419	1062	1750	450

PRODUCT FEATURES



The deep shoulder pattern design and wide pattern block provide extreme grip force, which ensured the excellent handling and safety performance for the vehicle on the severe condition such as mountain and muddy road etc.

The ideal configuration of the pattern grooves and blocks and the high proportional horizontal grooves guaranteed the excellent anti-skid performance on the muddy road.

The design of anti-collision wall in the sidewall prevents the puncture, road collision and pressure damage.



MT TYRES
MK868

The special 3D solid pattern design is suitable to the cross-country vehicles on the non-pavement road with supreme anti-skid performance on muddy road, powerful traction force and extreme grip performance.



PRODUCT FEATURES



The strong shoulder pattern design and unique wide pattern block provide extreme grip force and handing performance, which ensured the excellent safety handing performance and passability for the vehicle on any severe road condition.

The design of anti-collision wall in the sidewall prevents the puncture, road collision and pressure damage.



R/T TYRES
MK878


The special 3D solid pattern design is suitable to the cross-country vehicles on the whole road, with supreme anti-skid performance and extreme severe road passability.



Size	Ply Rating	Load Index	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
LT245/75R16	10PR	120/116	Q	7J	248	780	1400/1250	550
LT265/75R16	10PR	123/120	Q	7 1/2J	267	810	1550/1400	550
LT285/70R17	10PR	121/118	Q	8 1/2J	292	838	1450/1320	550
33x12.50R17LT	10PR	120	Q	10J	318	832	1400	450
35x12.50R17LT	10PR	125	Q	10J	318	883	1650	450
33x12.50R18LT	10PR	118	Q	10J	318	832	1320	450
35x12.50R18LT	10PR	123	Q	10J	318	883	1550	450
P275/60R20	/	115	S	8J	279	844	1215	300
LT275/65R20	10PR	126/123	Q	8J	279	872	1700/1550	550
33x12.50R20LT	10PR	114	Q	10J	318	832	1180	450
35x12.50R20LT	10PR	121	Q	10J	318	883	1450	450
33x12.50R22LT	10PR	114	Q	10J	318	832	1180	450
35x12.50R22LT	10PR	117	Q	10J	318	883	1285	450
35x12.50R24LT	10PR	117	Q	10J	318	883	1285	450

Size	Load Index	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
LT265/75R16 10PR	123/120	Q	7 1/2J	267	810	550	1550/1400
LT285/75R16 10PR	126/123	Q	8J	286	840	550	1700/1550
P265/70R17	115	T	8J	272	810	300	1215
P285/70R17	117	T	8 1/2J	292	838	300	1285
LT265/70R17 10PR	121/118	Q	8J	272	810	550	1450/1320
LT285/70R17 10PR	121/118	Q	8 1/2J	292	838	550	1450/1320
33x12.50R17LT 10PR	120	Q	10J	318	832	450	1400
35x12.50R17LT 10PR	125	Q	10J	318	883	450	1650
33x12.50R18LT 10PR	118	Q	10J	318	832	450	1320
35x12.50R18LT 10PR	123	Q	10J	318	883	450	1550
37x13.50R18LT 8PR	124	Q	11J	345	934	350	1600
P275/60R20	115	T	8J	279	844	300	1215
33x12.50R20LT 10PR	114	Q	10J	318	832	450	1180
35x12.50R20LT 10PR	121	Q	10J	318	883	450	1450
37x13.50R20LT 10PR	127	Q	11J	345	934	450	1750
33x12.50R22LT 10PR	114	Q	10J	318	832	450	1180
35x12.50R22LT 10PR	117	Q	10J	318	883	450	1285
33*12.50R24LT 10PR	104	Q	11 1/2J	318	832	450	900
33*14.50R24LT 10PR	110	Q	13J	372	832	450	1060

PRODUCT FEATURES



Strong and rigid pattern design provide strong and powerful grounding area with sturdy performance to resist the serious impact from road.

Special design with longitudinal and crosswise wide pattern grooves provide powerful traction force on muddy, snow and gravel condition. Supreme traction force and arduous crosscountry enriched your beautiful life.

The design with rectangular shoulder and wide tread has the wear-resistance formula to provide the excellent mileage of traveling.

The special design with impact-resistance in the shoulder and rigid tire sidewall improve the resistance performance on cutting, stripping and tearing.

NEW

X/T TYRES

MK877

The special 3D solid pattern design is suitable to the cross-country vehicles on the whole road, with supreme anti-skip performance and extreme severe road passability.

mileking



AT OFF-ROAD TIRE

MK829

This coupled design of irregular pattern block provided enhanced traction and grip performance. The outline design with computer simulation provides more stable, long-range stability. The enhanced design was specifically designed to enhance the puncture resistance performance. The pattern with low splayed ratio design improved the service life and mileage.

mileking

Size	Load Index	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
165R13C 8PR	94/93	Q	4.50B	165	594	670/650	450
175R13C 8PR	97/95	Q	5.00B	178	609	730/690	450
185R14C 8PR	102/100	Q	5 1/2J	188	650	850/800	450
195R14C 8PR	106/104	Q	5 1/2J	198	666	950/900	450
235/60R14	96	T	7J	240	638	710	250
195R15C 8PR	106/104	Q	5 1/2J	198	690	950/900	450
205/65R15C 6PR	102/100	Q	6J	209	647	850/800	375
205/70R15C 8PR	106/104	Q	6J	209	669	950/900	450
LT215/75R15 6PR	100/97	Q	6J	216	703	800/730	350
225/50R15	91	T	7J	233	607	615	250
235/60R15	98	T	7J	240	663	750	250
235/75R15XL	109	T	6 1/2J	235	733	1030	290
205/60R16	92	T	6J	209	652	630	250
215/70R16	100	T	6 1/2J	221	708	800	250
LT225/75R16 10PR	115/112	Q	6J	223	744	1215/1120	550
LT235/70R16 8PR (OWL)	110/107	Q	7J	240	736	1060/975	450
LT245/70R16 8PR (OWL)	113/110	Q	7J	248	750	1150/1060	450
LT255/70R16 8PR (OWL)	115/112	Q	7 1/2J	260	764	1215/1120	450
LT245/70R17 10PR (OWL)	119/116	R	7J	248	776	1360/1250	550
LT265/65R17 10PR (OWL)	120/117	Q	8J	272	776	1400/1285	550
LT265/70R17 10PR (OWL)	121/118	Q	8J	272	804	1450/1320	550
LT275/65R17 10PR (OWL)	121/118	Q	8J	279	790	1450/1320	550
LT275/70R17 10PR (OWL)	121/118	Q	8J	279	818	1450/1320	550
LT285/65R17 10PR (OWL)	121/118	Q	8 1/2J	292	802	1450/1320	550
LT285/70R17 10PR (OWL)	126/123	Q	8 1/2 J	292	832	1700/1550	550
LT315/70R17 10PR (OWL)	126/123	Q	9 1/2J	323	874	1700/1550	450
LT255/60R18 10PR (OWL)	117/114	R	7 1/2J	260	763	1280/1180	550
LT265/65R18 10PR (OWL)	122/119	Q	8J	272	801	1500/1360	550
LT285/60R18 10PR (OWL)	122/119	Q	8 1/2J	292	799	1500/1360	550
33 x 12.50R20LT 10PR (OWL)	119	R	10J	318	832	1360	550
P205/70R15	96	T	6J	209	669	710	300
P265/70R16	112	T	8J	272	778	1120	300
P265/60R18	114	H	8J	272	775	1180	340

PRODUCT FEATURES




The overall coupling design of irregular pattern block provides stronger traction ability and grip performance

Enhanced design of tire edge anti-collision block to enhance the anti puncture ability of poor road surface

Computer simulation of the tread square profile design provides more stable grounding ability

Size	Ply Rating	Load Index	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
LT265/75R16	10PR	123/120	R	7 1/2 J	267	804	1550/1400	550
LT285/75R16	10PR	126/123	R	8J	286	834	1700/1550	550
LT265/65R17	10PR	120/117	S	8J	272	776	1400/1285	550
LT265/70R17	10PR	121/118	S	8J	272	804	1450/1320	550
LT285/70R17	10PR	121/118	R	8 1/2 J	292	832	1450/1320	550
LT265/60R18	10PR	120/117	S	8J	272	775	1400/1285	550
LT265/65R18	10PR	122/119	R	8J	272	801	1500/1360	550
LT275/65R18	10PR	123/120	R	8J	279	815	1550/1400	550
LT275/55R20	10PR	120/117	S	8 1/2 J	284	810	1400/1285	550
LT305/55R20	10PR	121/118	S	9 1/2 J	316	844	1450/1320	450

PRODUCT FEATURES



Optimized pitching sequence blocks design offers quieter ride.

Wide pyramidal-shaped sipes for all-weather and various roads delivers excellent safety, maintains firm grip performance and aquaplaning resistance on wet roads, and enhances off-road steering response.

Unique lateral flange protector design enhances protection from puncture and impact damage.

Rectangle shoulder and wide tread design with 3D multiple thin sipes increases road contact area, provides superior handling on both wet and dry surfaces, and enhances wear-resisting performance.

4x4 AT TYRES

MK828

Rectangle shoulder and wide tread design with 3D multiple thin sipes provides superior traction, combines off-road capability in all conditions with on-road comfortable features.



4x4 AT TYRES

MK818

Tenacious and valiant with the MK818 cross-country pattern.



PRODUCT FEATURES



Outstanding performance with high-strength steel cord and cap ply.

Tranquility with fuzzy arrangement of pattern block without specified peak and with variable sound frequency blocks.


Safety with wide tapered groove pattern applicable to all weather and various road conditions. Better country-crossing capability with its gripping power and anti-skid performance on wet roads.

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
215/75R14C 8PR	104/101	Q	6J	216	678	900/825	450
215/75R15LT 8PR	100/97	S	6J	216	703	800/730	350
215/75R15LT 8PR	106/103	S	6J	216	703	950/875	450
P215/75R15LT 8PR	100	S	6J	216	703	950/875	350
225/75R15	102	S	6J	223	719	850	250
235/75R15LT 6PR	104/104	S	6 1/2J	235	733	900/825	350
235/75R15LT 10PR	116/113	Q	6 1/2J	235	733	1250/1150	550
31 x 10.5R15LT 6PR	109	Q	8 1/2J	268	775	1030	350
215R16C 6PR	109/107	Q	6J	218	750	1060/1000	375
245/75R16LT 10PR	120/116	Q	7J	248	774	1380/1260	550

Pattern Guide
to Steel-belted Radial Tyre / 22



PRODUCT FEATURES



The wide pattern block and transverse oblique grooves link broad longitudinal straight grooves, fuel-efficient, environmental and safety on driving.

Four broad longitudinal straight grooves match with creative wavy and pitching thin sipes, excellent performance on wet roads and stable steering performance.

The new outline and pitch design, as if across in a comfortable and tranquil city.

HT TYRES

MK837

All weather comfortable and energy saving cross-country tire.



ST TYRES

MK825



Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
235/75R15	105	T	6 1/2J	235	733	925	300
255/70R15	108	T	7 1/2J	260	739	1000	300
265/70R15	112	T	8J	272	753	1120	300
215/70R16	100	T	6 1/2J	221	708	800	300
225/70R16	103	T	6 1/2J	228	722	875	300
235/60R16	100	H	7J	240	688	800	300
235/70R16	106	T	7J	240	736	950	300
P245/70R16	107	T	7J	248	750	975	300
255/70R16	111	T	7 1/2J	260	764	1090	300
265/70R16	112	T	8J	272	778	1120	300
275/70R16	114	T	8J	279	792	1180	300
215/50R17	95XL	W	7J	226	648	690	340
215/60R17	96	H	6 1/2J	221	690	710	300
215/65R17	99	H	6 1/2 J	221	712	775	300
225/65R17	102	H	6 1/2J	228	724	850	300
235/65R17	104	H	7J	240	738	900	300
245/65R17	107	T	7J	248	750	975	300
265/65R17	112	T	8J	272	776	1120	300
265/70R17	115	T	8J	272	804	1215	300
215/55R18	99XL	V	7J	226	693	775	340
225/55R18	98	V	7J	233	703	750	300
235/50R18	101XL	V	7 1/2 J	245	693	825	340
235/55R18	104XL	V	7 1/2 J	245	715	900	340
245/60R18	105	H	7J	248	751	925	300
255/70R18	113	T	7 1/2 J	260	815	1150	300
265/60R18	114	H	8J	272	775	1180	340
265/70R18	116	T	8J	272	829	1250	300
275/55R20	117XL	H	8 1/2J	284	810	1285	340

PRODUCT FEATURES



Combined design with shoulder crosswise curve grooves and lengthwise curves grooves provide good stability and safety of driving.

Design of lengthwise grooves with multiple angles provide excellent controlling and steering performance on the dry/wet road.

Strengthened design of cacapability of the tyre,ross enhanced the load and impact

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	At Cold kPa	kgf/cm2	Inflation Pressure(kPa)
ST175/80R13 C	91/87	L	5.00B	177	610	615/545		350
ST205/75R14 C	100/96	L	5 1/2J	203	664	800/710		350
ST215/75R14 C	102/98	L	6J	216	678	850/750		350
ST205/75R15 D	107/102	L	5 1/2J	203	689	975/850		450
ST225/75R15 E	117/112	L	6 J	223	719	1285/1120		550
ST235/80R16 E	124/120	L	6 1/2J	235	782	1600/1400		550
ST235/85R16 E	125/121	L	6 1/2J	235	806	1650/1450		550

PRODUCT FEATURES



The design with three wide longitudinal water outlet slots and balanced pattern blocks/slots enhances the water outlet performance on wet/slippery road and provides excellent steerability of the vehicle. The outstanding durability provides better mileage of driving. The load capacity is stable and excellent.

The design with strong shoulder blocks and unique decoupling longitudinal grooves provides high performance of stable steerability and irregular anti-wearing on various road condition.



LIGHT TRUCK TYRES

MK737



PRODUCT FEATURES



The extra-strong structure design ensures the excellent braking and steering capability, which adapts various complex road & weather conditions.

Design of extra-deep pattern grooves and outstanding tread compound improves the anti-abrasion capability, which effectively prolonged the service life of the tyre.

Excellent grip on dry and wet roads for safe ride with zigzagging pattern grooves, reasonably arranged fine patterns and robust pattern blocks.



LIGHT TRUCK TYRES

MK717

Mk717 pattern with high quality/performance and rigidity balanced safety to you.



Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
185R14C 8PR	102/100	R	5 1/2J	188	650	850/800	450
195R14C 8PR	106/104	R	5 1/2J	198	652	950/900	450
195R15C 8PR	106/104	S	5 1/2J	198	668	950/900	450
195/70R15C 8PR	104/102	R	6J	201	655	900/850	450
205/70R15C 8PR	106/104	R	6J	209	669	950/900	450
215/70R15C 8PR	109/107	R	6 1/2J	221	683	1030/975	450
215/70R15LT 8PR	104/101	R	6 1/2J	221	683	900/825	450
215/65R15C 6PR	104/102	T	6 1/2J	221	661	900/850	375
225/70R15C 10PR	112/110	R	6 1/2J	228	697	1120/1060	550
255/70R15C 8PR	112/110	S	7 1/2J	260	739	1120/1060	450
185/75R16C 8PR	104/102	R	5 J	184	684	900/850	475
195/75R16LT 10PR	107/103	S	5 1/2J	196	698	975/875	550
195/75R16LT 12PR	112/109	T	5 1/2J	196	698	1120/1030	650
195/75R16C 8PR	107/105	R	5 1/2J	196	698	975/925	475
205/75R16C 8PR	110/108	R	5 1/2J	203	714	1060/100	475
215/70R16C 8PR	108/106	T	6 1/2J	221	708	1000/950	450
215/75R16C 10PR	116/114	R	6J	216	728	1250/1180	525
205/65R16C 8PR	107/105	T	6J	209	672	975/925	475
215/65R16C 8PR	109/107	T	6 1/2J	221	686	1030/975	475
225/65R16C 8PR	112/110	T	6 1/2J	228	698	1120/1060	475
235/65R16C 8PR	115/113	T	7J	240	712	1215/1150	475
235/65R16C 10PR	121/119	Q	7J	240	712	1450/1360	575

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
185R14C 8PR	102/100	Q	5 1/2J	188	652	850/800	450
195R14C 8PR	106/104	Q	5 1/2J	198	668	950/900	450
195R14C 8PR 白边	106/104	Q	5 1/2J	198	668	950/900	450
195R15C(LT) 8PR	106/104	S	5 1/2J	198	693	950/900	450
205/70R14	98 XL	T	6J	209	644	750	270
205/80R14	98	S	5 1/2J	203	710	750	250
215/75R14C(LT) 8PR	104/101	Q	6J	216	678	900/825	450
195/70R15C 6PR	98/96	S	6J	201	655	750/710	325
195/70R15LT 6PR	93/90	R	6J	201	655	650/600	350
195/70R15LT 8PR	99/96	Q,R	6J	201	655	775/710	450
195/70R15LT 10PR	104/101	Q,R	6J	201	655	900/825	550
195/70R15LT 12PR	109/105	Q	6J	201	655	1030/925	650



HIGH QUALITY LIGHT TRUCK TIRE

MK501

Mileking



HIGH QUALITY MINI-CAR TIRE

MK506

Mileking

PRODUCT FEATURES



High Quality design with deep grooves pattern and wide tread surface provide excellent endurance performance.

Simple and continuous design with big pattern block and smooth lengthwise grooves provide excellent steering and drainage performance.

The pattern design with wide shoulder enhanced the grounding performance, improved the stability when turning and ensured the safety of driving.

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
165R14LT 8PR	96/95	S	4 1/2J	165	620	710/690	450
175R14C 8PR	99/97	S	5J	177	636	775/730	450
175/70R14C 8PR	99/95	S	5J	177	602	775/690	450
175/75R14C 8PR	99/98	S	5J	177	618	670/630	450
185R14C 8PR	102/100	R	5 1/2J	189	652	900/850	450
185/70R14C 8PR	102/100	S	5 1/2J	189	616	850/800	450
195/70R15LT 10PR	104/101	S	6J	201	655	900/825	550
225/70R15C 10PR	112/110	R	6J	228	697	1120/1060	550
215/75R16C 10PR	112/109	R	6.5J	216	728	1120/1030	550

PRODUCT FEATURES



High Quality design with deep grooves pattern and wide tread surface provide excellent endurance performance.

Simple and continuous design with big pattern block and smooth lengthwise grooves provide excellent steering and drainage performance.

The pattern design with wide shoulder enhanced the grounding performance, improved the stability when turning and ensured the safety of driving.

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
225/55R12C 6PR	93	N	7J	233	553	650	350




ECONOMY PCR TYRES MK668

Optimal design coupled hardness with softness and high percentage silica tread compound improves fuel savings, low noise, safety and economy.



PRODUCT FEATURES



New formula reduces 30%–40% of rolling resistance, decreases fuel consumption and CO₂ emission load.

Wide tread design increases road contact area, maintains safe ride, and enhances wear-resisting performance.

High ratio straight main sipes design effectively reduces rolling resistance and noise, perfectly combines environmental protection with comfort.

Pitching sequence shoulder blocks design shows outstanding controlling at high speed. Perfect distribution of lug type pattern with thin sipes in the tread enhances traction on wet roads.

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
195/55R15	85	V	6J	201	595	515	300
195/60R15	88	H	6J	201	615	560	300
195/60R15LT	95/91	R	6J	201	615	690/615	450
195/65R15	91	H	6J	201	635	615	300
195/70R15	92	S	6J	201	655	630	300
205/60R15	91	V	6J	209	627	615	300
205/70R15	96	H	6J	209	669	710	300
205/65R15	94	H	6J	209	647	670	300
205/65R15	99XL	H	6J	209	647	775	340
215/70R15	98	T	6 1/2J	221	683	750	300
225/75R15	102	S	6J	223	719	850	300
195/50R16	84	V	6J	201	602	500	300
195/55R16	91XL	H	6J	201	620	615	340
195/60R16	89	H	6J	201	640	580	300
205/50R16	91XL	V	6 1/2J	214	312	615	340
205/55R16	91	V	6 1/2J	214	632	615	300
205/60R16	92	H	6J	209	652	630	300
205/65R16	95	H	6J	209	672	690	300
215/60R16	99XL	H	6 1/2J	221	664	775	340
215/65R16	98	H	6 1/2J	221	686	750	300
225/60R16	98	H	6 1/2J	228	676	750	300
205/55R17	91	H	6 1/2J	214	658	615	300
215/50R17	95XL	V	7J	226	648	690	340
215/55R17	94	V	7J	226	668	670	300
215/60R17	96	H	6 1/2J	221	690	710	300
215/65R17	99	V	6 1/2J	221	712	775	300
225/55R17	97	V	7J	233	680	730	300
225/60R17	99	H	6 1/2J	228	702	775	300
225/65R17	102	H	6 1/2J	228	724	850	300
225/60R18	100	V	6 1/2J	228	727	800	300
235/50R18	101XL	V	7 1/2J	245	693	825	340



ECONOMY PCR TYRES **MK667**

High quality, high performance, low carbon
and eco-friendly pattern, modern green tire.



PRODUCT FEATURES



Three broad longitudinal straight groove design with tread effectively increase the longitudinal groove width and offers tires optimum grip on wet roads and powerful water dispersion.

High ratio straight main groove matching whole block design effectively reduces rolling resistance and noise, perfectly combines environmental protection with comfort.

New formula reduces 30%–40% rolling resistance, fuel consumption and CO₂ emission load. Arc thin sipes pattern design and the effectively segmentation pattern design improving tires grip ability and the safety on driving.

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single dual)(kg)	Inflation Pressure(kPa)
145/70R12	69	Q	4.50B	150	509	325	300
145/70R12	69	S	4.50B	150	509	325	300
155/70R12	73	T	4.50B	157	523	365	300
165/70R12	77	T	5.00B	177	537	412	300
155/65R13	73	Q	4.50B	157	532	365	300
155/70R13	75	T	4.50B	157	548	387	300
165/65R13	77	T	5.00B	170	544	412	300
165/70R13	79	S	5.00B	170	562	437	300
175/60R13	77	H	5.00B	177	540	412	300
175/70R13	82	S	5.00B	177	576	475	300
185/70R13	86	T	5.50B	189	590	530	300
155/65R14	75	H	4 1/2J	157	558	387	300
165/60R14	75	T	5J	170	554	387	300
165/65R14	79	H	5J	170	570	437	300
175/65R14	82	T	5J	177	584	475	300
185/60R14	82	H	5 1/2J	189	578	475	300
185/65R14	86	T	5 1/2J	189	596	530	300
185/65R14	90XL	S	5 1/2J	189	596	600	300
185/70R14	88	T	5 1/2J	189	616	560	300
195/70R14	95XL	H	6J	201	630	690	340
205/60R14	88	H	6J	209	602	560	300
215/70R14	96	H	6 1/2J	221	658	710	300
185/55R15	82	V	6J	194	585	475	300
185/60R15	88XL	H	5 1/2J	189	603	560	340
185/65R15	88	H	5 1/2J	189	621	560	300
185/65R15	92	H	5 1/2J	189	621	630	340
185/65R15LT 8PR	94/91	R	5 1/2J	189	621	670/615	450
185/65R15LT 10PR	99/96	Q	5 1/2J	189	621	775/710	550
185/65R15LT 12PR	103/100	Q	5 1/2J	189	621	875/800	650
195/50R15	82	V	6J	201	577	475	300
195/55R15	85	H	6J	201	595	515	300
195/60R15	88	H	6J	201	615	560	300
195/65R15	91	H	6J	201	635	615	300
205/60R15	91	H	6J	209	627	615	300
205/65R15	94	H	6J	209	647	670	300
195/60R16	93 XL	H	6J	201	640	650	340
195/60R16C 6PR	99/97	Q	6J	201	640	775/730	375
205/55R16	91	V	6 1/2J	214	632	615	300
T125/80R16	97	M	4T	131	606	730	420
T125/90R16	98	M	4T	131	632	750	420
T155/90R16	110	M	4T	152	686	1060	420
T125/80R17	99	M	4T	131	632	775	420
T135/90R17	104	M	4T	138	676	900	420
T155/80R17	111	M	4T	152	680	1090	420
T155/90R17	112	M	4T	152	712	1120	420
T165/80R17	115	M	4T	159	696	1215	420
T135/80R18	104	M	4T	138	673	900	420
T145/80R18	109	M	4T	145	689	1030	420



PRODUCT FEATURES



The design with widened and big pattern blocks enlarged the contacting area and rigidity, which effectively resisted the wearing, improved the service life. The control-ability on dry/wet road and steer-ability is excellent.

The alkene rubber matched with high structure wearing resistance V10H-UH carbon black, together with the new mixing technology and high wearing resistance receipt, meet the requirements on long mileage performance.

The special design with gradient chamfer in grooves/blocks with better beauty to avoid the stone clamped, resisted the irregular wearing.

TAXI TIRE

MK665

Mileking®



ALL SEASON

MK725

Mileking®

PRODUCT FEATURES



The design with three lengthwise grooves and the rigid shoulder blocks provides excellent dry/wet land safety and steering performance.

The design with high-density 3D cutter slots patterns in tread and shoulder area guaranteed the excellent steering performance on snow/icy land.

The tread formula for all season design ensured the safety of the driving during the summer and icy winter seasons.

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
195/70R15C 8PR	104/102	S	6J	201	655	900/850	450
215/70R15C 8PR	109/107	S	6 1/2J	221	683	1030/975	450
225/70R15C 8PR	112/110	S	6 1/2J	228	697	1120/1060	450
185/75R16C 8PR	104/102	S	5J	184	684	900/850	475
185/75R16C 10PR	107/105	S	5J	184	684	975/925	525
195/75R16C 8PR	107/105	S	5 1/2J	196	698	975/925	475
195/75R16C 10PR	107/108	S	5 1/2J	196	698	1060/1000	525
205/65R16C 8PR	107/105	T	6J	209	672	975/925	475
205/75R16C 8PR	113/111	S	5 1/2J	203	714	1150/1090	525
215/65R16C 8PR	109/107	T	6 1/2J	221	686	1030/975	475
225/65R16C 8PR	112/110	S	6 1/2J	228	698	1120/1060	475
225/75R16LT 10PR	121/120	R	6J	223	744	1450/1400	575
235/65R16C 8PR	115/113	S	7J	240	712	1215/1150	475



PRODUCT FEATURES



The lengthwise cascade grooves improved the riding ability on dry/wet land with the summer fine grooves while draining the water effectively.

The design with special 3D cut slots helps to enhance the stability and the grasp force on ice road.

The tread formula for all season design ensured the safety of the driving during the summer and icy winter seasons.

The designed with two lengthwise zigzag pattern grooves and the high angle crosswise grooves guaranteed the water drainage performance on the wet land and the steering performance on the snow and ice road.

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
175/70R12	80	T	5.00B	177	551	450	300
165/70R13	79	T	5.00B	170	562	437	300
175/70R13	82	T	5.00B	177	576	475	300
155/65R14	75	T	4 1/2J	157	558	387	300
165/70R14	81	T	5.00B	170	588	462	300
175/65R14	82	T	5J	177	584	475	300
175/65R14	86XL	T	5J	177	584	530	340
185/60R14	82	H	5 1/2J	189	578	475	300
185/65R14	86	H	5 1/2J	189	596	530	300
185/70R14	88	T	5 1/2J	189	616	560	300
185/55R15	82	H	6J	194	585	475	300
185/60R15	84	H	5 1/2J	189	603	500	300
185/65R15	88	H	5 1/2J	189	621	560	300
195/50R15	82	V	6J	201	577	475	300
195/55R15	85	V	6J	201	595	515	300
195/60R15	88	V	6J	201	615	560	300
195/65R15	91	H	6J	201	635	615	300
205/65R15	94	V	6J	209	647	670	300
195/45R16	84XL	V	6 1/2J	195	582	500	340
195/55R16	87	V	6J	201	620	545	300
195/55R16	91XL	V	6J	201	620	615	340
195/60R16	89	V	6J	201	640	580	300
205/55R16	91	V	6 1/2J	214	632	615	300
205/55R16	94XL	V	6 1/2J	214	632	670	340
205/60R16	92	H	6J	209	652	630	300
215/55ZR16	97XL	W	7J	226	642	730	340
215/60R16	99XL	V	6 1/2J	221	664	775	340
215/65R16	102XL	V	6 1/2J	221	686	850	340
215/70R16	100	H	6 1/2J	221	708	800	300
205/45ZR17	88XL	W	7J	206	616	560	340
205/50ZR17	93XL	W	6 1/2J	214	638	650	340
205/55ZR17	95XL	W	6 1/2J	214	658	690	340
215/50ZR17	95XL	W	7J	226	648	690	340
215/55ZR17	98XL	W	7J	226	668	750	340
215/60R17	100XL	V	6 1/2J	221	690	800	340
225/45ZR17	94XL	Y	7 1/2J	225	634	670	340
225/50ZR17	98XL	Y	7J	233	658	750	340
225/55ZR17	101XL	W	7J	233	680	825	340
225/60R17	103XL	V	6 1/2J	228	702	875	340
235/55ZR17	103XL	W	7 1/2J	245	690	875	340
235/65ZR17	108XL	W	7J	240	738	1000	340
225/40ZR18	92XL	Y	8J	230	637	630	340
235/45ZR18	98XL	Y	8J	236	669	750	340
225/55ZR18	98	W	7J	233	703	750	300
235/50ZR18	101XL	W	7 1/2 J	245	693	825	340
235/55ZR18	104XL	W	7 1/2J	245	715	900	340
235/60ZR18	107XL	W	7J	240	739	975	340
235/55ZR19	105XL	W	7 1/2J	245	741	925	340
245/40ZR19	98XL	Y	8 1/2J	248	679	750	340
245/45ZR19	102XL	Y	8J	243	703	850	340

PRODUCT FEATURES



The design with directional V-Shape grooves enhances the flowing of water and snow in the grooves, which can effectively drainage the snow and water and provides better traction and grasp force in the snow/icy road.

The optimized design arrangement of stud hole increases the grasp force on snow/icy road and reduced the noise, providing better steerability and traction force on snow/icy road.

The design with 3D grooves increased the contacting area with ice and snow and improved the grasp force. The pattern design with continuous pattern in the tire cap effectively increased the rigidity of the pattern, the slant fine and wave grooves ensures better stability of steerability.




STUDDABLY WINTER TYRES

MK677

Meiking

PRODUCT FEATURES



The integrated pattern design in the center area improved the entire rigidity and the exact responding of driving, it also increased the grasp force on the road.

The special pattern design with 3D cutter grooves improved the stability of grasp performance on snow road.

The optimized arrangement of studs minimized the disturbing noise wave while increased the grasp force on ice road. It also improved the driving comfort for the driver.



NEW



WINTER TYRES

MK657

Meiking

Size	Load Index /PR	Speed	Wet Grip	Fuel Efficiency	Noise dB	Inflation Pressure(kPa)
PCR						
175/70R13	82	T	C	C	71	300
175/65R14	86 XL	T	C	C	71	340
185/65R14	90 XL	T	C	C	71	340
185/70R14	92 XL	T	C	C	71	340
185/55R15	86XL	T	C	C	71	340
185/60R15	88 XL	T	C	C	71	340
185/65R15	92XL	T	C	C	71	340
195/65R15	95 XL	T	C	C	72	340
205/65R15	99 XL	T	C	C	72	340
195/55R16	91XL	T	C	C	72	340
205/55R16	94 XL	T	C	C	72	340
205/60R16	96 XL	T	C	C	72	340
215/60R16	99 XL	T	C	C	72	340
205/50R17	93XL	T	C	C	72	340
215/50R17	95XL	T	C	C	72	340
215/55R17	98XL	T	C	C	72	340
225/55R17	101 XL	T	C	C	72	340
225/50R17	98 XL	T	C	C	72	340
225/45R17	94XL	T	C	C	72	340
235/55R17	99	T	C	C	72	300
225/40R18	92 XL	T	C	C	72	340
225/45R18	95 XL	T	C	C	72	340
235/55R18	104 XL	T	C	C	72	340
245/45R18	100 XL	T	C	C	72	340
235/55R19	105 XL	T	C	C	72	340
SUV						
215/65R16	102 XL	T	C	C	72	340
265/70R16	112	T	C	C	73	300
215/60R17	100 XL	T	C	C	72	340
225/60R17	103 XL	T	C	C	72	340
225/65R17	106 XL	T	C	C	72	340
235/65R17	108 XL	T	C	C	72	340
265/65R17	116XL	T	C	C	73	340
235/60R18	107 XL	T	C	C	72	340
235/45R18	98XL	T	C	C	72	340
285/60R18	116	T	C	C	75	300
265/60R18	114XL	T	C	C	73	340
LT275/70R18 10PR	125/122	Q	/	/	/	550
LT275/65R18 10PR	123/120	Q	/	/	/	550

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single dual)(kg)	Inflation Pressure(kPa)
195/60R15	92XL	T	6J	201	615	630	340
205/65R16C 8PR	107/105	Q	6J	209	672	975/925	475
215/55R16	97XL	T	7J	226	642	730	340
215/70R16	100	T	6 1/2J	221	708	800	300
225/65R16C 8PR	112/110	Q	6 1/2J	228	698	1120/1060	475
225/75R16C 12PR	121/120	Q	6J	223	744	1450/1400	575
235/65R16C 12PR	121/119	Q	7J	240	712	1450/1360	575
215/65R17	103XL	T	6 1/2J	221	712	875	340
235/45R17	97XL	T	8J	236	644	730	340
215/55R18	95	T	7J	226	693	690	300
235/50R18	101XL	T	7 1/2J	245	693	825	340
245/40R18	97XL	T	8 1/2J	248	653	730	340
225/55R18	102XL	T	7J	233	705	850	340
255/60R18	112XL	T	7 1/2J	260	763	1120	340
225/60R18	104XL	T	6 1/2J	228	727	900	340
255/45R19	104XL	T	8 1/2J	255	713	900	340
245/45R19	98	T	8J	243	703	750	300
255/50R19	103	T	8J	265	739	875	300
255/55R19	107	T	8J	265	763	975	300
255/40R20	101XL	T	9J	260	712	825	340
255/45R20	105XL	T	8 1/2J	255	738	925	340
265/50R20	111XL	T	8 1/2J	277	774	1090	340



PRODUCT FEATURES



Design with three longitudinal zigzag pattern grooves provides water drainage performance in wet road and excellent steer-ability on snow/ice road.

Design with big pattern block outside provides enough rigidity and excellent steer-ability.

Design with multiple crossed pattern inside enlarges snow holding capability and strength of snow column, and enhanced the grip capability.


The fine slots in the pattern reduced the hitting noise, the zigzag slots diffused the noise frequency, making the noise even in various frequency waves.

Size	Load Index /PR	Speed	Wet Grip	Fuel Efficiency	Noise dB	Inflation Pressure(kPa)
145/70R12	69	Q	/	/	/	300
155/65R13	73	Q	/	/	/	300
175/65R14	82	T	B	C	71	300
185/65R14	90XL	T	B	C	71	340
175/65R15	88XL	T	B	C	71	340
185/55R15	82	T	B	C	71	300
185/60R15	88XL	T	B	C	72	340
185/65R15	92XL	T	B	C	72	340
195/50R15	82	H	B	C	72	300
195/65R15	95XL	T	B	C	72	340
205/55R16	94XL	T	B	C	72	340
205/60R16	96XL	T	B	C	72	340
215/55R16	97XL	T	B	C	72	340
215/60R16	99XL	T	B	C	72	340
215/65R16	102XL	T	B	C	72	340
225/70R16	103	T	B	C	72	300
245/70R16	107	T	B	C	72	300
205/50R17	93XL	T	B	C	72	340
205/55R17	95XL	H	B	C	72	340
215/55R17	98XL	T	B	C	72	340
225/45R17	94XL	T	B	C	72	340
225/50R17	98XL	T	B	C	72	340
225/55R17	101XL	T	B	C	73	340
225/60R17	103XL	T	B	C	75	340
225/65R17	106XL	T	B	C	72	340
235/65R17	108XL	T	B	C	72	340
245/65R17	107	T	B	C	72	300
215/55R18	99XL	H	B	C	72	340
225/55R18	102XL	T	B	C	72	340
225/60R18	104XL	T	B	C	72	340
235/45R18	98XL	H	B	C	72	340
235/50R18	101XL	V	B	C	72	340
235/60R18	107XL	T	B	C	72	340
235/65R18	110XL	T	B	C	72	340
245/45R18	100XL	T	B	C	72	340
255/55R18	109XL	T	B	C	72	340
265/60R18	114XL	T	B	C	73	340
285/60R18	116	T	B	C	75	300
225/45R19	96XL	H	B	C	72	340
225/55R19	99H	H	B	C	72	300
235/35R19	91XL	V	B	C	72	340
235/40R19	96XL	V	B	C	72	340
235/50R19	103XL	V	B	C	72	340
235/55R19	105XL	H	B	C	72	340
245/45R19	102XL	H	B	C	72	340
245/55R19	107XL	H	B	C	72	340
255/40R19	100XL	V	B	C	73	340
255/50R19	107XL	T	B	C	73	340
255/45R19	104XL	H	B	C	72	340
235/45R20	100XL	H	B	C	72	340



The materials such as silica etc are added in the tread compound; it is low-temperature resistance and features excellent adhesion force on the ice/snow.

PRODUCT FEATURES



The four longitudinal pattern grooves with zigzag design provide excellent handling performance in snow and ice road.

The big pattern blocks with mutual supporting ensured the stability of steering, and the widened ribs and the pattern blocks with center vertical design guaranteed the grasp force in the ice road in starting or braking.

The saw-teeth pattern grooves coupled with horizontal grooves arranged in different inclination angle, provide excellent handling performance in snow road.

The design with crossed center cutter grooves and fine grooves improves the effective result of on the side edge. The inclination direction of the cutter grooves and the block edge is same to effectively outlet the water film on the ice road.



WINTER TYRES

MK697

mileking®

WINTER TYRES

MK617SUV

mileking®

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
155/65R14	75	T	4 1/2J	157	558	387	300
215/65R15	96	H	6 1/2J	221	661	710	300
205/45R16	87XL	H	7J	206	590	545	340
205/50R16	91XL	H	6 1/2J	214	612	615	340
235/60R16	102XL	H	6 1/2J	228	676	850	340
235/60R16	100	H	7J	240	688	800	300
205/65R16	95	H	6J	209	672	690	300
265/70R16	112	T	8J	272	778	1120	300
205/45R17	98XL	V	7J	206	616	560	340
215/65R17	103XL	T	6 1/2J	221	712	875	340
235/60R17	102	H	7J	240	714	850	300
245/45R17	99XL	V	8J	243	652	775	340
235/40R18	95XL	V	8 1/2J	241	645	690	340
225/50R18	99XL	H	7J	233	683	775	340
245/50R18	104XL	H	7 1/2J	253	703	900	340
225/40R19	93XL	V	8J	230	663	650	340
235/45R19	98XL	V	8J	236	695	775	340
245/40R19	98XL	V	8 1/2J	248	679	750	340
245/60R18	105	H	7J	248	751	925	300
255/60R19	113XL	T	7 1/2J	260	789	1150	340
265/55R19	109	H	8 1/2J	277	775	1030	300
255/35R19	96XL	V	9J	260	661	710	340
255/55R19	111XL	V	8J	265	763	1090	340
275/35R19	100XL	V	9 1/2J	278	675	800	340
275/40R19	105XL	V	9 1/2J	278	703	925	340
235/50R20	104XL	H	7 1/2J	245	744	900	340
235/55R20	105XL	V	7 1/2J	245	766	925	340
245/35R20	95XL	V	8 1/2J	248	680	690	340
245/40R20	99XL	V	8 1/2J	248	704	775	340
245/45R20	103XL	V	8J	253	728	875	340
245/50R20	102	H	7 1/2J	253	754	850	300
255/35R20	97XL	V	9J	260	686	730	340
255/40R20	101XL	V	9J	260	712	825	340
255/45R20	105XL	V	8 1/2J	255	738	925	340
255/55R20	110XL	H	8J	265	788	1060	340
255/50R20	109XL	H	8J	265	764	1030	340
275/35R20	102XL	V	9 1/2J	278	700	800	340
275/40R20	106XL	V	9 1/2J	278	728	950	340
275/45R20	110XL	H	9J	273	756	1060	340
275/50R20	113XL	H	8 1/2J	284	784	1150	340
265/45R21	108XL	H	9J	266	771	1000	340
275/45R21	110XL	H	9J	273	781	1060	340

PRODUCT FEATURES



The wide tire and new 3D saw tooth fine seam pattern design of the crown increase the grip area of the crown and effectively improve the ice and snow grip of the tire.

The unique single guide and V-shaped wide groove design increases the performance of water and snow drainage, and improves the braking and safe handling performance of snow driving in winter.

Silicon dioxide and other materials are added to the tread, which has low temperature resistance and excellent ice and snow adhesion.

The projected small sharp angle ensures the reliable contact of the tyre and the ground surface under low temperature, which also enhanced the grip capability.

The special design with directional pattern and various 3D steel sheets effectively enhanced the grasp capability on icy/snow pavement.

Size	Load Index /PR	Speed	Wet Grip	Fuel Efficiency	Noise dB	Inflation Pressure(kPa)
215/70R15	98	T	C	E	72	300
235/75R15	105	Q	C	E	72	300
215/70R16	100	Q	C	E	72	300
235/70R16	106	Q	C	E	72	300
215/60R17	96	T	C	E	72	300
225/60R17	99	T	C	E	72	300
235/65R17	104	T	C	E	72	300
265/70R17	115	T	C	E	73	300
265/65R17	112	T	C	E	73	300
275/65R17	115	T	C	E	73	300
235/55R18	104 XL	T	C	E	72	340
235/60R18	103	T	C	E	72	300
275/65R18	116	T	C	E	73	300
275/55R20	117 XL	T	C	E	73	340
275/60R20	115	T	C	E	73	300

PRODUCT FEATURES



The special design with directional pattern and various 3D steel sheets effectively enhanced the grasp capability on icy/snow pavement.

The design of shoulder pattern with rectangular shape and integrated coupling style enhanced the load capability and stable steerability on icy/snow pavement.

The design with three lengthwise zigzag grooves provide better capability to outlet the water and snow, and it also improved the steerability in slippery condition.

The projected small sharp angle ensures the reliable contact of the tyre and the ground surface under low temperature, which also enhanced the grip capability.



WINTER TYRES
MK627

Safely Driving on Icy/Snow Pavement.



PRODUCT FEATURES



The Design with Fully Connected Groove Bottom Effectively Drained Water/Mud.

Fine and Dense Steel Sheet Provides Excellent Braking/Traction Performance.

Varied Shoulder Pitch With Reinforced Rib Improved The Strength and Reduced The Running Noise.

NEW


ELECTRIC VEHICLE TYRE

MK858



Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
165R14C 8PR	97/95	Q	4 1/2J	167	622	730/690	450
175R14C 8PR	99/98	Q	5J	178	634	775/750	450
175/70R14C 8PR	99/95	Q	5J	177	602	775/690	450
175/75R14C 8PR	99/98	Q	5J	177	618	670/630	450
185R14C 8PR	102/100	Q	5 1/2J	189	652	900/850	450
195/70R15C 8PR	104/102	R	6J	201	655	900/850	450
205/70R15C 8PR	106/104	R	6J	209	669	950/900	450
215/70R15C 8PR	109/107	R	6 1/2J	221	683	1030/975	450
225/70R15C 8PR	112/110	R	6 1/2J	228	697	1120/1060	450
185/75R16C 8PR	104/102	R	5J	184	684	900/850	475
195/75R16C 8PR	107/105	R	5 1/2J	196	698	975/925	475
195/65R16C 8PR	104/102	Q	6J	201	660	900/850	475
205/75R16C 8PR	110/108	Q	5 1/2J	203	714	1060/1000	475
205/65R16C 8PR	107/105	T	6J	209	672	975/975	475
215/65R16C 8PR	109/107	R	6 1/2J	221	686	1030/975	475
215/75R16C 8PR	113/111	R	6J	216	728	1150/1090	475
225/65R16C 8PR	112/110	R	6.5J	228	698	1120/1060	475
235/65R16C 8PR	115/113	R	7J	240	712	1215/1150	475
235/65R16C 10PR	121/119	R	7J	240	712	1450/1360	575

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
265/65R17	112	T	8J	272	776	1120	300
235/60R18	107XL	H	7J	240	739	975	340
265/60R18	110	H	8J	272	775	1060	300
275/65R18	116	T	8J	279	815	1250	300
235/50R19	103XL	H	7 1/2J	245	719	875	340
235/55R19	105XL	H	7 1/2J	245	741	925	340
245/55R19	107XL	H	7 1/2J	253	753	975	340
255/55R19	111XL	H	8J	265	763	1090	340
255/50R20	109XL	H	8J	265	764	1030	340
265/45R21	108XL	H	9J	266	771	1000	340



NEW

ELECTRIC VEHICLE TYRE

MK317

Mileking®



PRODUCT FEATURES



The succinctly big block pattern design promotes tyre's rigidity capacity and improves irregular anti-wearing.

Tyre shoulder with semi-closed transverse pattern grooves design is balance the noise and drainage performance.

MINI-ELECTRIC VEHICLE TYRE

MK302

Mileking®

PRODUCT FEATURES



The four wide longitudinal drainage grooves increased the space of drainage, which prevent the side sliding with better performance on wetland and provide better security.

The asymmetrical design of pattern is simple and generous. The outside pattern block fastens the response of accelerating and steering, which improved the steering performance.

The design has five channels of pattern block which is optimized and arranged by the computer. The fine slots which arranged evenly in the slop bottom of drainage grooves damaged the noise wave in the channel, it effectively reduced the noise and improved the comfort during traveling.

The 3D slot chamfer enlarged the braking and grounding area. It provides the traction force, enlarged heat emission area and improved the endurance of the tire.

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
215/55R17	98XL	V	7J	226	668	750	340
215/50ZR18	96XL	W	7J	226	673	710	340
225/60R18	104XL	V	6 1/2J	228	727	900	340
235/45ZR18	98XL	Y	8J	236	669	750	340
235/60R18	107XL	V	7J	240	739	975	340
235/45ZR19	99XL	Y	8J	236	695	775	340
235/50R19	99	V	7 1/2J	245	719	775	300
245/45ZR19	102XL	W	8J	243	703	850	340
255/55R19	111XL	V	8J	265	763	1090	340
245/45R20	103XL	V	8J	243	728	875	340
245/50ZR20	105XL	W	7 1/2J	253	754	925	340
255/50R20	109XL	V	8J	265	764	1030	340
255/45ZR20	105XL	Y	8 1/2J	255	738	925	340
265/45ZR21	108XL	W	9J	266	771	1000	340

Size	Load Index /PR	Speed	Standard Rim	Inflatable Section Width (mm)	Inflatable Overall Diameter (mm)	Loading Capacity (single/dual)(kg)	Inflation Pressure(kPa)
135/70R12	65	Q	4.00B	138	495	290	300
145/70R12	69	Q	4.50B	150	509	325	300
155/70R12	73	Q	4.50B	157	523	365	300
165/55R12	68	R	5.00B	170	487	315	300
145/60R13	66	S	4.50B	150	504	300	300
155/65R13	73	Q	4.50B	157	532	365	300
165/55R13	70	S	5.00B	170	512	335	300
165/70R13	79	S	5.00B	170	562	487	300
155/65R14	75	T	4 1/2J	157	558	387	300
155/50R14	67	S	5J	162	512	307	300
165/65R14	79	T	5J	170	570	437	300
165/70R14	81	T	5J	170	588	462	300
155/60R15	74	T	4 1/2J	157	567	375	300
165/60R15	81	H	5 J	170	579	462	340
175/55R15	77	H	5 1/2J	182	573	412	300
165/65R15	81	H	5J	170	595	462	300
175/60R15	81	H	5J	177	591	462	300