ROCKBLADE TIRE

ROCKBLADE TIRE

# PCR · TIRE CATALOGUE

GTIRES U.S.A.

EJECUTIVO DE CUENTAS
Juan Carlos Burgos
+57 312 8675625

ROCKBLADE

# ALWAYS WITH U

# ROCKBLADE

HP | UHP | RFT | VAN | A/S | EV | SUV | WINTER

## CONTENTS



CONTENTS

# ROCK 515

### Silicon-containing tread compound

New Silicon-containing tread compound improves grip on wet road and reduce rolling resistance, provide a safe ride and reduce fuel consumption.


### "Skiving" pattern

"Skiving" pattern design. Stereoscopic straight line "Skiving" pattern design absorb shakes from road, and provide a more comfortable driving.




### Silence design

Silence pitches design. Computer-simulated tread pitches design reduces the driving resonance with excellent quietness and comfortable ride.


### Big block pattern

Big block pattern in the outside. Big block in the outside ensure the great rigidity, handling and sport performance.




| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| NEW 145/70R12 | 69T | 4.50B | 150 | 509 | 325 | 716 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 145/80R12 | 74T | 4.00B | 145 | 537 | 375 | 827 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 155/70R12 | 73T | 4.50B | 157 | 523 | 365 | 805 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 165/70R12 | 77T | 5.00B | 170 | 537 | 412 | 908 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/70R12 | 80T | 5.00B | 177 | 551 | 450 | 992 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 145/70R13 | 71T | 4.50B | 150 | 534 | 345 | 761 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 145/80R13 | 75T | 4.00B | 145 | 562 | 387 | 853 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 155/65R13 | 73T | 4.50B | 157 | 532 | 365 | 805 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 155/70R13 | 75T | 4.50B | 157 | 548 | 387 | 853 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 155/80R13 | 79T | 4.50B | 157 | 578 | 437 | 963 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 165/65R13 | 77T | 5.00B | 170 | 544 | 412 | 908 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 165/80R13 | 83T | 4.50B | 165 | 594 | 487 | 1074 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 165/70R13 | 79T | 5.00B | 170 | 562 | 437 | 963 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/60R13 | 77T | 5.00B | 177 | 540 | 412 | 908 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/65R13 | 80T | 5.00B | 177 | 558 | 450 | 992 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/70R13 | 82T | 5.00B | 177 | 576 | 475 | 1047 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 185/60R13 | 80H | 5.50B | 189 | 552 | 450 | 992 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 185/70R13 | 86T | 5.50B | 189 | 590 | 530 | 1168 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 155/60R14 | 72H | 4 1/2J | 157 | 542 | 355 | 783 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 155/65R14 | 75T | 4 1/2J | 157 | 558 | 387 | 853 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 155/70R14 | 77T | 4 1/2J | 157 | 574 | 412 | 908 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 165/55R14 | 72V | 5J | 170 | 538 | 355 | 783 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 165/60R14 | 75H | 5J | 170 | 554 | 387 | 853 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 165/65R14 | 79T | 5J | 170 | 570 | 437 | 963 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 165/70R14 | 81T | 5J | 170 | 588 | 462 | 1019 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/60R14 | 79H | 5.00B | 177 | 566 | 437 | 963 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/65R14 | 82T | 5J | 177 | 584 | 475 | 1047 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/65R14 | 82H | 5J | 177 | 584 | 475 | 1047 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/65R14 | 86T | 5J | 177 | 584 | 530 | 1168 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 175/70R14 | 84T | 5J | 177 | 602 | 500 | 1102 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 185/55R14 | 80H | 6J | 194 | 560 | 450 | 992 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 185/60R14 | 82H | 5 1/2J | 189 | 578 | 475 | 1047 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 185/65R14 | 86H | 5 1/2J | 189 | 596 | 530 | 1168 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 185/70R14 | 88H | 5 1/2J | 189 | 616 | 560 | 1235 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 195/60R14 | 86H | 6J | 201 | 590 | 530 | 1168 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 195/65R14 | 89H | 6J | 201 | 610 | 580 | 1278 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 195/70R14 | 91H | 6J | 201 | 630 | 615 | 1355 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 205/60R14 | 88H | 6J | 209 | 602 | 560 | 1234 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 205/70R14 | 95H | 6J | 209 | 644 | 690 | 1521 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 215/70R14 | 96H | 6 1/2J | 221 | 658 | 710 | 1565 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 145/65R15 | 72T | 4 1/2J | 150 | 569 | 355 | 783 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 165/50R15 | 73V | 5J | 170 | 547 | 365 | 805 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 165/55R15 | 75V | 5J | 170 | 563 | 387 | 853 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 165/60R15 | 81H XL | 5J | 170 | 579 | 462 | 1019 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 165/65R15 | 81T | 5J | 170 | 595 | 462 | 1019 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 175/50R15 | 75H | 5 1/2J | 182 | 557 | 387 | 853 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/55R15 | 77V | 5 1/2J | 182 | 573 | 412 | 908 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/60R15 | 81H | 5J | 177 | 591 | 462 | 1019 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/65R15 | 84H | 5J | 177 | 609 | 500 | 1102 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 185/55R15 | 82V | 6J | 194 | 585 | 475 | 1047 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 185/60R15 | 88H XL | 5 1/2J | 189 | 603 | 560 | 1235 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 185/65R15 | 88H | 5.5J | 189 | 621 | 560 | 1235 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 195/50R15 | 82V | 6 J | 201 | 577 | 475 | 1047 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 195/55R15 | 85V | 6 J | 201 | 595 | 515 | 1135 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 195/60R15 | 88V | 6J | 201 | 615 | 560 | 1235 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 195/60R15 | 88H | 6J | 201 | 615 | 560 | 1235 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 195/65R15 | 91H | 6J | 201 | 635 | 615 | 1356 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 195/65R15 | 91V | 6J | 201 | 635 | 615 | 1356 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 205/50R15 | 86V | 6 1/2J | 214 | 587 | 530 | 1168 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 205/55R15 | 88V | 6 1/2J | 214 | 607 | 560 | 1235 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 205/60R15 | 91V | 6J | 209 | 627 | 615 | 1355 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 205/65R15 | 94V | 6J | 209 | 647 | 670 | 1477 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 205/65R15 | 94H | 6J | 209 | 647 | 670 | 1477 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 205/70R15 | 96H | 6J | 209 | 669 | 710 | 1565 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 205/75R15 | 97T | 5 1/2J | 203 | 689 | 730 | 1609 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 215/60R15 | 94H | 6 1/2J | 221 | 639 | 670 | 1477 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 215/65R15 | 96H | 6 1/2J | 221 | 661 | 710 | 1565 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 215/70R15 | 98H | 6 1/2J | 221 | 683 | 750 | 1653 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 225/60R15 | 96V | 6 1/2J | 228 | 651 | 710 | 1565 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 225/70R15 | 100H | 6 1/2J | 228 | 697 | 800 | 1764 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/50R16 | 77V | 5 1/2J | 182 | 582 | 412 | 908 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 185/50R16 | 81V | 6J | 194 | 592 | 462 | 1019 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 185/55R16 | 83V | 6J | 194 | 610 | 487 | 1074 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 185/60R16 | 86H | 5 1/2J | 189 | 628 | 530 | 1168 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 195/50R16 | 84V | 6J | 201 | 602 | 500 | 1102 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 195/55R16 | 87V | 6J | 201 | 620 | 545 | 1201 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 195/60R16 | 89H | 6J | 201 | 640 | 580 | 1278 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 205/55R16 | 91V | 6.5J | 214 | 632 | 615 | 1356 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 205/60R16 | 92V | 6J | 209 | 652 | 630 | 1389 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 205/65R16 | 95H | 6J | 209 | 672 | 690 | 1521 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 205/80R16 | 104S XL | 5 1/2J | 203 | 734 | 900 | 1984 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 215/55R16 | 93V | 7J | 226 | 642 | 650 | 1432 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 215/60R16 | 99H XL | 6 1/2J | 221 | 664 | 775 | 1709 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 215/65R16 | 98H | 6 1/2J | 221 | 686 | 750 | 1653 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 225/55R16 | 95V | 7J | 233 | 654 | 690 | 1521 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 225/60R16 | 98H | 6.5J | 228 | 676 | 750 | 1653 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 225/60R16 | 98V | 6.5J | 228 | 676 | 750 | 1653 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 225/65R16 | 100T | 6 1/2J | 228 | 698 | 800 | 1764 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 235/60R16 | 100H | 7 J | 240 | 688 | 800 | 1763 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 235/65R16 | 103T | 7J | 240 | 712 | 875 | 1929 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 215/55R17 | 94V | 7J | 226 | 668 | 670 | 1477 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 215/60R17 | 96T | 6 1/2J | 221 | 690 | 710 | 1565 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 215/65R17 | 99T | 6 1/2J | 221 | 712 | 775 | 1709 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 225/55R17 | 101H | 7J | 233 | 680 | 825 | 1818 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 225/60R17 | 99H | 6 1/2J | 228 | 702 | 775 | 1708 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 225/65R17 | 102H | 6 1/2J | 228 | 724 | 850 | 1873 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 235/65R17 | 104H | 7J | 240 | 738 | 900 | 1984 | 300/44 | 420/A/A | BSW | √ | √ | √ |

New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ROCK 555

## Asymmetrical pattern design, balanced and optimized pattern groove design

This design full of personality can improve excellent handling performance and give people an extraordinary double-sided charm visual experience. And also effectively reduce noise and improve tire comfort.


## Wide longitudinal groove design

The wide longitudinal grooves can drain water quickly, effectively avoiding tire slipping on wet roads and improving wet handling.


## Break through the traditional design of the lateral groove on the inner shoulder

It can reduce the rigidity of the tire shoulders, effectively suppress eccentric wear, block the transmission of noise from the central block, reduce tire noise, and bring excellent driving comfort.


## Special hook groove design on outer shoulder

It can effectively reduce heat generation at the shoulder, reduce resonance during driving, and effectively reduce tire noise.




| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| NEW 145/70R12 | 69T | 4.50B | 150 | 509 | 325 | 716 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 145/80R12 | 74T | 4.00B | 145 | 537 | 375 | 827 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 155/70R12 | 73T | 4.50B | 157 | 523 | 365 | 805 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 165/70R12 | 77T | 5.00B | 170 | 537 | 412 | 908 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 175/70R12 | 80T | 5.00B | 177 | 551 | 450 | 992 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 145/80R13 | 75T | 4.00B | 145 | 562 | 387 | 853 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 155/65R13 | 73T | 4.50B | 157 | 532 | 365 | 805 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 155/70R13 | 75T | 4.50B | 157 | 548 | 387 | 853 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 155/80R13 | 79T | 4.50B | 157 | 578 | 437 | 963 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 165/65R13 | 77T | 5.00B | 170 | 544 | 412 | 908 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 165/70R13 | 79T | 5.00B | 170 | 562 | 437 | 963 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 165/80R13 | 83T | 4.50B | 165 | 594 | 487 | 1074 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 175/60R13 | 77T | 5.00B | 177 | 540 | 412 | 908 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 175/70R13 | 82T | 5.00B | 177 | 576 | 475 | 1047 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 185/60R13 | 80H | 5.50B | 189 | 552 | 450 | 992 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 185/70R13 | 86T | 5.50B | 189 | 590 | 530 | 1168 | 300/44 | 400/A/A | BSW | √ | √ | √ |

| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 155/65R14 | 75T | 4.50B | 157 | 558 | 387 | 853 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 155/70R14 | 77T | 4 1/2J | 157 | 574 | 412 | 908 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 165/55R14 | 72V | 5J | 170 | 538 | 355 | 783 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 165/60R14 | 75H | 5.00B | 170 | 554 | 387 | 853 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 165/65R14 | 79T | 5J | 170 | 570 | 437 | 963 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 165/70R14 | 85TXL | 5.00B | 170 | 588 | 515 | 1135 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 165/70R14 | 81T | 5.00B | 170 | 588 | 462 | 1019 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 175/60R14 | 79H | 5.00B | 177 | 566 | 437 | 963 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 175/65R14 | 86TXL | 5.00B | 177 | 584 | 530 | 1168 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 175/65R14 | 82H | 5.00B | 177 | 584 | 475 | 1047 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 175/70R14 | 88TXL | 5.00B | 177 | 602 | 560 | 1235 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 175/70R14 | 84T | 5.00B | 177 | 602 | 500 | 1102 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 185/50R14 | 77V | 6J | 194 | 542 | 412 | 908 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 185/55R14 | 80H | 6J | 194 | 560 | 450 | 992 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 185/60R14 | 82H | 5 1/2J | 189 | 578 | 475 | 1047 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 185/65R14 | 86H | 5 1/2J | 189 | 596 | 530 | 1168 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 185/70R14 | 88T | 5 1/2J | 189 | 616 | 560 | 1235 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 195/60R14 | 86H | 6 J | 201 | 590 | 530 | 1168 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 195/65R14 | 89H | 6J | 201 | 610 | 580 | 1279 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 195/70R14 | 91H | 6 J | 201 | 630 | 615 | 1355 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 205/60R14 | 88H | 6 J | 209 | 602 | 560 | 1234 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 205/70R14 | 95H | 6 J | 209 | 644 | 690 | 1521 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 215/70R14 | 96H | 6 1/2J | 221 | 658 | 710 | 1565 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 155/60R15 | 74T | 4.50B | 157 | 567 | 375 | 827 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 165/50R15 | 73V | 5J | 170 | 547 | 365 | 805 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 165/55R15 | 75V | 5J | 170 | 563 | 387 | 853 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 165/60R15 | 81HXL | 5.00B | 170 | 579 | 462 | 1019 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 165/65R15 | 81H | 5J | 170 | 595 | 462 | 1019 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 175/50R15 | 75H | 5 1/2J | 182 | 557 | 387 | 853 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 175/55R15 | 77H | 5 1/2J | 182 | 573 | 412 | 908 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 175/60R15 | 81H | 5J | 177 | 591 | 462 | 1019 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 175/65R15 | 84H | 5J | 177 | 609 | 500 | 1102 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 185/55R15 | 82V | 6J | 194 | 585 | 475 | 1047 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 185/60R15 | 88HXL | 5 1/2J | 189 | 603 | 560 | 1235 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 185/60R15 | 84H | 5 1/2J | 189 | 603 | 500 | 1102 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 185/65R15 | 88H | 5 1/2J | 189 | 621 | 560 | 1235 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 195/45R15 | 82VXL | 6 1/2J | 195 | 557 | 475 | 1047 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 195/50R15 | 82V | 6J | 201 | 577 | 475 | 1047 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 195/55R15 | 85V | 6J | 201 | 595 | 515 | 1135 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 195/60R15 | 88V | 6J | 201 | 615 | 560 | 1235 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 195/60R15 | 88H | 6J | 201 | 615 | 560 | 1235 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 195/65R15 | 95TXL | 6J | 201 | 635 | 690 | 1521 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 195/65R15 | 91V | 6J | 201 | 635 | 615 | 1356 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 205/50R15 | 86V | 6 1/2J | 214 | 587 | 530 | 1168 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 205/55R15 | 88V | 6 1/2J | 214 | 607 | 560 | 1235 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 205/60R15 | 91V | 6J | 209 | 627 | 615 | 1356 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 205/65R15 | 94V | 6J | 209 | 647 | 670 | 1477 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 205/70R15 | 96H | 6 J | 209 | 669 | 710 | 1565 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 215/65R15 | 96H | 6 1/2J | 221 | 661 | 710 | 1565 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 215/70R15 | 98H | 6 1/2J | 221 | 683 | 750 | 1653 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 225/60R15 | 96V | 6 1/2J | 228 | 651 | 710 | 1565 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 225/70R15 | 100H | 6 1/2J | 228 | 697 | 800 | 1764 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 175/50R16 | 77V | 5 1/2J | 182 | 582 | 412 | 908 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 185/50R16 | 81V | 6J | 194 | 592 | 462 | 1019 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 185/55R16 | 87VXL | 6J | 194 | 610 | 545 | 1202 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| NEW 185/60R16 | 86H | 5 1/2J | 189 | 628 | 530 | 1168 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 195/50R16 | 88VXL | 6J | 201 | 602 | 560 | 1235 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 195/55R16 | 91VXL | 6J | 201 | 620 | 615 | 1356 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| NEW 195/60R16 | 89H | 6 J | 201 | 640 | 580 | 1278 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 205/50R16 | 91WXL | 6 1/2J | 214 | 612 | 615 | 1356 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 205/55R16 | 94WXL | 6 1/2J | 214 | 632 | 670 | 1477 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 205/55R16 | 91V | 6 1/2J | 214 | 632 | 615 | 1356 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 205/60R16 | 96VXL | 6J | 209 | 652 | 710 | 1565 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 205/60R16 | 92V | 6J | 209 | 652 | 630 | 1389 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 205/65R16 | 95H | 6 J | 209 | 672 | 690 | 1521 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 215/55R16 | 97WXL | 7J | 226 | 642 | 730 | 1609 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 215/60R16 | 99HXL | 6 1/2J | 221 | 664 | 775 | 1709 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 215/60R16 | 95V | 6 1/2J | 221 | 664 | 690 | 1521 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 215/65R16 | 98H | 6 1/2J | 221 | 686 | 750 | 1653 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 225/55R16 | 99WXL | 7J | 233 | 654 | 775 | 1709 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 225/60R16 | 102VXL | 6 1/2J | 228 | 676 | 850 | 1874 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| NEW 225/65R16 | 100T | 6 1/2J | 228 | 698 | 800 | 1764 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 235/60R16 | 100H | 7 J | 240 | 688 | 800 | 1763 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 235/65R16 | 103T | 7J | 240 | 712 | 875 | 1929 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 215/60R17 | 96T | 6 1/2J | 221 | 690 | 710 | 1565 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 215/65R17 | 99T | 6 1/2J | 221 | 712 | 775 | 1709 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 225/60R17 | 99H | 6 1/2J | 228 | 702 | 775 | 1708 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 225/65R17 | 102H | 6 1/2J | 228 | 724 | 850 | 1873 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| NEW 235/65R17 | 104H | 7J | 240 | 738 | 900 | 1984 | 300/44 | 400/A/A | BSW | √ | √ | √ |

HP

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ROCK 525

## Asymmetric tread pattern

Asymmetric tread pattern design and functionally differed in medial and lateral sidewall improve steering performance in wet road conditions, and ensure high-speed stability.




## Silicon-containing tread compound

New silicon-containing tread compound enhance grip in wet road and reduce rolling resistance.


## Low-noise design

Creative tread grooves' fine lines design effectively reduce noise at high-speed driving.


## Anti-slip design

A mass of steel sheets and grooves design provide great grip ability and driving performance on wetland.




| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 195/45R16 | 84V XL | 6 1/2J | 195 | 582 | 500 | 1102 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 205/45R16 | 87W XL | 7 J | 206 | 590 | 545 | 1201 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 205/50R16 | 91W XL | 6 1/2J | 214 | 612 | 615 | 1356 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 205/55R16 | 94W XL | 6 1/2J | 214 | 632 | 670 | 1477 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 215/40ZR16 | 86W XL | 7 1/2J | 218 | 578 | 530 | 1168 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 215/45R16 | 90V XL | 7J | 213 | 600 | 600 | 1323 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 215/55ZR16 | 97W XL | 7J | 226 | 642 | 730 | 1609 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 225/50ZR16 | 96W XL | 7J | 233 | 632 | 710 | 1565 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 225/55R16 | 99W XL | 7 J | 233 | 654 | 775 | 1709 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| NEW 165/35R17 | 68VXL | 6 J | 170 | 547 | 315 | 694 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 165/40R17 | 72V | 6 J | 170 | 564 | 355 | 783 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| NEW 165/45R17 | 76V XL | 5 1/2J | 165 | 579 | 400 | 882 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 185/35R17 | 82V | 6 1/2J | 183 | 562 | 475 | 1047 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| NEW 185/40R17 | 78V XL | 6 1/2J | 188 | 580 | 425 | 937 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 195/45ZR17 | 85W XL | 6 1/2J | 195 | 608 | 515 | 1135 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 205/40R17 | 84W XL | 7 1/2J | 212 | 596 | 500 | 1102 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 205/45R17 | 88W XL | 7 J | 206 | 616 | 560 | 1235 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 205/50R17 | 93W XL | 6 1/2J | 214 | 638 | 650 | 1433 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 205/55ZR17 | 95W XL | 6 1/2J | 214 | 658 | 690 | 1521 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 215/40ZR17 | 87W XL | 7 1/2J | 218 | 604 | 545 | 1201 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 215/45R17 | 91W XL | 7 J | 213 | 626 | 615 | 1356 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 215/50R17 | 95W XL | 7 J | 226 | 648 | 690 | 1521 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 215/55R17 | 98W XL | 7 J | 226 | 668 | 750 | 1653 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 225/45R17 | 94W XL | 7 1/2J | 225 | 634 | 670 | 1477 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 225/50R17 | 98W XL | 7 J | 233 | 658 | 750 | 1653 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 225/55R17 | 101W XL | 7 J | 233 | 680 | 825 | 1819 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 235/45R17 | 97W XL | 8 J | 236 | 644 | 730 | 1609 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 235/50R17 | 100V | 7 1/2J | 245 | 668 | 800 | 1764 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 235/55ZR17 | 103W | 7 1/2J | 245 | 690 | 875 | 1929 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 245/40ZR17 | 95W XL | 8 1/2J | 248 | 628 | 690 | 1521 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 245/45ZR17 | 99W | 8 J | 243 | 652 | 775 | 1709 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 185/35R18 | 83V | 6 1/2J | 183 | 587 | 487 | 1074 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 215/35ZR18 | 84W XL | 7 1/2J | 218 | 607 | 500 | 1102 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 215/40ZR18 | 89W XL | 7 1/2J | 218 | 629 | 580 | 1279 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 215/45ZR18 | 93W XL | 7J | 213 | 651 | 650 | 1433 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 215/55R18 | 99V | 7 J | 226 | 693 | 775 | 1709 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 225/40R18 | 92W XL | 8 J | 230 | 637 | 630 | 1389 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 225/45R18 | 95W XL | 7 1/2J | 225 | 659 | 690 | 1521 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 225/55R18 | 102V | 7 J | 233 | 705 | 850 | 1874 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 235/40R18 | 95W XL | 8 1/2J | 241 | 645 | 690 | 1521 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 235/45ZR18 | 98W XL | 8 J | 236 | 669 | 750 | 1653 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 235/50R18 | 97V | 7 1/2J | 245 | 693 | 730 | 1609 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 235/55R18 | 104V | 7 1/2J | 245 | 715 | 900 | 1984 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 245/40R18 | 97W XL | 8 1/2J | 248 | 653 | 730 | 1609 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 245/45R18 | 100W XL | 8 J | 243 | 677 | 800 | 1764 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 245/50ZR18 | 104W | 7 1/2J | 253 | 703 | 900 | 1984 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 255/35ZR18 | 94W XL | 9J | 260 | 635 | 670 | 1477 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 255/40ZR18 | 99W XL | 9J | 260 | 661 | 775 | 1709 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 255/45ZR18 | 103W | 8 1/2J | 255 | 687 | 875 | 1929 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 255/55R18 | 109V | 8 J | 265 | 737 | 1030 | 2271 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 265/35ZR18 | 97W XL | 9 1/2J | 271 | 643 | 730 | 1609 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 275/35ZR18 | 99W XL | 9 1/2J | 278 | 649 | 775 | 1709 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 215/35ZR19 | 85W XL | 7 1/2J | 218 | 633 | 515 | 1135 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 225/35ZR19 | 88W XL | 8J | 230 | 641 | 560 | 1235 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 225/45ZR19 | 96W XL | 7 1/2J | 225 | 685 | 710 | 1565 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 225/55R19 | 99V | 7J | 233 | 731 | 775 | 1709 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 235/35ZR19 | 91W XL | 8 1/2J | 241 | 647 | 615 | 1356 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 235/40ZR19 | 96W | 8 1/2J | 241 | 671 | 710 | 1565 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 235/45ZR19 | 99W XL | 8J | 236 | 695 | 775 | 1709 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 235/50ZR19 | 103W XL | 7 1/2J | 245 | 719 | 875 | 1929 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 235/55R19 | 105V XL | 7 1/2J | 245 | 741 | 925 | 2039 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 245/35ZR19 | 93W XL | 8 1/2J | 248 | 655 | 650 | 1433 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 245/40ZR19 | 98W XL | 8 1/2J | 248 | 679 | 750 | 1653 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 245/45R19 | 102W XL | 8 J | 243 | 703 | 850 | 1874 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 245/55R19 | 107V XL | 7 1/2J | 253 | 753 | 975 | 2149 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 255/30ZR19 | 91Y XL | 9J | 260 | 637 | 615 | 1356 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 255/35ZR19 | 96W XL | 9J | 260 | 661 | 710 | 1565 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 255/40ZR19 | 100W XL | 9J | 260 | 687 | 800 | 1764 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 255/45ZR19 | 104W XL | 8 1/2J | 255 | 713 | 900 | 1984 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 255/50R19 | 107V XL | 8J | 265 | 739 | 975 | 2149 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 275/30ZR19 | 96W XL | 9 1/2J | 278 | 649 | 710 | 1565 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 275/35ZR19 | 100Y XL | 9 1/2J | 278 | 675 | 800 | 1764 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 275/40ZR19 | 105W XL | 9 1/2J | 278 | 703 | 925 | 2039 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 285/45R19 | 111V XL | 9 1/2J | 285 | 739 | 1090 | 2403 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 205/35R20 | 84V | 7 1/2J | 212 | 652 | 500 | 1102 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 225/35ZR20 | 90W | 8 J | 230 | 666 | 600 | 1323 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 245/35ZR20 | 95W XL | 8 1/2J | 248 | 680 | 690 | 1521 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 245/40ZR20 | 99W XL | 8 1/2J | 248 | 704 | 775 | 1709 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 255/35ZR20 | 97W XL | 9J | 260 | 686 | 730 | 1609 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 275/30ZR20 | 97W XL | 9 1/2J | 278 | 674 | 730 | 1609 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 275/35ZR20 | 102W XL | 9 1/2J | 278 | 700 | 850 | 1874 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 265/45ZR21 | 108W XL | 9J | 266 | 771 | 1000 | 2205 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 275/45ZR21 | 110W XL | 9J | 273 | 781 | 1060 | 2337 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 295/35ZR21 | 107W XL | 10 1/2J | 301 | 739 | 975 | 2149 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 295/40ZR21 | 111W XL | 10 1/2J | 301 | 769 | 1090 | 2403 | 340/50 | 400/A/A | BSW | √ | √ | √ |

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ROCK 535

## "V-shaped" pattern design

30 multi-angle "V-shaped" pattern design ensure high-speed handling and stability in straight lines and cornering.




## "Y -shaped" directional pattern design

"Y-shaped" directional pattern design provides excellent horizontal or vertical drainage performance.




## Shoulder design

Open shoulder design self-cleans the slush in the grooves.


## Tread pattern design

Central longitudinal ribs increase the contact area with road surface, and enhance braking performance in any road conditions.




| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 255/55R19 | 111V | 8J | 265 | 763 | 1090 | 2403 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 265/50R20 | 111V | 8 1/2J | 277 | 774 | 1090 | 2403 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 275/40ZR20 | 106W XL | 9 1/2J | 278 | 728 | 950 | 2094 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 275/45R20 | 110V XL | 9J | 273 | 756 | 1060 | 2337 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 275/55R20 | 117V XL | 8 1/2J | 284 | 810 | 1285 | 2833 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 275/60R20 | 119H XL | 8J | 279 | 838 | 1360 | 2998 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 285/50R20 | 116V | 9J | 297 | 794 | 1250 | 2756 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 295/45ZR20 | 114W | 10J | 296 | 774 | 1180 | 2601 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 265/35ZR22 | 102W XL | 9 1/2J | 271 | 745 | 850 | 1874 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 265/40R22 | 106V XL | 9 1/2J | 271 | 771 | 950 | 2094 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 285/35ZR22 | 106W | 10J | 290 | 759 | 950 | 2094 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 285/40R22 | 110V | 10J | 290 | 787 | 1060 | 2337 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 295/30ZR22 | 103W | 10 1/2J | 301 | 737 | 875 | 1929 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 305/40R22 | 114V XL | 11J | 313 | 803 | 1180 | 2601 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 275/25ZR24 | 96W | 10J | 283 | 748 | 710 | 1565 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 295/35ZR24 | 110W | 10 1/2J | 301 | 816 | 1060 | 2337 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 305/35ZR24 | 112W | 11J | 313 | 824 | 1120 | 2469 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 255/50R20 | 109V XL | 8J | 265 | 764 | 1030 | 2271 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 255/55R20 | 110V XL | 8J | 265 | 788 | 1060 | 2337 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 315/35ZR20 | 110W XL | 11J | 320 | 728 | 1060 | 2337 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 275/40ZR22 | 107W XL | 9 1/2J | 275 | 779 | 975 | 2149 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 285/45R22 | 114V XL | 9 1/2J | 285 | 815 | 1180 | 2601 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 305/45R22 | 118V XL | 10J | 303 | 833 | 1320 | 2910 | 340/50 | 400/A/A | BSW | √ | √ | √ |

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ROCK 566 (RFT)

## High-strength bead structure

High-strength bead structure design prevents the tires from falling off the ring when driving at 0 air pressure, and improves the driving durability.


## Apex Low-heat-generation formula design

Low-heat-generation formula design of apex can effectively reduce the heat generated when the tire is running under pressure and improve the durability.




## Sidewall with high-strength cord reinforcement layer

Sidewall adopts a high-strength cord reinforcement layer to increase the sidewall strength, maintain good thermal stability under pressure shortage, and improve low-pressure durability.


## Sidewall with dual composite sidewall support rubber

Sidewall adopts dual composite sidewall support rubber, which has high support strength and good buffering performance. Unique formula design can improve sidewall strength and reduce heat generation, increasing sidewall durability and providing safe driving.


| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 205/45ZRF17 | 88W XL | 7J | 206 | 616 | 560 | 1235 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 205/50ZRF17 | 93W XL | 6 1/2J | 214 | 638 | 650 | 1433 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 225/45ZRF17 | 94W XL | 7 1/2J | 225 | 634 | 670 | 1477 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 225/50ZRF17 | 98W XL | 7J | 233 | 658 | 750 | 1653 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 225/55RF17 | 97V | 7J | 233 | 680 | 730 | 1609 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 235/55RF17 | 99V | 7 1/2J | 245 | 690 | 775 | 1709 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 245/40ZRF17 | 95W XL | 8 1/2J | 248 | 628 | 690 | 1521 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 245/45ZRF17 | 99W XL | 8 J | 243 | 652 | 775 | 1709 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 215/55ZRF18 | 99W XL | 7J | 226 | 693 | 775 | 1709 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 225/40ZRF18 | 92W XL | 8 J | 230 | 637 | 630 | 1389 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 225/45ZRF18 | 95W XL | 7 1/2J | 225 | 659 | 690 | 1521 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 225/50ZRF18 | 95W | 7J | 233 | 683 | 690 | 1521 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 235/50RF18 | 97V | 7 1/2J | 245 | 693 | 730 | 1609 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 235/55RF18 | 100V | 7 1/2J | 245 | 715 | 800 | 1764 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 245/40ZRF18 | 97W XL | 8 1/2J | 248 | 653 | 730 | 1609 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 245/45ZRF18 | 100W XL | 8 J | 243 | 677 | 800 | 1764 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 245/50RF18 | 100V | 7 1/2J | 253 | 703 | 800 | 1764 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 255/35ZRF18 | 94W XL | 9 J | 260 | 635 | 670 | 1477 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 255/40ZRF18 | 99W XL | 9J | 260 | 661 | 775 | 1709 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 255/45ZRF18 | 99W | 8 1/2J | 255 | 687 | 775 | 1709 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 255/55RF18 | 105V | 8J | 265 | 737 | 925 | 2039 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 275/40ZRF18 | 99W | 9 1/2J | 278 | 677 | 775 | 1709 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 225/35ZRF19 | 84W | 8J | 230 | 641 | 500 | 1102 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 225/40ZRF19 | 93W XL | 8J | 230 | 663 | 650 | 1433 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 235/35ZRF19 | 91W XL | 8 1/2J | 241 | 647 | 615 | 1356 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 235/45ZRF19 | 95W | 8J | 236 | 695 | 690 | 1521 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 235/50RF19 | 99V | 7 1/2J | 245 | 719 | 775 | 1709 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 235/55RF19 | 101V | 7 1/2J | 245 | 741 | 825 | 1819 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 245/35ZRF19 | 93W XL | 8 1/2J | 248 | 655 | 650 | 1433 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 245/40ZRF19 | 98W XL | 8 1/2J | 248 | 679 | 750 | 1653 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 245/45ZRF19 | 98W | 8J | 243 | 703 | 750 | 1653 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 245/50RF19 | 105V XL | 7 1/2J | 253 | 729 | 925 | 2039 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 255/35ZRF19 | 96W XL | 9J | 260 | 661 | 710 | 1565 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 255/45ZRF19 | 100W | 8 1/2J | 255 | 713 | 800 | 1764 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 255/50RF19 | 103V | 8J | 265 | 739 | 875 | 1929 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 275/35ZRF19 | 100W XL | 9 1/2J | 278 | 675 | 800 | 1764 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 275/40ZRF19 | 105W XL | 9 1/2J | 278 | 703 | 925 | 2039 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 275/40ZRF19 | 101W | 9 1/2J | 278 | 703 | 825 | 1819 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 285/45RF19 | 107V | 9 1/2J | 285 | 739 | 975 | 2149 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 245/35ZRF20 | 95W XL | 8 1/2J | 248 | 680 | 690 | 1521 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 245/40ZRF20 | 99W XL | 8 1/2J | 248 | 704 | 775 | 1709 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 245/45ZRF20 | 103W XL | 8J | 243 | 728 | 875 | 1929 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 255/45RF20 | 101V | 8 1/2J | 255 | 738 | 825 | 1819 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 275/30ZRF20 | 97W XL | 9 1/2J | 278 | 674 | 730 | 1609 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 275/35ZRF20 | 102W XL | 9 1/2J | 278 | 700 | 850 | 1874 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 275/40ZRF20 | 102W | 9 1/2J | 278 | 728 | 850 | 1874 | 300/44 | 300/A/A | BSW | √ | √ | √ |
| 315/35ZRF20 | 110W XL | 11 J | 320 | 728 | 1060 | 2337 | 340/50 | 300/A/A | BSW | √ | √ | √ |
| 315/35ZRF20 | 106W | 11 J | 320 | 728 | 950 | 2094 | 300/44 | 300/A/A | BSW | √ | √ | √ |

COMING...
RFT

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ROCK 866C E1

## Pressure evenly distributed high wear technology

The pressure distribution technology with balanced grounding area, combined with high land-sea ratio pattern and specialized light truck tread compound design, makes the tire more good tread wear and economical.





## High drainage performance

The design of three straight circumferential grooves enables the tire to drain more quickly at high speeds and has better wetgrip performance.


## Good grip performance and good handling

The shoulder curved steel groove and the middle steel groove are matched and optimized for better load-bearing capacity, better tire grip performance, and better handling performance.




## Excellent durability performance

The widened shoulder block design provides better rigidity, and the wide straight groove design under the shoulder reduces the flexibility, resulting in better heat dissipation and longer mileage.




## Excellent seasonal performance

The optimized layout design of the center staggered steel groove provides higher ground adhesion in the central area of the tread, making it suitable for use in all seasons.


| Size | LI/SI | PR | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 185R14C | 102/100R | 8PR | 5 1/2J | 188 | 650 | 850/800 | 1874/1764 | 450/65 | BSW | √ | √ | √ |
| 195R14C | 106/104R | 8PR | 5 1/2J | 198 | 666 | 950/900 | 2094/1984 | 450/65 | BSW | √ | √ | √ |
| 195R15C | 106/104R | 8PR | 5 1/2J | 198 | 690 | 950/900 | 2094/1984 | 450/65 | BSW | √ | √ | √ |
| 195/70R15C | 104/102R | 8PR | 6J | 201 | 655 | 900/850 | 1984/1874 | 450/65 | BSW | √ | √ | √ |
| 205/65R15C | 102/100R | 6PR | 6J | 209 | 647 | 850/800 | 1874/1764 | 375/54 | BSW | √ | √ | √ |
| 205/70R15C | 106/104R | 8PR | 6J | 209 | 669 | 950/900 | 2094/1984 | 450/65 | BSW | √ | √ | √ |
| 215/65R15C | 104/102R | 6PR | 6 1/2J | 221 | 661 | 900/850 | 1984/1874 | 375/54 | BSW | √ | √ | √ |
| 215/70R15C | 109/107R | 8PR | 6 1/2J | 221 | 683 | 1030/975 | 2271/2149 | 450/65 | BSW | √ | √ | √ |
| 225/70R15C | 112/110R | 8PR | 6 1/2J | 228 | 697 | 1120/1060 | 2469/2337 | 450/65 | BSW | √ | √ | √ |
| 185/75R16C | 104/102R | 8PR | 5J | 184 | 684 | 900/850 | 1984/1874 | 475/69 | BSW | √ | √ | √ |
| 195/60R16C | 99/97T | 6PR | 6J | 201 | 640 | 775/730 | 1709/1609 | 375/54 | BSW | √ | √ | √ |
| 195/65R16C | 104/102R | 8PR | 6J | 201 | 660 | 900/850 | 1984/1874 | 475/69 | BSW | √ | √ | √ |
| 195/75R16C | 107/105R | 8PR | 5 1/2J | 196 | 698 | 975/925 | 2149/2039 | 475/69 | BSW | √ | √ | √ |
| 205/65R16C | 107/105R | 8PR | 6J | 209 | 672 | 975/925 | 2149/2039 | 475/69 | BSW | √ | √ | √ |
| 205/75R16C | 113/111R | 10PR | 5 1/2J | 203 | 714 | 1150/1090 | 2535/2403 | 525/76 | BSW | √ | √ | √ |
| 215/60R16C | 103/101T | 6PR | 6 1/2J | 221 | 664 | 875/825 | 1929/1819 | 375/54 | BSW | √ | √ | √ |
| 215/65R16C | 109/107R | 8PR | 6 1/2J | 221 | 686 | 1030/975 | 2271/2149 | 475/69 | BSW | √ | √ | √ |
| 215/75R16C | 116/114R | 10PR | 6J | 216 | 728 | 1250/1180 | 2756/2601 | 525/76 | BSW | √ | √ | √ |
| 225/65R16C | 112/110R | 8PR | 6 1/2J | 228 | 698 | 1120/1060 | 2469/2337 | 475/69 | BSW | √ | √ | √ |
| 225/75R16C | 121/120R | 10PR | 6J | 223 | 744 | 1450/1400 | 3197/3086 | 575/83 | BSW | √ | √ | √ |
| 235/65R16C | 115/113R | 8PR | 7J | 240 | 712 | 1215/1150 | 2679/2535 | 475/69 | BSW | √ | √ | √ |
| 215/60R17C | 109/107T | 8PR | 6 1/2J | 221 | 690 | 1030/975 | 2271/2149 | 475/69 | BSW | √ | √ | √ |

VAN

* New Developing Sizes / The Labeling Information Is Subject To Change Without Notice.

# ROCK 838C

## Silence design

Silence design of steel sheets. 700 pieces sipes divide the "Z" type tread blocks into small pieces greatly reduce tire noise and improve driving comfort, enjoying quiet and comfortable effect that same series tires cannot bring.


## Simulate Design

Simulate double "Y" tread pattern design improve grip performance without reducing tread blocks' rigidity, shorten braking distance, and improve driving safety.


## Zigzag grooves

Zigzag pattern grooves design. Classic zigzag grooves provide excellent driving stability, and assure a smooth and comfortable ride.




## White sidewall design

White sidewall. The white sidewall with 20mm width design is beautiful and dignified, and it is suitable for car modification.


| Size | LI/SI | PR | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 165/70R14C | 89/87R | 6PR | 5J | 170 | 588 | 580/545 | 1279/1202 | 375/54 | BSW | √ | √ | √ |
| 175/65R14C | 90/88R | 6PR | 5J | 177 | 584 | 600/560 | 1323/1235 | 375/54 | BSW | √ | √ | √ |
| 185R14C | 102/100R | 8PR | 5 1/2J | 188 | 650 | 850/800 | 1875/1765 | 450/65 | BSW | √ | √ | √ |
| 185R14C | 102/100R | 8PR | 5 1/2J | 188 | 650 | 850/800 | 1875/1765 | 450/65 | WSW | √ | √ | √ |
| 195R14C | 106/104R | 8PR | 5 1/2J | 198 | 666 | 950/900 | 2094/1984 | 450/65 | BSW | √ | √ | √ |
| 195R14C | 106/104R | 8PR | 5 1/2J | 198 | 666 | 950/900 | 2094/1984 | 450/65 | WSW | √ | √ | √ |
| 205/75R14C | 109/107R | 8PR | 5 1/2J | 203 | 664 | 1030/975 | 2271/2149 | 475/69 | BSW/WSW | √ | √ | √ |
| 205R14C | 109/107R | 8PR | 6J | 208 | 686 | 1030/975 | 2271/2150 | 450/65 | BSW | √ | √ | √ |
| 215/75R14C | 112/110R | 8PR | 6J | 216 | 678 | 1120/1060 | 2469/2337 | 475/69 | BSW | √ | √ | √ |
| 215R14C | 112/110R | 8PR | 6J | 218 | 700 | 1120/1060 | 2469/2337 | 450/65 | BSW | √ | √ | √ |
| 185R15C | 103/102R | 8PR | 5 1/2J | 188 | 674 | 875/850 | 1929/1874 | 450/65 | BSW | √ | √ | √ |
| 195/70R15C | 104/102R | 8PR | 6J | 201 | 655 | 900/850 | 1984/1874 | 450/65 | BSW | √ | √ | √ |
| 195R15C | 106/104R | 8PR | 5 1/2J | 196 | 693 | 950/900 | 2094/1984 | 450/65 | WSW | √ | √ | √ |
| 195R15C | 106/104R | 8PR | 5 1/2J | 196 | 693 | 950/900 | 2094/1984 | 450/65 | BSW | √ | √ | √ |
| 205/70R15C | 106/104R | 8PR | 6 | 209 | 669 | 950/900 | 2094/1984 | 450/65 | BSW | √ | √ | √ |
| 205/75R15C | 109/107R | 8PR | 5 1/2J | 203 | 689 | 1030/975 | 2271/2149 | 475/69 | WSW | √ | √ | √ |
| 215/65R15C | 104/102R | 6PR | 6 1/2 | 221 | 661 | 900/850 | 1984/1874 | 375/54 | BSW | √ | √ | √ |
| 215/70R15C | 104/101R | 8PR | 6 1/2J | 221 | 683 | 900/825 | 1984/1819 | 450/65 | BSW | √ | √ | √ |
| 225/70R15C | 112/110R | 8PR | 6 1/2 | 228 | 697 | 1120/1060 | 2469/2337 | 450/65 | BSW | √ | √ | √ |
| 175/75R16C | 101/99R | 8PR | 5J | 177 | 668 | 825/775 | 1819/1705 | 475/69 | BSW | √ | √ | √ |
| NEW 185/75R16C | 104/102R | 8PR | 5J | 184 | 684 | 900/850 | 1984/1874 | 475/69 | BSW | √ | √ | √ |
| 195/60R16C | 99/97T | 6PR | 6 | 201 | 640 | 775/730 | 1709/1609 | 375/54 | BSW | √ | √ | √ |
| NEW 195/65R16C | 104/102R | 8PR | 6J | 201 | 660 | 900/850 | 1984/1874 | 475/69 | BSW | √ | √ | √ |
| 195/75R16C | 107/105R | 8PR | 5 1/2J | 196 | 698 | 975/925 | 2149/2039 | 475/69 | BSW | √ | √ | √ |
| 205/65R16C | 107/105R | 8PR | 6J | 209 | 672 | 975/925 | 2149/2039 | 475/69 | BSW | √ | √ | √ |
| 205/75R16C | 110/108R | 8PR | 5 1/2 | 203 | 714 | 1060/1000 | 2337/2204 | 475/69 | BSW | √ | √ | √ |
| 215/60R16C | 103/101T | 6PR | 6 1/2 | 221 | 664 | 875/825 | 1929/1819 | 375/54 | BSW | √ | √ | √ |
| 215/65R16C | 109/107R | 8PR | 6 1/2J | 221 | 686 | 1030/975 | 2271/2149 | 475/69 | BSW | √ | √ | √ |
| 215/70R16C | 108/106R | 6PR | 6 1/2J | 221 | 708 | 1000/950 | 2205/2094 | 375/54 | BSW | √ | √ | √ |
| 215/75R16C | 116/114R | 10PR | 6J | 216 | 728 | 1250/1180 | 2756/2601 | 525/76 | BSW | √ | √ | √ |
| 225/65R16C | 112/110R | 8PR | 6 1/2J | 228 | 698 | 1120/1060 | 2469/2337 | 475/69 | BSW | √ | √ | √ |
| 225/75R16C | 116/114R | 8PR | 6J | 223 | 744 | 1250/1180 | 2756/2601 | 475/69 | BSW | √ | √ | √ |
| 235/65R16C | 115/113R | 8PR | 7J | 240 | 712 | 1215/1150 | 2679/2535 | 475/69 | BSW | √ | √ | √ |
| 215/60R17C | 109/107T | 8PR | 6 1/2J | 221 | 690 | 1030/975 | 2271/2149 | 475/69 | BSW | √ | √ | √ |

New Developing Sizes / The Labeling Information Is Subject To Change Without Notice.

# ROCK 818


## Zigzag grooves

Zigzag groove design. Zigzag and trailed main grooves enhance the strong traction; improve the drainage and anti-skip performance. Large slope tread grooves design provides excellent stone removing performance.




## 3D steel sheets

3D interlaced steel sheets design. 3D interlaced steel sheets increase the grip ability, braking force and safety of driving.




## Closed shoulder

Coherent closed shoulder design. Enhanced rid and coherent closed block design on shoulder prevents the leaning-grind caused by heavy rigidity, and remain the high-speed turning agility at the same time.




## Irregular pattern

Irregular pattern and multi-pitch design brings silence and comfortable ride.




| Size | LI/SI | PR | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 145R12C | 86/84Q | 8PR | 4.00B | 145 | 537 | 530/500 | 1168/1102 | 450/65 | BSW | √ | √ | √ |
| 155R12LT/C | 88/86S | 8PR | 4.50B | 157 | 553 | 560/530 | 1235/1168 | 450/65 | BSW | √ | √ | √ |
| 155/70R12LT | 104/102R | 12PR | 4.50B | 157 | 523 | 900/850 | 1984/1874 | 650 | BSW | √ | √ | √ |
| NEW 5.00R12LT | 83/81Q | 8PR | 3.50B | 143 | 568 | 487/462 | 1074/1019 | 450/65 | BSW | √ | √ | √ |
| NEW 5.50R12LT | 92/90Q | 10PR | 3.50B | 160 | 595 | 630/600 | 1389/1323 | 560/81 | BSW | √ | √ | √ |
| 5.50R13LT | 88/84Q | 8PR | 4.00B | 160 | 620 | 560/500 | 1235/1102 | 460/67 | BSW | √ | √ | √ |
| NEW 145R13C | 88/86Q | 8PR | 4.00B | 147 | 566 | 560/530 | 1235/1168 | 450/65 | BSW | √ | √ | √ |
| 155R13LT/C | 90/88Q | 8PR | 4.50B | 157 | 578 | 600/560 | 1323/1235 | 450/65 | BSW | √ | √ | √ |
| 165R13LT | 94/93R | 8PR | 4.50B | 165 | 594 | 670/650 | 1477/1433 | 450/65 | BSW | √ | √ | √ |
| 165/70R13LT | 88/86R | 6PR | 5.00B | 170 | 562 | 560/530 | 1235/1168 | 375 | BSW | √ | √ | √ |
| 175R13LT | 97/95R | 8PR | 5.00B | 177 | 610 | 730/690 | 1609/1521 | 450/65 | BSW | √ | √ | √ |
| 165R14LT | 91/90R | 6PR | 4 1/2J | 165 | 620 | 615/600 | 1356/1323 | 350/51 | BSW | √ | √ | √ |
| 175R14LT | 99/97R | 8PR | 5J | 178 | 634 | 775/730 | 1709/1609 | 450/65 | BSW | √ | √ | √ |
| 175/70R14LT | 95/93S | 6PR | 5J | 177 | 602 | 690/650 | 1521/1433 | 375/54 | BSW | √ | √ | √ |
| 175/75R14LT | 94/91R | 8PR | 5J | 177 | 618 | 670/615 | 1477/1356 | 450/65 | BSW | √ | √ | √ |
| 165/70R13 | 79T | - | 5.00B | 170 | 562 | 437 | 964 | 300/44 | BSW | - | - | - |
| 165/70R14 | 81T | - | 5J | 170 | 588 | 462 | 1019 | 300/44 | BSW | - | - | - |

VAN

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ROCK 858C


## Zigzag grooves

The Zigzag pattern main grooves design ensures excellent anti-hydro performance and improves wet grip.


## Wear-resistant

Deep pattern grooves and high wear-resistant tread compound, ensures excellent wear resistance.


## The thicker sidewall

The strengthened carcass and thicker sidewall make the tire stronger with better bearing capacity and puncture resistant.




## High-load

Using high-strength steel wire and cap layer in tire structure to make the tire stronger and enhance the reliability and durability .


| Size | LI/SI | PR | Rim | S/W (mm) | O/D (mm) | load Index | | Max Pressure (Kpa/Psi) | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | (kg) | (Lbs) | | | | | |
| 7.00R16LT | 115/110N | 12PR | 5.50F | 200 | 775 | 1215/1060 | 2679/2337 | 670/97 | BSW | - | - | - |
| 7.50R16LT | 122/118N | 14PR | 6.00G | 215 | 805 | 1500/1320 | 3307/2910 | 770/112 | BSW | - | - | - |

VAN

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ROCK A/S ONE

M+S

### Streamlined lateral grooves supplemented by sipe design

The streamlined lateral groove improves drainage performance, ensures driving stability for better braking performance.

Wet Grip

### High rigidity shoulder design

Adjusted rigidity of the shoulder block to reach more balanced grounding pressure to handle problem of swinging and eccentric for more stable driving.

Self-cleaning

### Optimized tread pattern design

The pattern groove distribution and the optimized groove angle design reduce the tread pattern noise.

Silence Design

### Unique directional, streamlined and radial pattern design

Increase the ability of water breaking to reduce hydroplaning, quickly eliminate the road water to improve the wet handling.

Driveability

### Innovative Four Seasons Tread compound

Compound features high grip performance and high temperature resistance, and improve the grip under low temperature conditions.

Special Formula

| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| NEW 145/70R13 | 71T | 4.50B | 150 | 534 | 345 | 761 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 145/80R13 | 75T | 4.00B | 145 | 562 | 387 | 853 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 155/65R13 | 73T | 4.50B | 157 | 532 | 365 | 805 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 155/70R13 | 75T | 4.50B | 157 | 548 | 387 | 853 | 300/44 | -- | BSW | √ | √ | √ |
| 155/80R13 | 79T | 4.50B | 157 | 578 | 437 | 963 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 165/70R13 | 79T | 5.00B | 170 | 562 | 437 | 963 | 300/44 | -- | BSW | √ | √ | √ |
| 175/65R13 | 80T | 5.00B | 177 | 558 | 450 | 992 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/70R13 | 82T | 5J | 177 | 576 | 475 | 1047 | 300/44 | -- | BSW | √ | √ | √ |
| 155/65R14 | 75T | 4.50B | 157 | 558 | 387 | 853 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 165/60R14 | 75H | 5.00B | 170 | 554 | 387 | 853 | 300/44 | 420/A/A | BSW | √ | √ | √ |

| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 165/65R14 | 79T | 5J | 170 | 570 | 437 | 963 | 300/44 | - | BSW | √ | √ | √ |
| 165/70R14 | 81T | 5J | 170 | 588 | 462 | 1019 | 300/44 | - | BSW | √ | √ | √ |
| 175/65R14 | 82T | 5J | 177 | 584 | 475 | 1047 | 300/44 | - | BSW | √ | √ | √ |
| 175/70R14 | 88T XL | 5J | 177 | 602 | 560 | 1235 | 340/50 | - | BSW | √ | √ | √ |
| NEW 175/80R14 | 88T | 5J | 177 | 636 | 560 | 1235 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 185/55R14 | 80H | 6J | 194 | 560 | 450 | 992 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 185/60R14 | 82H | 5 1/2J | 189 | 578 | 475 | 1047 | 300/44 | - | BSW | √ | √ | √ |
| 185/65R14 | 86H | 5 1/2J | 189 | 596 | 530 | 1168 | 300/44 | - | BSW | √ | √ | √ |
| 185/70R14 | 88H | 5 1/2J | 189 | 616 | 560 | 1235 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 195/70R14 | 91H | 6J | 201 | 630 | 615 | 1356 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 165/60R15 | 81H XL | 5J | 170 | 579 | 462 | 1019 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 165/65R15 | 81T | 5J | 170 | 595 | 462 | 1019 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/55R15 | 77H | 5 1/2J | 182 | 573 | 412 | 908 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/60R15 | 81H | 5J | 177 | 591 | 462 | 1019 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 175/65R15 | 84H | 5J | 177 | 609 | 500 | 1102 | 300/44 | - | BSW | √ | √ | √ |
| 185/55R15 | 82H | 6J | 194 | 585 | 475 | 1047 | 300/44 | - | BSW | √ | √ | √ |
| 185/60R15 | 88H XL | 5 1/2J | 189 | 603 | 560 | 1235 | 340/50 | - | BSW | √ | √ | √ |
| 185/65R15 | 92T XL | 5 1/2J | 189 | 621 | 630 | 1389 | 340/50 | - | BSW | √ | √ | √ |
| 195/50R15 | 82V | 6J | 201 | 577 | 475 | 1047 | 300/44 | - | BSW | √ | √ | √ |
| 195/55R15 | 85H | 6J | 201 | 595 | 515 | 1135 | 300/44 | - | BSW | √ | √ | √ |
| 195/60R15 | 88H | 6J | 201 | 615 | 560 | 1235 | 300/44 | - | BSW | √ | √ | √ |
| 195/65R15 | 91H | 6J | 201 | 635 | 615 | 1356 | 300/44 | - | BSW | √ | √ | √ |
| 195/65R15 | 95V XL | 6J | 201 | 635 | 690 | 1521 | 340/50 | - | BSW | √ | √ | √ |
| 205/65R15 | 94V | 6J | 209 | 647 | 670 | 1477 | 300/44 | - | BSW | √ | √ | √ |
| 215/65R15 | 96H | 6 1/2J | 221 | 661 | 710 | 1565 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 195/45R16 | 84V XL | 6 1/2J | 195 | 582 | 500 | 1102 | 340/50 | - | BSW | √ | √ | √ |
| 195/50R16 | 88V XL | 6J | 201 | 602 | 560 | 1235 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 195/55R16 | 91V XL | 6J | 201 | 620 | 615 | 1356 | 340/50 | - | BSW | √ | √ | √ |
| NEW 195/60R16 | 89H | 6J | 201 | 640 | 580 | 1278 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 205/45ZR16 | 87W XL | 7J | 206 | 590 | 545 | 1201 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 205/50ZR16 | 91W XL | 6 1/2J | 214 | 612 | 615 | 1356 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 205/55R16 | 91H | 6 1/2J | 214 | 632 | 615 | 1356 | 300/44 | - | BSW | √ | √ | √ |
| 205/55R16 | 94V XL | 6 1/2J | 214 | 632 | 670 | 1477 | 340/50 | - | BSW | √ | √ | √ |
| 205/60R16 | 96V XL | 6J | 209 | 652 | 710 | 1565 | 340/50 | - | BSW | √ | √ | √ |
| 215/45R16 | 90V XL | 7J | 213 | 600 | 600 | 1323 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 215/55R16 | 97V XL | 7J | 226 | 642 | 730 | 1609 | 340/50 | - | BSW | √ | √ | √ |
| 215/60R16 | 99H XL | 6 1/2J | 221 | 664 | 775 | 1709 | 340/50 | - | BSW | √ | √ | √ |
| 215/65R16 | 102H XL | 6 1/2J | 221 | 686 | 850 | 1874 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 215/70R16 | 100H | 6 1/2J | 221 | 708 | 800 | 1764 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 225/55ZR16 | 99W XL | 7J | 233 | 654 | 775 | 1709 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 225/60R16 | 98H | 6 1/2J | 228 | 676 | 750 | 1653 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 235/60R16 | 100H | 7J | 240 | 688 | 800 | 1764 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 205/40ZR17 | 84W XL | 7 1/2J | 212 | 596 | 500 | 1102 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 205/45ZR17 | 88W XL | 7J | 206 | 616 | 560 | 1235 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 205/50ZR17 | 93W XL | 6 1/2J | 214 | 638 | 650 | 1433 | 340/50 | - | BSW | √ | √ | √ |
| 205/55ZR17 | 95W XL | 6 1/2J | 214 | 658 | 690 | 1521 | 340/50 | - | BSW | √ | √ | √ |
| NEW 215/40ZR17 | 87W XL | 7 1/2J | 218 | 604 | 545 | 1201 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 215/45ZR17 | 91W XL | 7J | 213 | 626 | 615 | 1356 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 215/50ZR17 | 95W XL | 7J | 226 | 648 | 690 | 1521 | 340/50 | - | BSW | √ | √ | √ |
| 215/55ZR17 | 98W XL | 7J | 226 | 668 | 750 | 1653 | 340/50 | - | BSW | √ | √ | √ |
| 215/60R17 | 96H | 6 1/2J | 221 | 690 | 710 | 1565 | 300/44 | - | BSW | √ | √ | √ |
| NEW 215/65R17 | 99T | 6 1/2J | 221 | 712 | 775 | 1709 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 225/45ZR17 | 94W XL | 7 1/2J | 225 | 634 | 670 | 1477 | 340/50 | - | BSW | √ | √ | √ |
| 225/50ZR17 | 98W XL | 7J | 233 | 658 | 750 | 1653 | 340/50 | - | BSW | √ | √ | √ |
| 225/55ZR17 | 101W XL | 7J | 233 | 680 | 825 | 1819 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 225/60R17 | 99H | 6 1/2J | 228 | 702 | 775 | 1709 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 225/65R17 | 106H XL | 6 1/2J | 228 | 724 | 950 | 2094 | 340/50 | - | BSW | √ | √ | √ |
| 235/45ZR17 | 97W XL | 8J | 236 | 644 | 730 | 1609 | 340/50 | - | BSW | √ | √ | √ |
| 235/55ZR17 | 103W XL | 7 1/2J | 245 | 690 | 875 | 1929 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 235/65R17 | 108H XL | 7J | 240 | 738 | 1000 | 2205 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 245/45ZR17 | 99W XL | 8J | 243 | 652 | 775 | 1709 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 255/60R17 | 110H XL | 7 1/2J | 260 | 738 | 1060 | 2337 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 215/55R18 | 99V XL | 7J | 226 | 693 | 775 | 1709 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 225/40ZR18 | 92W XL | 8J | 230 | 637 | 630 | 1389 | 340/50 | - | BSW | √ | √ | √ |
| 225/45ZR18 | 95W XL | 7 1/2J | 225 | 659 | 690 | 1521 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 225/50ZR18 | 99W XL | 7J | 233 | 683 | 775 | 1709 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 225/55R18 | 98V | 7J | 233 | 705 | 750 | 1653 | 300/44 | - | BSW | √ | √ | √ |
| NEW 235/40ZR18 | 95W XL | 8 1/2J | 241 | 645 | 690 | 1521 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 235/45ZR18 | 98W XL | 8J | 236 | 669 | 750 | 1653 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 235/50ZR18 | 101W XL | 7 1/2J | 245 | 693 | 825 | 1819 | 340/50 | - | BSW | √ | √ | √ |
| NEW 235/55R18 | 104V XL | 7 1/2J | 245 | 715 | 900 | 1984 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 235/60R18 | 107V XL | 7J | 240 | 739 | 975 | 2149 | 340/50 | - | BSW | √ | √ | √ |
| 245/40ZR18 | 97W XL | 8 1/2J | 248 | 653 | 730 | 1609 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 245/45ZR18 | 100W XL | 8J | 243 | 677 | 800 | 1764 | 340/50 | - | BSW | √ | √ | √ |
| NEW 255/55R18 | 105V | 8J | 265 | 737 | 925 | 2039 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 255/60R18 | 112H XL | 7 1/2J | 260 | 763 | 1120 | 2469 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 155/70R19 | 84T | 4 1/2J | 157 | 701 | 500 | 1102 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 205/55R19 | 97V XL | 6 1/2J | 214 | 709 | 730 | 1609 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 225/35ZR19 | 88W XL | 8J | 230 | 641 | 560 | 1235 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 225/40ZR19 | 93W XL | 8J | 230 | 663 | 650 | 1433 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 225/45ZR19 | 96W XL | 7 1/2J | 225 | 685 | 710 | 1565 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 225/55R19 | 99V | 7J | 233 | 731 | 775 | 1709 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 235/35ZR19 | 91W XL | 8 1/2J | 241 | 647 | 615 | 1356 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 235/45ZR19 | 99W XL | 8J | 236 | 695 | 775 | 1709 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 235/55R19 | 105V XL | 7 1/2J | 245 | 741 | 925 | 2039 | 340/50 | - | BSW | √ | √ | √ |
| NEW 245/40ZR19 | 98W XL | 8 1/2J | 248 | 679 | 750 | 1653 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 245/45ZR19 | 102W XL | 8J | 243 | 703 | 850 | 1874 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 255/35ZR19 | 96W XL | 9J | 260 | 661 | 710 | 1565 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 255/40ZR19 | 100W XL | 9J | 260 | 687 | 800 | 1764 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 285/45R19 | 111V XL | 9 1/2J | 285 | 739 | 1090 | 2403 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 195/55R20 | 91V | 6J | 201 | 722 | 615 | 1356 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| NEW 245/35ZR20 | 95W XL | 8 1/2J | 248 | 680 | 690 | 1521 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 245/40ZR20 | 99W XL | 8 1/2J | 248 | 704 | 775 | 1709 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 255/35ZR20 | 97W XL | 9J | 260 | 686 | 730 | 1609 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 255/40ZR20 | 101W XL | 9J | 260 | 712 | 825 | 1819 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 255/45ZR20 | 105W XL | 8 1/2J | 255 | 738 | 925 | 2039 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 265/45R20 | 108V XL | 9J | 266 | 746 | 1000 | 2205 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 315/35ZR20 | 110W XL | 11J | 320 | 728 | 1060 | 2337 | 340/50 | 420/A/A | BSW | √ | √ | √ |

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ROCK A/S TWO


### Three stepped longitudinal main groove design

Excellent drainage performance and firm grip on wet and dry roads.


### Unique design of the block and the high-density sipe

Ensure the good heat dissipation of the block with great grip and traction.


### Wide shoulder block design

Improve the robustness of the block and the durability and load capacity of the tire; enhance the steering performance.




### Low noise pattern design

Closed shoulder effectively prevent the noise spread; the tuned pattern extends to the rear of the shoulders to allow for evener wear and further noise elimination.


### Innovative four-season tread compound

Compound features high grip performance and high temperature resistance, and improve the grip under low temperature conditions.

A/S

M+S

| Size | LI/SI | PR | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 175/65R14C | 90/88T | 6PR | 5J | 177 | 584 | 600/560 | 1323/1235 | 375/54 | BSW | √ | √ | √ |
| 175/70R14C | 95/93T | 6PR | 5J | 177 | 602 | 690/650 | 1521/1433 | 375/54 | BSW | √ | √ | √ |
| 195/70R15C | 104/102R | 8PR | 6J | 201 | 655 | 900/850 | 1984/1874 | 450/65 | BSW | √ | √ | √ |
| 205/70R15C | 106/104R | 8PR | 6J | 209 | 669 | 950/900 | 2094/1984 | 450/65 | BSW | √ | √ | √ |
| 215/70R15C | 109/107R | 8PR | 6 1/2J | 221 | 683 | 1030/975 | 2271/2149 | 450/65 | BSW | √ | √ | √ |
| 225/70R15C | 112/110R | 8PR | 6 1/2J | 228 | 697 | 1120/1060 | 2469/2337 | 450/65 | BSW | √ | √ | √ |
| 185/75R16C | 104/102R | 8PR | 5J | 184 | 684 | 900/850 | 1984/1874 | 475/69 | BSW | √ | √ | √ |
| 195/60R16C | 99/97H | 6PR | 6J | 201 | 640 | 775/730 | 1709/1609 | 375/54 | BSW | √ | √ | √ |
| 195/65R16C | 104/102T | 8PR | 6J | 201 | 660 | 900/850 | 1984/1874 | 475/69 | BSW | √ | √ | √ |
| 195/75R16C | 107/105R | 8PR | 5 1/2J | 196 | 698 | 975/925 | 2149/2039 | 475/69 | BSW | √ | √ | √ |
| 205/65R16C | 107/105T | 8PR | 6J | 209 | 672 | 975/925 | 2149/2039 | 475/69 | BSW | √ | √ | √ |
| 205/75R16C | 113/111R | 10PR | 5 1/2J | 203 | 714 | 1150/1090 | 2535/2403 | 525/76 | BSW | √ | √ | √ |
| 215/60R16C | 103/101T | 6PR | 6 1/2J | 221 | 664 | 875/825 | 1929/1819 | 375/54 | BSW | √ | √ | √ |
| 215/65R16C | 109/107T | 8PR | 6 1/2J | 221 | 686 | 1030/975 | 2271/2149 | 475/69 | BSW | √ | √ | √ |
| 215/75R16C | 113/111R | 8PR | 6J | 216 | 728 | 1150/1090 | 2535/2403 | 475/69 | BSW | √ | √ | √ |
| 225/65R16C | 112/110R | 8PR | 6 1/2J | 228 | 698 | 1120/1060 | 2469/2337 | 475/69 | BSW | √ | √ | √ |
| 225/75R16C | 121/120R | 10PR | 6J | 223 | 744 | 1450/1400 | 3197/3086 | 575/83 | BSW | √ | √ | √ |
| 235/65R16C | 115/113R | 8PR | 7J | 240 | 712 | 1215/1150 | 2679/2535 | 475/69 | BSW | √ | √ | √ |
| 215/60R17C | 109/107T | 8PR | 6 1/2J | 221 | 690 | 1030/975 | 2271/2149 | 475/69 | BSW | √ | √ | √ |

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# X-636EV

## Comfortable and quiet

The three-in-one compound pitch design can effectively reduce the tire tread noise. The tire blocks with different sizes are optimized by computer simulation, so that the sound energy tends to be evenly dispersed and the tire quiet performance is improved.




## Precise control

Asymmetrical pattern design, high rigidity pattern on the outside to improve control stability, and linear pattern on the inside to improve wetland performance; The lateral penetration steel sheet reduces the stiffness of the pattern and improves the comfort; The lateral shoulder block is designed with continuous decorative block to bring a good control experience.


## High speed and stability

The broad shoulder pattern can reduce the creep of tread pattern during high-speed cornering and steering, provide excellent grip and improve high-speed cornering stability. The intensity of each pattern block is optimized by computer simulation, which brings the vehicle high-speed stability and driving accuracy.


## Safety on dry and wet land

The widened main ditch design is adopted to improve the drainage performance of wet road in rainy days. The inner and outer responsive curved cutter-groove design improves the dry and wet land performance of tires; Interactive design of intermediate pattern groove and three-dimensional Angle cutting design can effectively break the water film on wet road and improve the wet performance of tires.




## Excellent wet grip and low rolling resistance

Excellent wet grip and low rolling resistance tread formula design, tread adopts a new generation of nano-silicon ultra-low roll resistance formula design, effectively improve the range of new energy vehicles; The uniform design of pressure distribution, computer simulation analysis to optimize the tire ground shape, improve the tire ground area, ensure the tire comprehensive performance.


**Quiet cotton technology**

Use a special polyurethane foam sponge

| | Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 185/65R15 | 92T XL | 5.5J | 189 | 621 | 630 | 1389 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| | 195/55R16 | 91V | 6 J | 201 | 620 | 615 | 1356 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| | 205/55R16 | 91V | 6.5J | 214 | 632 | 615 | 1356 | 300/44 | 360/A/A | BSW | √ | √ | √ |
| | 205/45R17 | 88W | 7J | 206 | 616 | 560 | 1235 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| | 215/55R17 | 94V | 7J | 226 | 668 | 670 | 1477 | 300/44 | 360/A/A | BSW | √ | √ | √ |
| | 215/50R18 | 92W | 7J | 226 | 673 | 630 | 1389 | 300/44 | 360/A/A | BSW | √ | √ | √ |
| | 215/55R18 | 99V | 7J | 226 | 693 | 775 | 1709 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| | 235/45R18 | 98W | 8 J | 236 | 669 | 750 | 1653 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| | 235/60R18 | 107H | 7 J | 240 | 739 | 975 | 2149 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| | 235/40R19 | 96W | 8 1/2J | 241 | 671 | 710 | 1565 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| NEW | 235/50ZR19 | 103W XL | 7 1/2J | 245 | 719 | 875 | 1929 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| NEW | 235/55R19 | 105V XL | 7 1/2J | 245 | 741 | 925 | 2039 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| NEW | 245/45R19 | 102V XL | 8 J | 243 | 703 | 850 | 1874 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| NEW | 245/50R19 | 105V XL | 7 1/2J | 253 | 729 | 925 | 2039 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| NEW | 255/45ZR19 | 104W XL | 8 1/2J | 255 | 713 | 900 | 1984 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| NEW | 255/50R19 | 107V XL | 8J | 265 | 739 | 975 | 2149 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| NEW | 255/55R19 | 111V XL | 8J | 265 | 763 | 1090 | 2403 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| | 275/35R19 | 100Y | 91/2J | 278 | 675 | 800 | 1764 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| | 235/35ZR20 | 92Y/92W | 8 1/2J | 241 | 672 | 630 | 1389 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| NEW | 235/50ZR20 | 104W XL | 7 1/2J | 245 | 744 | 900 | 1984 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| NEW | 235/55R20 | 105V XL | 7 1/2J | 245 | 766 | 925 | 2039 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| | 245/35ZR20 | 95Y/95W | 8 1/2J | 248 | 680 | 690 | 1521 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| NEW | 245/45ZR20 | 103W XL | 8J | 243 | 728 | 875 | 1929 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| NEW | 255/45ZR20 | 105W XL | 8 1/2J | 255 | 738 | 925 | 2039 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| NEW | 255/50R20 | 109V XL | 8J | 265 | 764 | 1030 | 2271 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| | 275/30ZR20 | 97W | 9 1/2J | 278 | 674 | 730 | 1609 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| | 285/30ZR20 | 99W | 10J | 290 | 680 | 775 | 1709 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| | 255/35ZR21 | 98W XL | 9J | 260 | 711 | 750 | 1653 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| NEW | 255/40ZR21 | 102Y XL | 9J | 260 | 737 | 850 | 1874 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| NEW | 255/45ZR21 | 106Y XL | 8 1/2J | 255 | 763 | 950 | 2094 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| NEW | 265/45ZR21 | 108W XL | 9J | 266 | 771 | 1000 | 2205 | 340/50 | 360/A/A | BSW | √ | √ | √ |
| | 275/35ZR21 | 103W XL | 9 1/2J | 278 | 725 | 875 | 1929 | 340/50 | 360/A/A | BSW | √ | √ | √ |


**Velvet design**

premium velvet touch effect sidewall mark

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ROCK 717 H/T

## All season tread design

All season tread design superior comprehensive performance.


## Silence design

5 pitches design with best pattern permutation effectively reduce noise and show extremely silence.


## Coordinated tread pattern

Ribs pattern in central tread and coordinated tread blocks on both sides ensure excellent steering and handling performance.


## High density grooves

High density grooves design. Pattern with a mass of grooves increase the contact area with road surface, enhance the drainage and wetland grip ability. Shorten the wetland braking distance.




| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 215/75R15 | 100H | 6 J | 216 | 703 | 800 | 1763 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 225/75R15 | 102H | 6 J | 223 | 719 | 850 | 1873 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 235/75R15 | 105H | 6 1/2J | 235 | 733 | 925 | 2039 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 265/70R15 | 112T | 8 J | 272 | 753 | 1120 | 2469 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 215/65R16 | 102H | 6 1/2J | 221 | 686 | 850 | 1873 | 340/50 | 460/A/A | BSW | √ | √ | √ |
| 215/70R16 | 100H | 6 1/2J | 221 | 708 | 800 | 1763 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 225/70R16 | 103H | 6 1/2J | 228 | 722 | 875 | 1929 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 225/75R16 | 104T | 6 J | 223 | 744 | 900 | 1984 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 235/70R16 | 106H | 7 J | 240 | 736 | 950 | 2094 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 245/70R16 | 111H | 7 J | 248 | 750 | 1090 | 2403 | 340/50 | 460/A/A | BSW | √ | √ | √ |
| 255/70R16 | 111H | 7 1/2J | 260 | 764 | 1090 | 2403 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 265/70R16 | 112T | 8 J | 272 | 778 | 1120 | 2469 | 300/44 | 460/A/B | BSW | √ | √ | √ |
| 265/75R16 | 116T | 7 1/2J | 267 | 804 | 1250 | 2755 | 300/44 | 460/A/B | BSW | √ | √ | √ |
| 215/60R17 | 100H | 6 1/2J | 221 | 690 | 800 | 1763 | 340/50 | 460/A/A | BSW | √ | √ | √ |
| 215/65R17 | 99V | 6 1/2J | 221 | 712 | 775 | 1708 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 235/60R17 | 102H | 7 J | 240 | 714 | 850 | 1873 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 235/65R17 | 108H | 7 J | 240 | 738 | 1000 | 2204 | 340/50 | 460/A/A | BSW | √ | √ | √ |
| 235/70R17 | 107H | 7 J | 240 | 762 | 975 | 2149 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 245/65R17 | 111H | 7 J | 248 | 750 | 1090 | 2403 | 340/50 | 460/A/A | BSW | √ | √ | √ |
| 265/65R17 | 112H | 8 J | 272 | 776 | 1120 | 2469 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 265/70R17 | 115H | 8 J | 272 | 804 | 1215 | 2678 | 300/44 | 460/A/B | BSW | √ | √ | √ |
| 235/60R18 | 107H | 7 J | 240 | 739 | 975 | 2149 | 340/50 | 460/A/A | BSW | √ | √ | √ |
| 245/60R18 | 105H | 7 J | 248 | 751 | 925 | 2039 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 255/60R18 | 112H | 7 1/2J | 260 | 763 | 1120 | 2469 | 340/50 | 460/A/A | BSW | √ | √ | √ |
| 265/60R18 | 114H | 8 J | 272 | 775 | 1180 | 2601 | 340/50 | 460/A/A | BSW | √ | √ | √ |
| 275/65R18 | 116H | 8 J | 279 | 815 | 1250 | 2755 | 300/44 | 460/A/B | BSW | √ | √ | √ |
| 255/55R19 | 111V | 8 J | 265 | 763 | 1090 | 2403 | 340/50 | 460/A/A | BSW | √ | √ | √ |

New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ROCK 719 H/T

## Four wide vertical drainage grooves

Offer necessary high-speed performance of SUV and cross country vehicle, provide great wetland drainage, and improve steering and handling ability on wet road.




## Directional rib in the center of crown with particularly

Designed lateral grooves and multiple sipes for balanced block rigidity, provide excellent drainage performance, ensure good handing performance in rain or snow.




## Continuously closed design on the tire shoulder and supported by longitudinal vertical grooves

Reduce the rigidity of tire shoulder and restrain the eccentric wear effectively, block noise spread of central pattern, reduce the noise and bring extraordinary driving comfortability.




## Restrain the eccentric wear rib design on tire shoulder

Stabilize tire shoulder contour, reduce eccentric wear of tire shoulder, and improve the handling stability when turning at high speed.




| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 215/65R16 | 98H | 6 1/2J | 221 | 686 | 750 | 1653 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 215/70R16 | 100H | 6 1/2J | 221 | 708 | 800 | 1764 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 225/70R16 | 107H XL | 6 1/2J | 228 | 722 | 975 | 2149 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 235/60R16 | 100H | 7J | 240 | 688 | 800 | 1764 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 235/70R16 | 106H | 7J | 240 | 736 | 950 | 2094 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 245/70R16 | 111H XL | 7J | 248 | 750 | 1090 | 2403 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 255/65R16 | 109H | 7 1/2J | 260 | 738 | 1030 | 2271 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 255/70R16 | 111T | 7 1/2J | 260 | 764 | 1090 | 2403 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 265/70R16 | 112T | 8J | 272 | 778 | 1120 | 2469 | 300/44 | 420/A/B | BSW | √ | √ | √ |
| 275/70R16 | 114T | 8J | 279 | 792 | 1180 | 2601 | 300/44 | 420/A/B | BSW | √ | √ | √ |
| 215/60R17 | 96H | 6 1/2J | 221 | 690 | 710 | 1565 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 215/65R17 | 99V | 6 1/2J | 221 | 712 | 775 | 1709 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 225/60R17 | 99H | 6 1/2J | 228 | 702 | 775 | 1709 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 235/60R17 | 106H XL | 7J | 240 | 714 | 950 | 2094 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 225/65R17 | 102H | 6 1/2J | 228 | 724 | 850 | 1874 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 235/65R17 | 104H | 7J | 240 | 738 | 900 | 1984 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 245/65R17 | 111H XL | 7J | 248 | 750 | 1090 | 2403 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 245/70R17 | 114T XL | 7J | 248 | 776 | 1180 | 2601 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 255/60R17 | 110H XL | 7 1/2J | 260 | 738 | 1060 | 2337 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 255/65R17 | 110H | 7 1/2J | 260 | 764 | 1060 | 2337 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 265/65R17 | 112H | 8J | 272 | 776 | 1120 | 2469 | 300/44 | 420/A/B | BSW | √ | √ | √ |
| 265/70R17 | 115T | 8J | 272 | 804 | 1215 | 2679 | 300/44 | 420/A/B | BSW | √ | √ | √ |
| 275/65R17 | 115T | 8J | 279 | 790 | 1215 | 2679 | 300/44 | 420/A/B | BSW | √ | √ | √ |
| 285/65R17 | 116T | 8 1/2J | 292 | 802 | 1250 | 2756 | 300/44 | 420/A/B | BSW | √ | √ | √ |
| 225/55R18 | 98H | 7J | 233 | 705 | 750 | 1653 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 235/55R18 | 104H XL | 7 1/2J | 245 | 715 | 900 | 1984 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 225/60R18 | 104H XL | 6 1/2J | 228 | 727 | 900 | 1984 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 235/60R18 | 107H XL | 7J | 240 | 739 | 975 | 2149 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 235/65R18 | 110H XL | 7J | 240 | 763 | 1060 | 2337 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 245/60R18 | 105H | 7J | 248 | 751 | 925 | 2039 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 255/60R18 | 112H XL | 7 1/2J | 260 | 763 | 1120 | 2469 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 255/70R18 | 113T | 7 1/2J | 260 | 815 | 1150 | 2535 | 300/44 | 420/A/B | BSW | √ | √ | √ |
| 265/60R18 | 110H | 8J | 272 | 775 | 1060 | 2337 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 265/70R18 | 116T | 8J | 272 | 829 | 1250 | 2756 | 300/44 | 420/A/B | BSW | √ | √ | √ |
| 275/60R18 | 117H XL | 8J | 279 | 787 | 1285 | 2833 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 285/60R18 | 116H | 8 1/2J | 292 | 799 | 1250 | 2756 | 300/44 | 420/A/A | BSW | √ | √ | √ |
| 235/65R19 | 109H XL | 7 | 240 | 789 | 1030 | 2271 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 245/55R19 | 107V XL | 7 1/2J | 253 | 753 | 975 | 2149 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 255/50R19 | 107V XL | 8J | 265 | 739 | 975 | 2149 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 255/55R19 | 111V XL | 8J | 265 | 763 | 1090 | 2403 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| 285/50R20 | 116V XL | 9J | 297 | 794 | 1250 | 2756 | 340/50 | 420/A/A | BSW | √ | √ | √ |
| NEW 235/60R19 | 107H XL | 7J | 240 | 765 | 975 | 2149 | 340/50 | 420/A/A | BSW | √ | √ | √ |

* New Developing Sizes / The Labeling Information Is Subject To Change Without Notice.

# ROCK 727 A/T

## All-terrain design

All-terrain four season tire pattern, more strengthful tread block design.


## Stone ejection design

Open tread pattern design effectively prevents stone retention, strengthen stone ejection performance.


## Zigzag steel sheets

Small zigzag "3D steel sheet" design effectively deliver grips on wet road conditions, enhance driving traction.




## Abrasion resistance formula

Special tread glue formula delivers a longer life.


| Size | LI/SI | PR | Rim | S/W (mm) | O/D (mm) | load Index | | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | (kg) | (Lbs) | | | | | | |
| 235/75R15 | 109S XL | - | 6 1/2J | 235 | 733 | 1030 | 2271 | 340/50 | 460/A/A | BSW | √ | √ | √ |
| 235/70R16 | 106T | - | 7 J | 240 | 736 | 950 | 2094 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 245/70R16 | 107T | - | 7 J | 248 | 750 | 975 | 2149 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 265/70R16 | 112T | - | 8 J | 272 | 778 | 1120 | 2469 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 235/65R17 | 104T | - | 7 J | 240 | 738 | 900 | 1984 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 245/65R17 | 107S | - | 7 J | 248 | 750 | 975 | 2149 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 265/70R17 | 115S | - | 8 J | 272 | 804 | 1215 | 2679 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 31X10.50R15LT | 109S | 6PR | 8 1/2J | 268 | 775 | 1030 | 2270 | 350/50 | - | BSW | √ | √ | √ |
| LT225/75R16 | 115/112Q | 10PR | 6 J | 223 | 744 | 1215/1120 | 2470/2680 | 550/80 | - | BSW | √ | √ | √ |
| LT235/85R16 | 120/116Q | 10PR | 6 1/2J | 235 | 806 | 1380/1260 | 3042/2778 | 550/80 | - | BSW | √ | √ | √ |
| LT245/75R16 | 120/116Q | 10PR | 7 J | 248 | 774 | 1380/1260 | 3042/2778 | 550/80 | - | BSW | √ | √ | √ |
| LT265/70R17 | 121/118R | 10PR | 8 J | 272 | 804 | 1450/1320 | 3195/2910 | 550/80 | - | BSW | √ | √ | √ |

* New Developing Sizes / The Labeling Information Is Subject To Change Without Notice.





A/T

# ROCK 737 A/T


## All-terrain design

All-terrain four season tire pattern, more strengthful tread block design.

All-terrain Design

## Stone ejection design

Open tread pattern design effectively prevents stone retention, strengthen stone ejection performance.

Stone Ejection Design

## Zigzag steel sheets

Small zigzag "3D steel sheet" design effectively deliver grips on wet road conditions, enhance driving traction.



Wet Grip

## Abrasion resistance formula

Special tread glue formula delivers a longer life.

Special Formula

| Size | LI/SI | PR | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 175/75R13 | 84T | - | 5.00B | 177 | 593 | 500 | 1102 | 300/44 | 400/A/A | BSW | - | - | - |
| 175/75R14 | 86T | - | 5J | 177 | 618 | 530 | 1168 | 300/44 | 400/A/A | BSW | - | - | - |
| 205/60R15 | 91H | - | 6J | 209 | 627 | 615 | 1356 | 300/44 | 400/A/A | BSW | - | - | - |
| 205/65R15 | 94H | - | 6J | 209 | 647 | 670 | 1477 | 300/44 | 400/A/A | BSW | - | - | - |
| (P) 205/70R15 | 96H | - | 6J | 209 | 669 | 710 | 1565 | 300/44 | 400/A/A | B/W | - | - | - |
| 205/60R16 | 92H | - | 6J | 209 | 652 | 630 | 1389 | 300/44 | 400/A/A | BSW | - | - | - |
| 215/65R16 | 98T | - | 6 1/2J | 221 | 686 | 750 | 1653 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 225/70R16 | 103T | - | 6 1/2J | 228 | 722 | 875 | 1929 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 245/75R16 | 111T | - | 7J | 248 | 774 | 1090 | 2403 | 300/44 | 400/A/A | WSW | √ | √ | √ |
| 255/70R16 | 111T | - | 7 1/2J | 260 | 764 | 1090 | 2403 | 300/44 | 400/A/A | WSW | √ | √ | √ |
| 265/70R16 | 112T | - | 8J | 272 | 778 | 1120 | 2469 | 300/44 | 460/A/B | BSW | √ | √ | √ |
| 215/65R17 | 99T | - | 6 1/2J | 221 | 712 | 775 | 1708 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 225/60R17 | 99H | - | 6 1/2J | 228 | 702 | 775 | 1708 | 300/44 | 400/A/A | BSW | √ | √ | √ |
| 265/65R17 | 112T | - | 8J | 272 | 776 | 1120 | 2469 | 300/44 | 460/A/B | BSW/WSW | √ | √ | √ |
| 265/70R17 | 115S | - | 8J | 272 | 804 | 1215 | 2679 | 300/44 | 460/A/B | BSW | √ | √ | √ |
| 275/65R17 | 115T | - | 8J | 279 | 790 | 1215 | 2679 | 300/44 | 400/A/B | WSW | √ | √ | √ |
| 285/65R17 | 116T | - | 8 1/2J | 292 | 802 | 1250 | 2755 | 300/44 | 400/A/B | WSW | √ | √ | √ |
| 255/60R18 | 112T | - | 7 1/2J | 260 | 763 | 1120 | 2469 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 265/60R18 | 110T | - | 8J | 272 | 775 | 1060 | 2336 | 300/44 | 400/A/A | BSW/WSW | √ | √ | √ |
| 275/65R18 | 116T | - | 8J | 279 | 815 | 1250 | 2755 | 300/44 | 400/A/B | BSW | √ | √ | √ |
| 285/60R18 | 120S XL | - | 8 1/2J | 292 | 799 | 1400 | 3086 | 340/50 | 460/A/A | BSW | √ | √ | √ |
| NEW 305/60R18 | 120S | - | 9J | 311 | 823 | 1400 | 3086 | 300/44 | 460/A/A | BSW | √ | √ | √ |
| 265/50R20 | 111S XL | - | 8 1/2J | 277 | 774 | 1090 | 2403 | 340/50 | 400/A/A | BSW/WSW | √ | √ | √ |
| 275/55R20 | 117S XL | - | 8 1/2J | 284 | 810 | 1285 | 2833 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| NEW 285/50R20 | 116TXL | - | 9 | 297 | 794 | 1250 | 2756 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| NEW 285/55R20 | 119S XL | - | 9J | 297 | 822 | 1360 | 2998 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| NEW 305/50R20 | 120S XL | - | 9 1/2J | 316 | 814 | 1400 | 3086 | 340/50 | 400/A/A | BSW | √ | √ | √ |
| 215R15C | 112/110S | 8PR | 6J | 218 | 725 | 1120/1060 | 2469/2337 | 450/65 | - | BSW | √ | √ | √ |
| LT215/75R15 | 100/97Q | 6PR | 6J | 216 | 703 | 800/730 | 1765/1610 | 350/50 | - | WSW | √ | √ | √ |
| LT235/75R15 | 104/101S | 6PR | 6 1/2J | 235 | 733 | 900/825 | 1985/1820 | 350/50 | - | WSW | √ | √ | √ |
| 245/75R15C | 109/107S | 6PR | 7J | 248 | 749 | 1030/975 | 2271/2149 | 375/54 | - | BSW | √ | √ | √ |
| 255/70R15C | 112/110S | 6PR | 7 1/2J | 260 | 739 | 1120/1060 | 2469/2337 | 375/54 | - | BSW | √ | √ | √ |
| 185/75R16C | 104/102R | 8PR | 5J | 184 | 684 | 900/850 | 1984/1874 | 475/69 | - | BSW | √ | √ | √ |
| 205R16C | 110/108S | 8PR | 6J | 208 | 736 | 1060/1000 | 2337/2205 | 450/65 | - | WSW | √ | √ | √ |
| LT215/85R16 | 115/112Q | 10PR | 6J | 216 | 772 | 1215/1120 | 2679/2469 | 575/84 | - | WSW | √ | √ | √ |
| LT245/70R16 | 113/110S | 8PR | 7J | 248 | 750 | 1150/1060 | 2535/2335 | 450/65 | - | WSW | √ | √ | √ |
| LT265/70R16 | 121/118S | 10PR | 8J | 272 | 778 | 1450/1320 | 3195/2910 | 550/80 | - | WSW | √ | √ | √ |
| LT265/75R16 | 123/120Q | 10PR | 7 1/2J | 267 | 804 | 1550/1400 | 3415/3085 | 550/80 | - | BSW | - | - | - |
| LT285/75R16 | 126/123Q | 10PR | 8J | 286 | 834 | 1700/1550 | 3750/3415 | 550/80 | - | BSW | - | - | - |
| LT245/65R17 | 111/108R | 8PR | 7J | 248 | 750 | 1090/1000 | 2403/2205 | 450/65 | - | WSW | √ | √ | √ |
| LT245/70R17 | 119/116S | 10PR | 7J | 248 | 776 | 1360/1250 | 3000/2755 | 550/80 | - | WSW | √ | √ | √ |
| LT245/75R17 | 121/118S | 10PR | 7J | 248 | 800 | 1450/1320 | 3195/2910 | 550/80 | - | WSW | √ | √ | √ |
| LT285/70R17 | 121/118Q | 10PR | 8 1/2J | 292 | 832 | 1450/1320 | 3195/2910 | 550/80 | - | BSW/WSW | √ | √ | √ |
| LT285/60R18 | 122/119Q | 10PR | 8 1/2J | 292 | 799 | 1500/1360 | 3305/3000 | 550/80 | - | BSW | - | - | - |
| LT285/65R18 | 125/122R | 10PR | 8 1/2J | 292 | 827 | 1650/1500 | 3640/3305 | 550/80 | - | WSW | - | - | - |
| LT325/60R18 | 124/121Q | 10PR | 9 1/2J | 331 | 847 | 1600/1450 | 3525/3195 | 450/65 | - | BSW | - | - | - |
| LT325/65R18 | 127/124Q | 10PR | 9 1/2J | 331 | 879 | 1750/1600 | 3860/3525 | 450/65 | - | BSW | - | - | - |
| 31X10.50R15LT | 109S | 6PR | 8 1/2J | 268 | 775 | 1030 | 2270 | 350/50 | - | WSW | √ | √ | √ |

* New Developing Sizes / The Labeling Information Is Subject To Change Without Notice.

# GRIPTRAC A/T

| Size | LI/SI | PR | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| P205/70R15 | 96T | - | 6J | 209 | 669 | 710 | 1565 | 300/44 | 460/A/A | RWL | - | - | - |
| LT205/70R15 | 96/93S | 6PR | 6J | 209 | 669 | 710/650 | 1565/1435 | 350/50 | - | RWL | - | - | - |
| LT215/70R15 | 104/101S | 8PR | 6 1/2J | 221 | 683 | 900/825 | 1985/1820 | 450/65 | - | RWL | - | - | - |
| P215/75R15 | 100S | - | 6J | 216 | 703 | 800 | 1764 | 300/44 | 460/A/A | RWL | - | - | - |
| LT215/75R15 | 100/97R | 6PR | 6J | 216 | 703 | 800/730 | 1765/1610 | 350/50 | - | RWL | - | - | - |
| LT235/75R15 | 104/101R | 6PR | 6 1/2J | 235 | 733 | 900/825 | 1985/1820 | 350/50 | - | RWL | - | - | - |
| P235/75R15 | 105T | - | 6 1/2J | 235 | 733 | 925 | 2039 | 300/44 | 460/A/A | RWL | - | - | - |
| 255/70R15C | 112/110S | 6PR | 7 1/2J | 260 | 739 | 1120/1060 | 2470/2335 | 375/54 | - | RWL | - | - | - |
| 31×10.50R15LT | 109S | 6PR | 8 1/2J | 268 | 775 | 1030 | 2270 | 350/50 | - | RWL | - | - | - |
| P215/70R16 | 99T | - | 6 1/2J | 221 | 708 | 775 | 1709 | 300/44 | 460/A/A | RWL | - | - | - |
| P225/70R16 | 101T | - | 6 1/2J | 228 | 722 | 825 | 1819 | 300/44 | 460/A/A | RWL | - | - | - |
| LT225/75R16 | 115/112R | 10PR | 6J | 223 | 744 | 1215/1120 | 2680/2470 | 550/80 | - | RWL | - | - | - |
| 235/60R16 | 100H | - | 7J | 240 | 688 | 800 | 1764 | 300/44 | 460/A/A | RWL | - | - | - |
| LT235/70R16 | 110/107S | 8PR | 7J | 240 | 736 | 1060/975 | 2335/2150 | 450/65 | - | RWL | - | - | - |
| P235/70R16 | 104S | - | 7J | 240 | 736 | 900 | 1984 | 300/44 | 460/A/A | RWL | - | - | - |
| P235/75R16 | 109TXL | - | 6 1/2J | 235 | 758 | 1030 | 2271 | 340/50 | 460/A/A | RWL | - | - | - |
| LT235/85R16 | 120/116R | 10PR | 6 1/2J | 235 | 806 | 1400/1250 | 3085/2755 | 550/80 | - | RWL | - | - | - |
| LT245/70R16 | 113/110S | 8PR | 7J | 248 | 750 | 1150/1060 | 2535/2335 | 450/65 | - | RWL | - | - | - |
| P245/70R16 | 111T XL | - | 7J | 248 | 750 | 1090 | 2403 | 340/50 | 460/A/A | RWL | - | - | - |
| LT245/75R16 | 120/116R | 10PR | 7J | 248 | 774 | 1380/1260 | 3042/2778 | 550/80 | - | RWL | - | - | - |
| P245/75R16 | 111T | - | 7J | 248 | 774 | 1090 | 2403 | 300/44 | 460/A/A | RWL | - | - | - |
| P255/70R16 | 111T | - | 7 1/2J | 260 | 764 | 1090 | 2403 | 300/44 | 460/A/B | RWL | - | - | - |
| LT265/70R16 | 121/118R | 10PR | 8J | 272 | 778 | 1450/1320 | 3195/2910 | 550/80 | - | RWL | - | - | - |
| P265/70R16 | 111T | - | 8J | 272 | 778 | 1090 | 2403 | 300/44 | 460/A/B | RWL | - | - | - |
| LT265/75R16 | 123/120S | 10PR | 7 1/2J | 267 | 804 | 1550/1400 | 3415/3085 | 550/80 | - | RWL | - | - | - |
| P275/70R16 | 114T | - | 8J | 279 | 792 | 1180 | 2601 | 300/44 | 460/A/B | RWL | - | - | - |
| LT285/75R16 | 126/123R | 10PR | 8J | 286 | 834 | 1700/1550 | 3750/3415 | 550/80 | - | RWL | - | - | - |
| P225/60R17 | 103H XL | - | 6 1/2J | 228 | 702 | 875 | 1929 | 340/50 | 460/A/A | RWL | - | - | - |
| P225/65R17 | 102T | - | 6 1/2J | 228 | 724 | 850 | 1874 | 300/44 | 460/A/A | RWL | - | - | - |
| LT225/65R17 | 107/103S | 8PR | 6 1/2J | 228 | 724 | 975/875 | 2150/1930 | 450/65 | - | RWL | - | - | - |
| P235/60R17 | 106H XL | - | 7J | 240 | 714 | 950 | 2094 | 340/50 | 460/A/A | RWL | - | - | - |
| P235/65R17 | 108T XL | - | 7J | 240 | 738 | 1000 | 2205 | 340/50 | 460/A/A | RWL | - | - | - |
| LT245/65R17 | 111/108S | 8PR | 7J | 248 | 750 | 1090/1000 | 2405/2205 | 450/65 | - | RWL | - | - | - |
| P245/65R17 | 111T XL | - | 7J | 248 | 750 | 1090 | 2403 | 340/50 | 460/A/A | RWL | - | - | - |
| LT245/70R17 | 119/116S | 10PR | 7J | 248 | 776 | 1360/1250 | 3000/2755 | 550/80 | - | RWL | - | - | - |
| LT245/75R17 | 121/118S | 10PR | 7J | 248 | 800 | 1450/1320 | 3195/2910 | 550/80 | - | RWL | - | - | - |
| P255/65R17 | 114H XL | - | 7 1/2J | 260 | 764 | 1180 | 2601 | 340/50 | 460/A/B | RWL | - | - | - |
| LT265/65R17 | 120/117S | 10PR | 8J | 272 | 776 | 1400/1285 | 3085/2835 | 550/80 | - | RWL | - | - | - |
| P265/65R17 | 112S | - | 8J | 272 | 776 | 1120 | 2469 | 300/44 | 460/A/B | RWL | - | - | - |
| LT265/70R17 | 123/120R | 10PR | 8J | 272 | 804 | 1550/1400 | 3415/3085 | 550/80 | - | RWL | - | - | - |
| P265/70R17 | 115T | - | 8J | 272 | 804 | 1215 | 2679 | 300/44 | 460/A/B | RWL | - | - | - |
| LT275/65R17 | 121/118S | 10PR | 8J | 279 | 790 | 1450/1320 | 3195/2910 | 550/80 | - | RWL | - | - | - |
| P275/65R17 | 115T | - | 8J | 279 | 790 | 1215 | 2679 | 300/44 | 460/A/B | RWL | - | - | - |
| LT275/70R17 | 120/117S | 8PR | 8J | 279 | 818 | 1400/1285 | 3085/2835 | 450/65 | - | RWL | - | - | - |
| LT285/65R17 | 121/118S | 10PR | 8 1/2J | 292 | 802 | 1450/1320 | 3195/2910 | 550/80 | - | RWL | - | - | - |
| P285/65R17 | 116T | - | 8 1/2J | 292 | 802 | 1250 | 2756 | 300/44 | 460/A/B | RWL | - | - | - |
| LT285/70R17 | 122/119S | 8PR | 8 1/2J | 292 | 832 | 1500/1360 | 3305/3000 | 450/65 | - | RWL | - | - | - |
| LT305/70R17 | 125/122S | 10PR | 9J | 311 | 860 | 1650/1500 | 3640/3305 | 450/65 | - | RWL | - | - | - |
| LT315/70R17 | 121/118S | 8PR | 9 1/2J | 323 | 874 | 1450/1320 | 3195/2910 | 350/50 | - | RWL | - | - | - |
| 33×12.50R17LT | 120S | 10PR | 10J | 318 | 826 | 1400 | 3085 | 450/65 | - | RWL | - | - | - |
| 35×12.50R17LT | 125S | 10PR | 10J | 318 | 877 | 1650 | 3640 | 450/65 | - | RWL | - | - | - |
| 215/55R18 | 99H XL | - | 7J | 226 | 693 | 775 | 1709 | 340/50 | 460/A/A | RWL | - | - | - |
| LT225/55R18 | 108/105S | 8PR | 7J | 233 | 705 | 1000/925 | 2205/2040 | 450/65 | - | RWL | - | - | - |
| P225/60R18 | 104T XL | - | 6 1/2J | 228 | 727 | 900 | 1984 | 340/50 | 460/A/A | RWL | - | - | - |
| P235/60R18 | 103T | - | 7J | 240 | 739 | 875 | 1929 | 300/44 | 460/A/A | RWL | - | - | - |
| LT235/60R18 | 108/104S | 8PR | 7J | 240 | 739 | 1000/900 | 2205/1985 | 450/65 | - | RWL | - | - | - |
| P235/65R18 | 106T | - | 7J | 240 | 763 | 950 | 2094 | 300/44 | 460/A/A | RWL | - | - | - |
| LT235/65R18 | 110/107S | 8PR | 7J | 240 | 763 | 1060/975 | 2335/2150 | 450/65 | - | RWL | - | - | - |
| P245/60R18 | 105T | - | 7J | 248 | 751 | 925 | 2039 | 300/44 | 460/A/A | RWL | - | - | - |
| LT245/60R18 | 110/107S | 8PR | 7J | 248 | 751 | 1060/975 | 2335/2150 | 450/65 | - | RWL | - | - | - |

A/T COMING

New Developing Sizes / The Labeling Information Is Subject To Change Without Notice.

ROCKBLADE

| Size | LI/SI | PR | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| P255/60R18 | 112H XL | - | 7½J | 260 | 763 | 1120 | 2469 | 340/50 | 460/A/B | RWL | - | - | - |
| LT255/60R18 | 112/109S | 8PR | 7½J | 260 | 763 | 1120/1030 | 2470/2270 | 450/65 | - | RWL | - | - | - |
| LT255/70R18 | 122/119Q | 10PR | 7½J | 260 | 815 | 1500/1360 | 3305/3000 | 550/80 | - | RWL | - | - | - |
| P265/60R18 | 114H XL | - | 8J | 272 | 775 | 1180 | 2601 | 340/50 | 460/A/B | RWL | - | - | - |
| LT265/60R18 | 114/110S | 8PR | 8J | 272 | 775 | 1180/1060 | 2600/2335 | 450/65 | - | RWL | - | - | - |
| P265/65R18 | 114T XL | - | 8J | 272 | 801 | 1180 | 2601 | 300/44 | 460/A/B | RWL | - | - | - |
| LT265/65R18 | 122/119S | 10PR | 8J | 272 | 801 | 1500/1360 | 3305/3000 | 550/80 | - | RWL | - | - | - |
| P265/70R18 | 116T | - | 8J | 272 | 829 | 1250 | 2756 | 300/44 | 460/A/B | RWL | - | - | - |
| LT265/70R18 | 124/121S | 10PR | 8J | 272 | 829 | 1600/1450 | 3525/3195 | 550/80 | - | RWL | - | - | - |
| LT275/65R18 | 123/120S | 10PR | 8J | 279 | 815 | 1550/1400 | 3415/3085 | 550/80 | - | RWL | - | - | - |
| P275/65R18 | 116T XL | - | 8J | 279 | 815 | 1250 | 2756 | 340/50 | 460/A/B | RWL | - | - | - |
| LT275/70R18 | 125/122S | 10PR | 8J | 279 | 843 | 1650/1500 | 3640/3305 | 550/80 | - | RWL | - | - | - |
| P285/60R18 | 116T | - | 8½J | 292 | 799 | 1250 | 2756 | 300/44 | 460/A/B | RWL | - | - | - |
| LT285/60R18 | 118/115S | 8PR | 8½J | 292 | 799 | 1320/1215 | 2910/2680 | 450/65 | - | RWL | - | - | - |
| P285/65R18 | 116T | - | 8½J | 292 | 827 | 1250 | 2756 | 300/44 | 460/A/B | RWL | - | - | - |
| LT285/65R18 | 125/122S | 10PR | 8½J | 292 | 827 | 1650/1500 | 3640/3305 | 550/80 | - | RWL | - | - | - |
| 33×12.50R18LT | 118S | 10PR | 10J | 318 | 826 | 1320 | 2910 | 450/65 | - | RWL | - | - | - |
| 35×12.50R18LT | 123S | 10PR | 10J | 318 | 877 | 1550 | 3415 | 450/65 | - | RWL | - | - | - |
| LT235/55R19 | 111/108S | 10PR | 7½J | 245 | 741 | 1090/1000 | 2405/2205 | 550/80 | - | RWL | - | - | - |
| P235/60R19 | 107T XL | - | 7J | 240 | 765 | 975 | 2149 | 340/50 | 460/A/A | RWL | - | - | - |
| LT235/65R19 | 117/114S | 10PR | 7J | 240 | 789 | 1285/1180 | 2830/2600 | 550/80 | - | RWL | - | - | - |
| P245/55R19 | 107H XL | - | 7½J | 253 | 753 | 975 | 2149 | 340/50 | 460/A/A | RWL | - | - | - |
| LT245/55R19 | 110/107S | 8PR | 7½J | 253 | 753 | 1060/975 | 2335/2150 | 450/65 | - | RWL | - | - | - |
| LT255/50R19 | 113/110S | 8PR | 8J | 265 | 739 | 1150/1060 | 2535/2335 | 450/65 | - | RWL | - | - | - |
| P255/55R19 | 111H XL | - | 8J | 265 | 763 | 1090 | 2403 | 340/50 | 460/A/B | RWL | - | - | - |
| LT255/55R19 | 115/112S | 10PR | 8J | 265 | 763 | 1215/1120 | 2680/2470 | 550/80 | - | RWL | - | - | - |
| P255/60R19 | 113T XL | - | 7½J | 260 | 789 | 1150 | 2535 | 340/50 | 460/A/B | RWL | - | - | - |
| P265/55R19 | 113H XL | - | 8½J | 277 | 775 | 1150 | 2535 | 340/50 | 460/A/B | RWL | - | - | - |
| LT265/55R19 | 114/110Q | 10PR | 8½J | 277 | 775 | 1180/1060 | 2600/2335 | 550/80 | - | RWL | - | - | - |
| 275/55R19 | 111S | - | 8½J | 284 | 785 | 1090 | 2403 | 300/44 | 460/A/B | RWL | - | - | - |
| LT275/55R19 | 119/116S | 10PR | 8½J | 284 | 785 | 1360/1250 | 3000/2755 | 550/80 | - | RWL | - | - | - |
| 245/50R20 | 105H XL | - | 7½J | 253 | 754 | 925 | 2039 | 340/50 | 460/A/A | RWL | - | - | - |
| LT245/50R20 | 108/104S | 8PR | 7½J | 253 | 754 | 1000/900 | 2205/1985 | 450/65 | - | RWL | - | - | - |
| LT255/55R20 | 117/114S | 10PR | 8J | 265 | 788 | 1285/1180 | 2830/2600 | 550/80 | - | RWL | - | - | - |
| LT255/60R20 | 115/112S | 8PR | 7½J | 260 | 814 | 1215/1120 | 2680/2470 | 450/65 | - | RWL | - | - | - |
| P265/50R20 | 107T | - | 8½J | 277 | 774 | 975 | 2149 | 300/44 | 460/A/B | RWL | - | - | - |
| LT265/50R20 | 115/112S | 10PR | 8½J | 277 | 774 | 1215/1120 | 2680/2470 | 550/80 | - | RWL | - | - | - |
| P265/55R20 | 113H XL | - | 8½J | 277 | 800 | 1150 | 2535 | 340/50 | 460/A/B | RWL | - | - | - |
| LT265/55R20 | 119/116S | 10PR | 8½J | 277 | 800 | 1360/1250 | 3000/2755 | 550/80 | - | RWL | - | - | - |
| LT275/50R20 | 116/113Q | 10PR | 8½J | 284 | 784 | 1250/1150 | 2755/2535 | 550/80 | - | RWL | - | - | - |
| LT275/55R20 | 120/117S | 10PR | 8½J | 284 | 810 | 1400/1285 | 3085/2835 | 550/80 | - | RWL | - | - | - |
| P275/55R20 | 117S XL | - | 8½J | 284 | 810 | 1285 | 2833 | 340/50 | 460/A/B | RWL | - | - | - |
| LT275/60R20 | 119/116S | 8PR | 8J | 279 | 838 | 1360/1250 | 3000/2755 | 450/65 | - | RWL | - | - | - |
| P275/60R20 | 115T | - | 8J | 279 | 838 | 1215 | 2679 | 300/44 | 460/A/B | RWL | - | - | - |
| LT275/65R20 | 126/123S | 10PR | 8J | 279 | 866 | 1700/1550 | 3750/3415 | 550/80 | - | RWL | - | - | - |
| LT285/50R20 | 119/116S | 10PR | 9J | 297 | 794 | 1360/1250 | 3000/2755 | 550/80 | - | RWL | - | - | - |
| P285/50R20 | 116T XL | - | 9J | 297 | 794 | 1250 | 2756 | 340/50 | 460/A/B | RWL | - | - | - |
| LT285/55R20 | 122/119S | 10PR | 9J | 297 | 822 | 1500/1360 | 3305/3000 | 550/80 | - | RWL | - | - | - |
| P285/55R20 | 119S XL | - | 9J | 297 | 822 | 1360 | 2998 | 340/50 | 460/A/B | RWL | - | - | - |
| 33×12.50R20LT | 114S | 10PR | 10J | 318 | 826 | 1180 | 2600 | 450/65 | - | RWL | - | - | - |
| 35×12.50R20LT | 121S | 10PR | 10J | 318 | 877 | 1450 | 3195 | 450/65 | - | RWL | - | - | - |
| LT275/45R21 | 118/115S | 12PR | 9J | 273 | 781 | 1150/1060 | 2535/2335 | 650/94 | - | RWL | - | - | - |
| LT275/50R21 | 122/119S | 12PR | 8½J | 284 | 809 | 1500/1360 | 3305/3000 | 650/94 | - | RWL | - | - | - |
| 275/40R22 | 107T XL | - | 9½J | 278 | 779 | 975 | 2149 | 340/50 | 460/A/B | RBL | - | - | - |
| 275/50R22 | 115T | - | 8½J | 284 | 835 | 1215 | 2679 | 340/50 | 460/A/B | RWL | - | - | - |
| LT275/50R22 | 119/116S | 10PR | 8½J | 284 | 835 | 1360/1250 | 3000/2755 | 550/80 | - | RWL | - | - | - |
| LT285/45R22 | 116/113S | 10PR | 9½J | 285 | 815 | 1250/1150 | 2755/2535 | 550/80 | - | RWL | - | - | - |
| 33×12.50R22LT | 109S | 10PR | 10 1/2J | 316 | 826 | 1030 | 2270 | 450/65 | - | RWL | - | - | - |
| 35×12.50R22LT | 117S | 10PR | 10J | 318 | 877 | 1285 | 2835 | 450/65 | - | RWL | - | - | - |


## GRIPTRAC A/T

A/T

COMING

- New Development Size / Tire Labeling Information Is Subject To Change Without Notice.

# ROCK 787 R/T

NEW

## Open pattern shoulder design

Improve the longitudinal grip of the tires, and ensure the traction performance of muddy, gravel and snow roads.


## Staggered pattern shoulder design

The staggered shoulder shape is combined with stronger skeleton material to prevent the side rock from damaging the tire and improve the grip of the tire.


## Different Under-shoulder pattern design

Protect the tire shoulder and upper sidewall from damage, improve the grip of the tire on muddy roads, and improve the grip under low adhesion conditions with low air pressure, different of two shoulder design to meet the needs of different users on the tire appearance.




## Large shoulder matching small flower pattern block design in the middle

Ensure the off-road performance of tires, improve the comfort of pavement, and realize the perfect combination of off-road and road driving performance.


## Composite pitch fit pitch random arrangement design

Improve tire grip and comfort, and reduce tire regular noise.


| Size | LI/SI | PR | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | UTQG | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 27X8.50R14LT | 95Q | 6PR | 7J | 218 | 674 | 690 | 1520 | 350/50 | - | WSW | | POR | |
| 235/75R15 | 109Q XL | - | 6 1/2J | 235 | 733 | 1030 | 2271 | 340/50 | 560/A/B | WSW | √ | √ | √ |
| 31X10.50R15LT | 109Q | 6PR | 8 1/2J | 268 | 775 | 1030 | 2270 | 350/50 | - | WSW | | POR | |
| 33X12.50R15LT | 108Q | 6PR | 10J | 318 | 826 | 1000 | 2205 | 250/35 | - | WSW | | POR | |
| 235/70R16 | 109Q XL | - | 7 J | 240 | 736 | 1030 | 2271 | 340/50 | 560/A/B | WSW | √ | √ | √ |
| 255/70R16 | 111Q | - | 7 1/2J | 260 | 764 | 1090 | 2403 | 300/44 | 560/A/B | WSW | √ | √ | √ |
| 265/70R16 | 116Q XL | - | 8J | 272 | 778 | 1250 | 2756 | 340/50 | 560/A/B | WSW | √ | √ | √ |
| LT245/75R16 | 120/116Q | 10PR | 7 J | 248 | 774 | 1380/1260 | 3042/2778 | 550/80 | - | WSW | | POR | |
| 245/75R16 | 111Q | - | 7 J | 248 | 774 | 1090 | 2403 | 300/44 | 560/A/B | WSW | √ | √ | √ |
| LT265/75R16 | 119/116Q | 8PR | 7 1/2J | 267 | 804 | 1360/1250 | 3000/2755 | 450/65 | - | WSW | | POR | |
| LT285/75R16 | 116/113Q | 6PR | 8 J | 286 | 834 | 1250/1150 | 2755/2535 | 350/50 | - | WSW | | POR | |
| 265/65R17 | 116Q XL | - | 8J | 272 | 776 | 1250 | 2756 | 340/50 | 560/A/B | WSW | √ | √ | √ |
| 35X12.50R17LT | 121Q | 10PR | 10J | 318 | 877 | 1450 | 3195 | 450/65 | - | WSW | | POR | |
| LT265/70R17 | 118/115Q | 8PR | 8 J | 272 | 804 | 1320/1215 | 2910/2680 | 450/65 | - | WSW | | POR | |
| 265/70R17 | 115Q | - | 8 J | 272 | 804 | 1215 | 2679 | 300/44 | 560/A/B | WSW | √ | √ | √ |
| LT285/70R17 | 116/113Q | 6PR | 8 1/2J | 292 | 832 | 1250/1150 | 2755/2535 | 350/50 | - | WSW | | POR | |
| 265/60R18 | 114Q XL | - | 8J | 272 | 775 | 1180 | 2601 | 340/50 | 560/A/B | WSW | √ | √ | √ |
| 265/65R18 | 116Q XL | - | 8J | 272 | 801 | 1250 | 2756 | 340/50 | 560/A/B | WSW | √ | √ | √ |
| 275/65R18 | 116Q XL | - | 8J | 279 | 815 | 1250 | 2756 | 340/50 | 560/A/B | WSW | √ | √ | √ |
| 33X12.50R18LT | 118Q | 10PR | 10J | 318 | 826 | 1320 | 2910 | 450/65 | - | WSW | | POR | |
| 35X12.50R18LT | 118Q | 8PR | 10J | 318 | 877 | 1320 | 2910 | 350/50 | - | WSW | | POR | |
| LT285/65R18 | 121/118Q | 8PR | 8 1/2J | 292 | 827 | 1450/1320 | 3195/2910 | 450/65 | - | WSW | | POR | |
| 265/50R20 | 111Q XL | - | 8 1/2J | 277 | 774 | 1090 | 2403 | 340/50 | 560/A/B | WSW | √ | √ | √ |
| 275/60R20 | 116Q XL | - | 8J | 279 | 838 | 1250 | 2756 | 340/50 | 560/A/B | WSW | √ | √ | √ |
| 33X12.50R20LT | 114Q | 10PR | 10J | 318 | 826 | 1180 | 2600 | 450/65 | - | WSW | | POR | |
| 35X12.50R20LT | 121Q | 10PR | 10J | 318 | 877 | 1450 | 3195 | 450/65 | - | WSW | | POR | |
| LT285/55R20 | 117/114Q | 8PR | 9J | 297 | 822 | 1285/1180 | 2835/2600 | 450/65 | - | WSW | | POR | |
| 285/45R22 | 114Q XL | - | 9 1/2J | 285 | 815 | 1180 | 2601 | 340/50 | 560/A/B | WSW | √ | √ | √ |
| 33X12.50R22LT | 109Q | 10PR | 10J | 318 | 826 | 1030 | 2270 | 450/65 | - | WSW | | POR | |
| 35X12.50R22LT | 117Q | 10PR | 10J | 318 | 877 | 1285 | 2835 | 450/65 | - | WSW | | POR | |


New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ROCK 767 M/T


## Tread bionic "shark', block design

Better embedded with off-road complex terrain to enhance the grip of tires.


## Widen and deepen the groove design

Good heat dissipation, good self-cleaning performance and strong grip, suitable for all kinds of complex road conditions.




## The shoulder pattern adopts the silt self-cleaning technology and the stone ejection groove

The sludge accumulated in the groove automatically removed in rotation and the stone ejected to ensure safe and smooth driving.




## Sidewall bionic decorative design

The thickened sidewall matched with the bionic pattern to improve impact and damage resistance while meeting the individual needs of consumers.




| Size | LI/SI | PR | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| LT235/85R16 | 120/116Q | 10PR | 6 1/2J | 235 | 806 | 1380/1260 | 3042/2778 | 550/80 | WSW | | POR | |
| LT235/75R15 | 104/101Q | 6PR | 6 1/2J | 235 | 733 | 900/825 | 1985/1820 | 350/50 | WSW | | POR | |
| LT235/70R16 | 110/107Q | 8PR | 7J | 240 | 736 | 1060/975 | 2335/2150 | 450/65 | WSW | | POR | |
| LT265/75R16 | 119/116Q | 8PR | 7 1/2J | 267 | 804 | 1360/1250 | 3000/2755 | 450/65 | WSW | | POR | |
| LT265/75R16 | 123/120Q | 10PR | 7 1/2J | 267 | 804 | 1500/1400 | 3415/3085 | 550/80 | WSW | | - | |
| NEW LT265/65R17 | 120/117Q | 10PR | 8J | 272 | 782 | 1400/1285 | 3085/2835 | 550/80 | WSW | | POR | |
| LT265/70R17 | 121/118Q | 10PR | 8J | 272 | 804 | 1450/1320 | 3195/2910 | 550/80 | WSW | | POR | |
| LT285/75R16 | 116/113Q | 6PR | 8J | 286 | 834 | 1250/1150 | 2755/2535 | 350/50 | WSW | | POR | |
| LT285/75R16 | 126/123Q | 10PR | 8J | 286 | 834 | 1700/1550 | 3750/3415 | 550/80 | WSW | | - | |
| LT285/70R17 | 121/118Q | 8PR | 8 1/2J | 292 | 832 | 1450/1320 | 3195/2910 | 450/65 | WSW | | POR | |
| LT245/70R16 | 118/115Q | 10PR | 7J | 248 | 750 | 1320/1215 | 2910/2680 | 550/80 | WSW | | POR | |
| 31X10.50R15LT | 109Q | 6PR | 8 1/2J | 268 | 775 | 1030 | 2270 | 350/50 | WSW | | POR | |
| 35X12.50R15LT | 113Q | 6PR | 10J | 318 | 877 | 1150 | 2535 | 250/35 | WSW | | POR | |
| 35X12.50R17LT | 121Q | 10PR | 10J | 318 | 877 | 1450 | 3195 | 450/65 | WSW | | POR | |
| 33X12.50R18LT | 118Q | 10PR | 10J | 318 | 826 | 1320 | 2910 | 450/65 | WSW | | POR | |
| 33X12.50R20LT | 114Q | 10PR | 10J | 318 | 826 | 1180 | 2600 | 450/65 | WSW | | POR | |
| 35X12.50R18LT | 118Q | 8PR | 10J | 318 | 877 | 1320 | 2910 | 350/50 | WSW | | POR | |
| 35X12.50R20LT | 121Q | 10PR | 10J | 318 | 877 | 1450 | 3195 | 450/65 | WSW | | POR | |
| NEW 33X12.50R22LT | 109Q | 10PR | 10J | 318 | 832 | 1030 | 2270 | 450/65 | BSW | | POR | |

*New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ROCK 757 M/T



## Pyramid-shaped pattern

Pyramid-shaped pattern design improves grip and traction on muddy and sandstone roads.

**P**yramid-shaped Pattern

## Self-cleaning grooves

Slush self-cleaning and rejection groove design guarantee a safe and smooth driving.

**S**elf-cleaning

## Rigidity shoulder

The shoulder extends to sidewall tread block design greatly protect the tire from external puncture or injury.



**S**ecurity

## Anti-skip design

A mass of steel sheets and grooves design provide great grip ability and driving performance on wetland.



**W**et Grip

M/T

| Size | LI/SI | PR | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 31x10.50R15LT | 109Q | 6PR | 8 1/2J | 268 | 775 | 1030 | 2270 | 350/50 | BSW | | POR | |
| 32X11.50R15LT | 113Q | 6PR | 9 J | 290 | 801 | 1150 | 2535 | 350/50 | BSW | | POR | |
| 33X12.50R15LT | 108Q | 6PR | 10J | 318 | 826 | 1000 | 2205 | 250/35 | BSW | | POR | |
| 33X12.50R17LT | 120Q | 10PR | 10 J | 318 | 826 | 1400 | 3085 | 450/65 | BSW | | POR | |
| LT215/75R15 | 100/97Q | 6PR | 6 J | 216 | 703 | 800/730 | 1765/1610 | 350/50 | BSW | | POR | |
| LT235/75R15 | 104/101Q | 6PR | 6 1/2J | 235 | 733 | 900/825 | 1985/1820 | 350/50 | BSW | | POR | |
| LT215/85R16 | 115/112Q | 10PR | 6 J | 216 | 772 | 1215/1120 | 2680/2470 | 550/80 | BSW | | POR | |
| LT225/75R16 | 115/112N | 10PR | 6 J | 223 | 744 | 1215/1120 | 2680/2470 | 550/80 | BSW | | POR | |
| LT235/85R16 | 120/116Q | 10PR | 6 1/2J | 235 | 806 | 1380/1260 | 3042/2778 | 550/80 | BSW | | POR | |
| LT245/75R16 | 120/116N | 10PR | 7 J | 248 | 774 | 1380/1260 | 3042/2778 | 550/80 | BSW | | POR | |
| LT305/70R16 | 124/121P | 10PR | 9 J | 311 | 834 | 1600/1450 | 3525/3195 | 450/65 | BSW | | - | |
| LT315/75R16 | 127/124Q | 10PR | 8 1/2J | 313 | 878 | 1750/1600 | 3860/3525 | 450/65 | BSW | | - | |


* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ICECRUISER I

## Multiple groove mixed design

This design suitable for various roads, well balanced the grip and handling on different ice and snow roads, provides extra grooves on the tire surface, and increased the grip.




## Innovative optimization design of bionic wave-shaped high-density groove

This design enabled the tire rubber block to have up to 2500 tread grooves, It is more conducive to tread deformation in snowy weather, thereby providing more traction and enhancing handling.


## Tread pattern noise reduction design

This design effectively disperses the noise frequency, bringing a quiet and comfortable driving experience to the driver.


## Special formula designed for ice and snow road conditions to escort driving in winter


## New directional tread pattern design

This design not only maximized the traction, but also enhanced the drainage and snow removal capabilities.


| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 145/70R13 | 71T | 4.50B | 150 | 534 | 345 | 761 | 300/44 | BSW | √ | √ | √ |
| 145/80R13 | 75T | 4.00B | 145 | 562 | 387 | 853 | 300/44 | BSW | √ | √ | √ |
| 155/65R13 | 73T | 4.50B | 157 | 532 | 365 | 805 | 300/44 | BSW | √ | √ | √ |
| 155/70R13 | 75T | 4.50B | 157 | 548 | 387 | 853 | 300/44 | BSW | √ | √ | √ |
| 155/80R13 | 79T | 4.50B | 157 | 578 | 437 | 963 | 300/44 | BSW | √ | √ | √ |
| 165/70R13 | 79T | 5.00B | 170 | 562 | 437 | 963 | 300/44 | BSW | √ | √ | √ |
| 165/80R13 | 83T | 4.50B | 165 | 594 | 487 | 1074 | 300/44 | BSW | √ | √ | √ |
| 175/65R13 | 80T | 5.00B | 177 | 558 | 450 | 992 | 300/44 | BSW | √ | √ | √ |
| 175/70R13 | 82T | 5.00B | 177 | 576 | 475 | 1047 | 300/44 | BSW | √ | √ | √ |

| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 155/65R14 | 75T | 4 1/2J | 157 | 558 | 387 | 853 | 300/44 | BSW | √ | √ | √ |
| 165/60R14 | 75H | 5J | 170 | 554 | 387 | 853 | 300/44 | BSW | √ | √ | √ |
| 165/65R14 | 79T | 5J | 170 | 570 | 437 | 963 | 300/44 | BSW | √ | √ | √ |
| 165/70R14 | 81T | 5J | 170 | 588 | 462 | 1019 | 300/44 | BSW | √ | √ | √ |
| 175/65R14 | 82T | 5J | 177 | 584 | 475 | 1047 | 300/44 | BSW | √ | √ | √ |
| 175/70R14 | 84T | 5J | 177 | 602 | 500 | 1102 | 300/44 | BSW | √ | √ | √ |
| 185/55R14 | 80H | 6J | 194 | 560 | 450 | 992 | 300/44 | BSW | √ | √ | √ |
| 185/60R14 | 82T | 5 1/2J | 189 | 578 | 475 | 1047 | 300/44 | BSW | √ | √ | √ |
| 185/65R14 | 86T | 5 1/2J | 189 | 596 | 530 | 1168 | 300/44 | BSW | √ | √ | √ |
| 185/70R14 | 88T | 5 1/2J | 189 | 616 | 560 | 1235 | 300/44 | BSW | √ | √ | √ |
| 195/60R14 | 86H | 6J | 201 | 590 | 530 | 1168 | 300/44 | BSW | √ | √ | √ |
| 195/65R14 | 89H | 6J | 201 | 610 | 580 | 1279 | 300/44 | BSW | √ | √ | √ |
| 195/70R14 | 91T | 6J | 201 | 630 | 615 | 1356 | 300/44 | BSW | √ | √ | √ |
| 165/60R15 | 81H XL | 5J | 170 | 579 | 462 | 1019 | 340/50 | BSW | √ | √ | √ |
| 165/65R15 | 81T | 5J | 170 | 595 | 462 | 1019 | 300/44 | BSW | √ | √ | √ |
| 175/55R15 | 77H | 5 1/2J | 182 | 573 | 412 | 908 | 300/44 | BSW | √ | √ | √ |
| 175/60R15 | 81H | 5J | 177 | 591 | 462 | 1019 | 300/44 | BSW | √ | √ | √ |
| 175/65R15 | 84T | 5J | 177 | 609 | 500 | 1102 | 300/44 | BSW | √ | √ | √ |
| 185/55R15 | 82H | 6J | 194 | 585 | 475 | 1047 | 300/44 | BSW | √ | √ | √ |
| 185/60R15 | 84H | 5 1/2J | 189 | 603 | 500 | 1102 | 300/44 | BSW | √ | √ | √ |
| 185/65R15 | 88T | 5 1/2J | 189 | 621 | 560 | 1235 | 300/44 | BSW | √ | √ | √ |
| 195/50R15 | 82V | 6J | 201 | 577 | 475 | 1047 | 300/44 | BSW | √ | √ | √ |
| 195/55R15 | 85H | 6J | 201 | 595 | 515 | 1135 | 300/44 | BSW | √ | √ | √ |
| 195/60R15 | 88H | 6J | 201 | 615 | 560 | 1235 | 300/44 | BSW | √ | √ | √ |
| 195/65R15 | 95T XL | 6J | 201 | 635 | 690 | 1521 | 340/50 | BSW | √ | √ | √ |
| 205/60R15 | 91H | 6J | 209 | 627 | 615 | 1356 | 300/44 | BSW | √ | √ | √ |
| 205/65R15 | 94H | 6J | 209 | 647 | 670 | 1477 | 300/44 | BSW | √ | √ | √ |
| 205/70R15 | 96T | 6J | 209 | 669 | 710 | 1565 | 300/44 | BSW | √ | √ | √ |
| 215/65R15 | 96H | 6 1/2J | 221 | 661 | 710 | 1565 | 300/44 | BSW | √ | √ | √ |
| 185/50R16 | 81V | 6J | 194 | 592 | 462 | 1019 | 300/44 | BSW | √ | √ | √ |
| 185/55R16 | 83H | 6J | 194 | 610 | 487 | 1074 | 300/44 | BSW | √ | √ | √ |
| 185/60R16 | 86H | 5 1/2J | 189 | 628 | 530 | 1168 | 300/44 | BSW | √ | √ | √ |
| 195/45R16 | 84V XL | 6 1/2J | 195 | 582 | 500 | 1102 | 340/50 | BSW | √ | √ | √ |
| 195/50R16 | 84V | 6J | 201 | 602 | 500 | 1102 | 300/44 | BSW | √ | √ | √ |
| 195/55R16 | 91H XL | 6J | 201 | 620 | 615 | 1356 | 340/50 | BSW | √ | √ | √ |
| 205/45R16 | 87V XL | 7J | 206 | 590 | 545 | 1201 | 340/50 | BSW | √ | √ | √ |
| 205/50R16 | 91V XL | 6 1/2J | 214 | 612 | 615 | 1356 | 340/50 | BSW | √ | √ | √ |
| 205/55R16 | 91H | 6 1/2J | 214 | 632 | 615 | 1356 | 300/44 | BSW | √ | √ | √ |
| 205/60R16 | 92H | 6J | 209 | 652 | 630 | 1389 | 300/44 | BSW | √ | √ | √ |
| 205/65R16 | 95H | 6J | 209 | 672 | 690 | 1521 | 300/44 | BSW | √ | √ | √ |
| 215/45R16 | 90V XL | 7J | 213 | 600 | 600 | 1323 | 340/50 | BSW | √ | √ | √ |
| 215/55R16 | 97H XL | 7J | 226 | 642 | 730 | 1609 | 340/50 | BSW | √ | √ | √ |
| 215/60R16 | 99H XL | 6 1/2J | 221 | 664 | 775 | 1709 | 340/50 | BSW | √ | √ | √ |
| 215/65R16 | 98T | 6 1/2J | 221 | 686 | 750 | 1653 | 300/44 | BSW | √ | √ | √ |
| 225/55R16 | 95H | 7J | 233 | 654 | 690 | 1521 | 300/44 | BSW | √ | √ | √ |
| 225/60R16 | 98H | 6 1/2J | 228 | 676 | 750 | 1653 | 300/44 | BSW | √ | √ | √ |
| 225/65R16 | 100T | 6 1/2J | 228 | 698 | 800 | 1764 | 300/44 | BSW | √ | √ | √ |
| 205/40R17 | 84V XL | 7 1/2J | 212 | 596 | 500 | 1102 | 340/50 | BSW | √ | √ | √ |
| 205/45R17 | 88V XL | 7J | 206 | 616 | 560 | 1235 | 340/50 | BSW | √ | √ | √ |
| 205/50R17 | 93H XL | 6 1/2J | 214 | 638 | 650 | 1433 | 340/50 | BSW | √ | √ | √ |
| 205/55R17 | 95H XL | 6 1/2J | 214 | 658 | 690 | 1521 | 340/50 | BSW | √ | √ | √ |
| 215/40R17 | 87V XL | 7 1/2J | 218 | 604 | 545 | 1201 | 340/50 | BSW | √ | √ | √ |
| 215/45R17 | 91V XL | 7J | 213 | 626 | 615 | 1356 | 340/50 | BSW | √ | √ | √ |
| 215/50R17 | 95H XL | 7J | 226 | 648 | 690 | 1521 | 340/50 | BSW | √ | √ | √ |
| 215/55R17 | 98V XL | 7J | 226 | 668 | 750 | 1653 | 340/50 | BSW | √ | √ | √ |
| 225/45R17 | 94V XL | 7 1/2J | 225 | 634 | 670 | 1477 | 340/50 | BSW | √ | √ | √ |
| 225/50R17 | 98H XL | 7J | 233 | 658 | 750 | 1653 | 340/50 | BSW | √ | √ | √ |
| 225/55R17 | 101H XL | 7J | 233 | 680 | 825 | 1819 | 340/50 | BSW | √ | √ | √ |
| 235/45R17 | 97H XL | 8J | 236 | 644 | 730 | 1609 | 340/50 | BSW | √ | √ | √ |
| 235/55R17 | 103H XL | 7 1/2J | 245 | 690 | 875 | 1929 | 340/50 | BSW | √ | √ | √ |
| 245/40R17 | 95V XL | 8 1/2J | 248 | 628 | 690 | 1521 | 340/50 | BSW | √ | √ | √ |
| 245/45R17 | 99V XL | 8J | 243 | 652 | 775 | 1709 | 340/50 | BSW | √ | √ | √ |
| 215/45R18 | 93V XL | 7J | 213 | 651 | 650 | 1433 | 340/50 | BSW | √ | √ | √ |
| 215/55R18 | 99H XL | 7J | 226 | 693 | 775 | 1709 | 340/50 | BSW | √ | √ | √ |
| 225/40R18 | 92H XL | 8J | 230 | 637 | 630 | 1389 | 340/50 | BSW | √ | √ | √ |
| 225/45R18 | 95H XL | 7 1/2J | 225 | 659 | 690 | 1521 | 340/50 | BSW | √ | √ | √ |
| 225/50R18 | 99H XL | 7J | 233 | 683 | 775 | 1709 | 340/50 | BSW | √ | √ | √ |
| 225/55R18 | 98H | 7J | 233 | 705 | 750 | 1653 | 300/44 | BSW | √ | √ | √ |
| 235/40R18 | 95V XL | 8 1/2J | 241 | 645 | 690 | 1521 | 340/50 | BSW | √ | √ | √ |
| 235/45R18 | 98H XL | 8J | 236 | 669 | 750 | 1653 | 340/50 | BSW | √ | √ | √ |
| 235/50R18 | 97V | 7 1/2J | 245 | 693 | 730 | 1609 | 300/44 | BSW | √ | √ | √ |
| 235/55R18 | 104H XL | 7 1/2J | 245 | 715 | 900 | 1984 | 340/50 | BSW | √ | √ | √ |
| 245/40R18 | 97V XL | 8 1/2J | 248 | 653 | 730 | 1609 | 340/50 | BSW | √ | √ | √ |
| 245/45R18 | 100H XL | 8J | 243 | 677 | 800 | 1764 | 340/50 | BSW | √ | √ | √ |
| 245/50R18 | 104H XL | 7 1/2J | 253 | 703 | 900 | 1984 | 340/50 | BSW | √ | √ | √ |
| 255/40R18 | 99H XL | 9J | 260 | 661 | 775 | 1709 | 340/50 | BSW | √ | √ | √ |
| 255/45R18 | 99V | 8 1/2J | 255 | 687 | 775 | 1709 | 300/44 | BSW | √ | √ | √ |
| 225/40R19 | 93V XL | 8J | 230 | 663 | 650 | 1433 | 340/50 | BSW | √ | √ | √ |
| 225/45R19 | 96V XL | 7 1/2J | 225 | 685 | 710 | 1565 | 340/50 | BSW | √ | √ | √ |
| 225/55R19 | 99H | 7J | 233 | 731 | 775 | 1709 | 300/44 | BSW | √ | √ | √ |
| 235/35R19 | 91V XL | 8 1/2J | 241 | 647 | 615 | 1356 | 340/50 | BSW | √ | √ | √ |
| 235/45R19 | 99V XL | 8J | 236 | 695 | 775 | 1709 | 340/50 | BSW | √ | √ | √ |
| 235/50R19 | 103V XL | 7 1/2J | 245 | 719 | 875 | 1929 | 340/50 | BSW | √ | √ | √ |
| 235/55R19 | 105H XL | 7 1/2J | 245 | 741 | 925 | 2039 | 340/50 | BSW | √ | √ | √ |
| 245/40R19 | 98V XL | 8 1/2J | 248 | 679 | 750 | 1653 | 340/50 | BSW | √ | √ | √ |
| 245/45R19 | 102H XL | 8J | 243 | 703 | 850 | 1874 | 340/50 | BSW | √ | √ | √ |
| 245/50R19 | 105H XL | 7 1/2J | 253 | 729 | 925 | 2039 | 340/50 | BSW | √ | √ | √ |
| 255/35R19 | 96V XL | 9J | 260 | 661 | 710 | 1565 | 340/50 | BSW | √ | √ | √ |
| 255/40R19 | 100H XL | 9J | 260 | 687 | 800 | 1764 | 340/50 | BSW | √ | √ | √ |
| 255/45R19 | 104H XL | 8 1/2J | 255 | 713 | 900 | 1984 | 340/50 | BSW | √ | √ | √ |
| 235/55R20 | 105H XL | 7 1/2J | 245 | 766 | 925 | 2039 | 340/50 | BSW | √ | √ | √ |
| 245/35R20 | 95V XL | 8 1/2J | 248 | 680 | 690 | 1521 | 340/50 | BSW | √ | √ | √ |
| 245/40R20 | 99V XL | 8 1/2J | 248 | 704 | 775 | 1709 | 340/50 | BSW | √ | √ | √ |
| 245/45R20 | 103V XL | 8J | 243 | 728 | 875 | 1929 | 340/50 | BSW | √ | √ | √ |
| 245/50R20 | 105H XL | 7 1/2J | 253 | 754 | 925 | 2039 | 340/50 | BSW | √ | √ | √ |
| 255/35R20 | 97V XL | 9J | 260 | 686 | 730 | 1609 | 340/50 | BSW | √ | √ | √ |
| 255/40R20 | 101V XL | 9J | 260 | 712 | 825 | 1819 | 340/50 | BSW | √ | √ | √ |
| 255/45R20 | 105V XL | 8 1/2J | 255 | 738 | 925 | 2039 | 340/50 | BSW | √ | √ | √ |

WINTER

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ICECRUISER II

## Optimal of tread pattern of directional tire

The single-guide and wide block design of shoulder chamfer can maximize the traction and the anti-skid performance and traction on the corners while improving the grip.




## Special vertical and horizontal groove staggered design

The special staggered design of longitudinal and lateral grooves can effectively disperse the noise frequency and shorten the braking distance by 50% on icy and snowy roads.


## Combination design of S-shaped and I-shaped groove

The combined design of S-shaped fine grooves and I-shaped straight grooves further strengthens the tire contact area and ensures the grip and guidance of snowy and slippery roads.




## New silica formula design

The new silica formula design keeps the rubber soft at -30°C to -40°C, can better fit the road surface, and increase the tire contact area and the friction coefficient between the tread and the ice surface.




WINTER

| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 255/55R18 | 109HXL | 8J | 265 | 737 | 1030 | 2271 | 340/50 | BSW | √ | √ | √ |
| 265/35R18 | 97VXL | 9 1/2J | 271 | 643 | 730 | 1609 | 340/50 | BSW | √ | √ | √ |
| 275/40R18 | 103H XL | 9 1/2J | 278 | 677 | 875 | 1929 | 340/50 | BSW | √ | √ | √ |
| NEW 235/40R19 | 96VXL | 8 1/2J | 241 | 671 | 710 | 1565 | 340/50 | BSW | √ | √ | √ |
| 245/40R19 | 98VXL | 8 1/2J | 248 | 679 | 750 | 1653 | 340/50 | BSW | √ | √ | √ |
| 245/40R19 | 98VXL | 8 1/2J | 248 | 679 | 750 | 1653 | 340/50 | BSW | √ | √ | √ |
| 245/45R19 | 102HXL | 8J | 243 | 703 | 850 | 1874 | 340/50 | BSW | √ | √ | √ |
| 245/55R19 | 107HXL | 7 1/2J | 253 | 753 | 975 | 2149 | 340/50 | BSW | √ | √ | √ |
| 255/50R19 | 107HXL | 8J | 265 | 739 | 975 | 2149 | 340/50 | BSW | √ | √ | √ |
| 255/55R19 | 111HXL | 8J | 265 | 763 | 1090 | 2403 | 340/50 | BSW | √ | √ | √ |
| 265/50R19 | 110H XL | 8 1/2J | 277 | 749 | 1060 | 2337 | 340/50 | BSW | √ | √ | √ |
| 265/55R19 | 113TXL | 8 1/2J | 277 | 775 | 1150 | 2535 | 340/50 | BSW | √ | √ | √ |
| 275/35R19 | 100VXL | 9 1/2J | 278 | 675 | 800 | 1764 | 340/50 | BSW | √ | √ | √ |
| 275/40R19 | 105VXL | 9 1/2J | 278 | 703 | 925 | 2039 | 340/50 | BSW | √ | √ | √ |
| 275/55R19 | 111H | 8 1/2J | 284 | 785 | 1090 | 2403 | 300/44 | BSW | √ | √ | √ |
| 285/45R19 | 111HXL | 9 1/2J | 285 | 739 | 1090 | 2403 | 340/50 | BSW | √ | √ | √ |
| 245/40R20 | 99VXL | 8 1/2J | 248 | 704 | 775 | 1709 | 340/50 | BSW | √ | √ | √ |
| 245/45R20 | 103VXL | 8J | 243 | 728 | 875 | 1929 | 340/50 | BSW | √ | √ | √ |
| 255/45R20 | 105VXL | 8 1/2J | 255 | 738 | 925 | 2039 | 340/50 | BSW | √ | √ | √ |
| 255/50R20 | 109HXL | 8J | 265 | 764 | 1030 | 2271 | 340/50 | BSW | √ | √ | √ |
| 255/55R20 | 110HXL | 8J | 265 | 788 | 1060 | 2337 | 340/50 | BSW | √ | √ | √ |
| 265/35R20 | 99H XL | 9 1/2J | 271 | 694 | 775 | 1709 | 340/50 | BSW | √ | √ | √ |
| 265/45R20 | 108HXL | 9J | 266 | 746 | 1000 | 2205 | 340/50 | BSW | √ | √ | √ |
| 265/50R20 | 111H XL | 8 1/2J | 277 | 774 | 1090 | 2403 | 340/50 | BSW | √ | √ | √ |
| 275/30R20 | 97H XL | 9 1/2J | 278 | 674 | 730 | 1609 | 340/50 | BSW | √ | √ | √ |
| 275/35R20 | 102HXL | 9 1/2J | 278 | 700 | 850 | 1874 | 340/50 | BSW | √ | √ | √ |
| 275/40R20 | 106HXL | 9 1/2J | 278 | 728 | 950 | 2094 | 340/50 | BSW | √ | √ | √ |
| 275/45R20 | 110HXL | 9J | 273 | 756 | 1060 | 2337 | 340/50 | BSW | √ | √ | √ |
| 275/50R20 | 113HXL | 8 1/2J | 284 | 784 | 1150 | 2535 | 340/50 | BSW | √ | √ | √ |
| 275/55R20 | 117SXL | 8 1/2J | 284 | 810 | 1285 | 2833 | 340/50 | BSW | √ | √ | √ |
| 285/30R20 | 99H XL | 10J | 290 | 680 | 775 | 1709 | 340/50 | BSW | √ | √ | √ |
| NEW 285/45R20 | 112HXL | 9 1/2J | 285 | 764 | 1120 | 2469 | 340/50 | BSW | √ | √ | √ |
| 285/50R20 | 116HXL | 9J | 297 | 794 | 1250 | 2756 | 340/50 | BSW | √ | √ | √ |
| 305/40R20 | 112HXL | 11J | 313 | 752 | 1120 | 2469 | 340/50 | BSW | √ | √ | √ |
| 315/35R20 | 110VXl | 11J | 320 | 728 | 1060 | 2337 | 340/50 | BSW | √ | √ | √ |
| NEW 255/40R21 | 102V | 9J | 260 | 737 | 850 | 1874 | 340/50 | BSW | √ | √ | √ |
| 265/45R21 | 108HXL | 9J | 266 | 771 | 1000 | 2205 | 340/50 | BSW | √ | √ | √ |
| 275/40R21 | 107HXL | 9 1/2J | 278 | 753 | 975 | 2149 | 340/50 | BSW | √ | √ | √ |
| 275/45R21 | 110HXL | 9J | 273 | 781 | 1060 | 2337 | 340/50 | BSW | √ | √ | √ |
| 275/50R21 | 113HXL | 8 1/2J | 284 | 809 | 1150 | 2535 | 340/50 | BSW | √ | √ | √ |
| 285/40R21 | 109HXL | 10J | 290 | 761 | 1030 | 2271 | 340/50 | BSW | √ | √ | √ |
| NEW 285/45R21 | 113HXL | 9 1/2J | 285 | 789 | 1150 | 2535 | 340/50 | BSW | √ | √ | √ |
| 295/35R21 | 107HXL | 10 1/2J | 301 | 739 | 975 | 2149 | 340/50 | BSW | √ | √ | √ |
| 295/40R21 | 111HXL | 10 1/2J | 301 | 769 | 1090 | 2403 | 340/50 | BSW | √ | √ | √ |
| 315/35R21 | 111HXL | 11J | 320 | 753 | 1090 | 2403 | 340/50 | BSW | √ | √ | √ |
| 315/40R21 | 115HXL | 11J | 320 | 785 | 1215 | 2679 | 340/50 | BSW | √ | √ | √ |
| NEW 265/40R22 | 106HXL | 9 1/2J | 271 | 771 | 950 | 2094 | 340/50 | BSW | √ | √ | √ |
| 275/40R22 | 107HXL | 9 1/2J | 278 | 779 | 975 | 2149 | 340/50 | BSW | √ | √ | √ |
| NEW 285/40R22 | 110HXL | 10J | 290 | 787 | 1060 | 2337 | 340/50 | BSW | √ | √ | √ |
| 315/35R22 | 111H XL | 11J | 320 | 779 | 1090 | 2403 | 340/50 | BSW | √ | √ | √ |

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ROCK 868S

## Asymmetric pattern design for winter tire

The high saturation pattern on the outside ensures the handling performance of the tire;the wide grooves in the inside ensure the drainage performance of the tire and prevent sideslip.


## Zigzag longitudinal pattern groove on both sides

The zigzag groove design establishes a meshing effect between the tire and the snow surface, constantly pressing and displacing snow, and improving the stability of driving on snow. According to the width of the driving surface, the reasonable layout of 3-4 pattern longitudinal wide pattern groove efficient drainage, mud and snow, greatly improve the tire skid performance. At the same time, the segmented longitudinal continuous ribs provide excellent handling performance.


## 3D zigzag steel sheet design and optimized distribution

Inside: high-density steel sheet distribution to achieve the best traction/braking performance on snow and ice road;

Outside: relatively low density steel sheet distribution to maintain excellent handling performance




## New Formulation design with silica

The tire using new formula design with silica makes the rubber still maintain viscoelastic properties even in -30°C to -40°C, and it can better fit the road, increase the tire contact area and the friction coefficient between the tread and the ice surface, so makes driving safer in winter when it rains and snows.




WINTER

| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 155/65R13 | 73T | 4.50B | 157 | 532 | 365 | 805 | 300/44 | BSW | √ | √ | √ |
| 155/70R13 | 75T | 4 1/2J | 157 | 548 | 387 | 853 | 300/44 | BSW | √ | √ | √ |
| 165/70R13 | 79T | 5.00B | 170 | 562 | 437 | 963 | 300/44 | BSW | √ | √ | √ |
| 155/65R14 | 75T | 4 1/2J | 157 | 558 | 387 | 853 | 300/44 | BSW | √ | √ | √ |
| 165/65R14 | 79T | 5J | 170 | 570 | 437 | 963 | 300/44 | BSW | √ | √ | √ |
| 165/70R14 | 85TXL | 5J | 170 | 588 | 515 | 1135 | 340/50 | BSW | √ | √ | √ |
| 175/70R14 | 88T | 5J | 177 | 602 | 560 | 1235 | 340/50 | BSW | √ | √ | √ |
| 185/60R14 | 82T | 5 1/2J | 189 | 578 | 475 | 1047 | 300/44 | BSW | √ | √ | √ |
| 185/65R14 | 86H | 5 1/2J | 189 | 596 | 530 | 1168 | 300/44 | BSW | √ | √ | √ |
| 195/60R14 | 86H | 6J | 201 | 590 | 530 | 1168 | 300/44 | BSW | √ | √ | √ |
| 175/65R15 | 84T | 5J | 177 | 609 | 500 | 1102 | 300/44 | BSW | √ | √ | √ |
| 185/60R15 | 84H | 5 1/2J | 189 | 603 | 500 | 1102 | 300/44 | BSW | √ | √ | √ |
| 185/65R15 | 88H | 5 1/2J | 189 | 621 | 560 | 1235 | 300/44 | BSW | √ | √ | √ |
| 195/55R15 | 85V | 6J | 201 | 595 | 515 | 1135 | 300/44 | BSW | √ | √ | √ |
| 195/60R15 | 88H | 6J | 201 | 615 | 560 | 1235 | 300/44 | BSW | √ | √ | √ |
| 195/65R15 | 95T | 6J | 201 | 635 | 690 | 1521 | 340/50 | BSW | √ | √ | √ |
| 205/65R15 | 94H | 6J | 209 | 647 | 670 | 1477 | 300/44 | BSW | √ | √ | √ |
| 215/70R15 | 98T | 6 1/2J | 221 | 683 | 750 | 1653 | 300/44 | BSW | √ | √ | √ |
| 195/55R16 | 91H XL | 6J | 201 | 620 | 615 | 1356 | 340/50 | BSW | √ | √ | √ |
| 195/60R16 | 89H | 6J | 201 | 640 | 580 | 1279 | 300/44 | BSW | √ | √ | √ |
| 205/55R16 | 91H | 6 1/2J | 214 | 632 | 615 | 1356 | 300/44 | BSW | √ | √ | √ |
| 205/60R16 | 96H | 6J | 209 | 652 | 710 | 1565 | 340/50 | BSW | √ | √ | √ |
| 215/55R16 | 97H XL | 7J | 226 | 642 | 730 | 1609 | 340/50 | BSW | √ | √ | √ |
| 215/60R16 | 99H | 6 1/2J | 221 | 664 | 775 | 1709 | 340/50 | BSW | √ | √ | √ |
| 215/70R16 | 100T | 6 1/2J | 221 | 708 | 800 | 1763 | 300/44 | BSW | √ | √ | √ |
| 225/70R16 | 107TXL | 6 1/2J | 228 | 722 | 975 | 2149 | 340/50 | BSW | √ | √ | √ |
| 235/60R16 | 100H | 7J | 240 | 688 | 800 | 1764 | 300/44 | BSW | √ | √ | √ |
| 245/70R16 | 111TXL | 7J | 248 | 750 | 1090 | 2403 | 340/50 | BSW | √ | √ | √ |
| 265/70R16 | 112T | 8J | 272 | 778 | 1120 | 2469 | 300/44 | BSW | √ | √ | √ |
| 205/50R17 | 93H XL | 6 1/2J | 214 | 638 | 650 | 1433 | 340/50 | BSW | √ | √ | √ |
| 215/50R17 | 95H XL | 7J | 226 | 648 | 690 | 1521 | 340/50 | BSW | √ | √ | √ |
| 215/55R17 | 98V | 7 J | 226 | 668 | 750 | 1653 | 340/50 | BSW | √ | √ | √ |
| 215/60R17 | 96H | 6 1/2J | 221 | 690 | 710 | 1565 | 300/44 | BSW | √ | √ | √ |
| 225/50R17 | 98H XL | 7J | 233 | 658 | 750 | 1653 | 340/50 | BSW | √ | √ | √ |
| 225/55R17 | 101V | 7J | 233 | 680 | 825 | 1819 | 340/50 | BSW | √ | √ | √ |
| 225/60R17 | 99H | 6 1/2J | 228 | 702 | 775 | 1709 | 300/44 | BSW | √ | √ | √ |
| 225/65R17 | 102H | 6 1/2J | 228 | 724 | 850 | 1874 | 300/44 | BSW | √ | √ | √ |
| 235/45R17 | 97H XL | 8J | 236 | 644 | 730 | 1609 | 340/50 | BSW | √ | √ | √ |
| 235/55R17 | 103H XL | 7 1/2J | 245 | 690 | 875 | 1929 | 340/50 | BSW | √ | √ | √ |
| 235/60R17 | 102H | 7 J | 240 | 714 | 850 | 1873 | 300/44 | BSW | √ | √ | √ |
| 235/65R17 | 108T XL | 7J | 240 | 738 | 1000 | 2205 | 340/50 | BSW | √ | √ | √ |
| 245/65R17 | 107S | 7 J | 248 | 750 | 975 | 2149 | 300/44 | BSW | √ | √ | √ |
| 255/60R17 | 110TXL | 7 1/2J | 260 | 738 | 1060 | 2337 | 340/50 | BSW | √ | √ | √ |
| 265/65R17 | 112T | 8J | 272 | 776 | 1120 | 2469 | 300/44 | BSW | √ | √ | √ |
| 265/70R17 | 115T | 8J | 272 | 804 | 1215 | 2678 | 300/44 | BSW | √ | √ | √ |
| 225/40R18 | 92H XL | 8J | 230 | 637 | 630 | 1389 | 340/50 | BSW | √ | √ | √ |
| 225/45R18 | 95H XL | 7 1/2J | 225 | 659 | 690 | 1521 | 340/50 | BSW | √ | √ | √ |
| 225/60R18 | 104HXL | 6 1/2J | 228 | 727 | 900 | 1984 | 340/50 | BSW | √ | √ | √ |
| 235/45R18 | 98H XL | 8J | 236 | 669 | 750 | 1653 | 340/50 | BSW | √ | √ | √ |
| 235/60R18 | 107H XL | 7J | 240 | 739 | 975 | 2149 | 340/50 | BSW | √ | √ | √ |
| 245/40R18 | 97VXL | 8 1/2J | 248 | 653 | 730 | 1609 | 340/50 | BSW | √ | √ | √ |
| 245/45R18 | 100H XL | 8J | 243 | 677 | 800 | 1764 | 340/50 | BSW | √ | √ | √ |
| 245/60R18 | 105H | 7J | 248 | 751 | 925 | 2039 | 300/44 | BSW | √ | √ | √ |
| 255/55R18 | 109H XL | 8J | 265 | 737 | 1030 | 2271 | 340/50 | BSW | √ | √ | √ |
| 255/60R18 | 112TXL | 7 1/2J | 260 | 763 | 1120 | 2469 | 340/50 | BSW | √ | √ | √ |
| 265/60R18 | 110T | 8J | 272 | 775 | 1060 | 2337 | 300/44 | BSW | √ | √ | √ |
| 265/70R18 | 116S | 8J | 272 | 829 | 1250 | 2756 | 300/44 | BSW | √ | √ | √ |
| 285/60R18 | 116H | 8 1/2J | 292 | 799 | 1250 | 2756 | 300/44 | BSW | √ | √ | √ |
| 235/55R19 | 105HXL | 7 1/2J | 245 | 741 | 925 | 2039 | 340/50 | BSW | √ | √ | √ |
| 245/45R19 | 102HXL | 8J | 243 | 703 | 850 | 1874 | 340/50 | BSW | √ | √ | √ |
| 245/55R19 | 107HXL | 7 1/2J | 253 | 753 | 975 | 2149 | 340/50 | BSW | √ | √ | √ |
| 255/50R19 | 107HXL | 8J | 265 | 739 | 975 | 2149 | 340/50 | BSW | √ | √ | √ |
| 255/55R19 | 111HXL | 8J | 265 | 763 | 1090 | 2403 | 340/50 | BSW | √ | √ | √ |
| 255/45R20 | 105VXL | 8 1/2J | 255 | 738 | 925 | 2039 | 340/50 | BSW | √ | √ | √ |
| 275/40R20 | 106HXL | 9 1/2J | 278 | 728 | 950 | 2094 | 340/50 | BSW | √ | √ | √ |
| 275/45R20 | 110H XL | 9J | 273 | 756 | 1060 | 2337 | 340/50 | BSW | √ | √ | √ |
| 275/60R20 | 119HXL | 8J | 279 | 838 | 1360 | 2998 | 340/50 | BSW | √ | √ | √ |
| 315/35R20 | 110VXL | 11J | 320 | 728 | 1060 | 2337 | 340/50 | BSW | √ | √ | √ |

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# ROCK 989S

## The tacit connection of the longitudinal and transverse grooves complemented by a fine and tortuous sipe design

Effective elimination of snow and better grip to greatly increase the adhesion to ice and snow, eliminate hydroplanning and improve mud & snow shedding and self-cleaning performance.

Self-cleaning

## Combination design of shoulder blocks and special sipe

Effectively equalize the rigidity of the block to ensure excellent turning performance and handling; combined design of the block and the sipe to significantly increase the number of lateral grooves without affecting the overall rigidity of the block, more and further balanced contact area on the snow and ice road for better braking performance.

Combination Design

## Special compound design for winter pattern

Improve the traction and grip of winter tires on snow and ice.

Special Compound Design

## Optimized contour design and layout

Provides smooth operation and even pressure distribution.

Even Pressure Distribution

WINTER

| Size | LI/SI | PR | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 165/70R14C | 89/87R | 6PR | 5J | 170 | 588 | 580/545 | 1279/1202 | 375/54 | BSW | √ | √ | √ |
| 175/65R14C | 90/88T | 6PR | 5J | 177 | 584 | 600/560 | 1323/1235 | 375/54 | BSW | √ | √ | √ |
| 175/70R14C | 95/93T | 6PR | 5J | 177 | 602 | 690/650 | 1521/1433 | 375/54 | BSW | √ | √ | √ |
| 175R14C | 99/97R | 8PR | 5J | 177 | 636 | 775/730 | 1709/1609 | 450/65 | BSW | √ | √ | √ |
| 185R14C | 102/100R | 8PR | 5 1/2J | 188 | 650 | 850/800 | 1874/1764 | 450/65 | BSW | √ | √ | √ |
| NEW 185R15C | 103/102R | 8PR | 5 1/2J | 188 | 674 | 875/850 | 1930/1875 | 450/65 | BSW | √ | √ | √ |
| NEW 195R15C | 106/104R | 8PR | 5 1/2J | 198 | 690 | 950/900 | 2095/1985 | 450/65 | BSW | √ | √ | √ |
| 195/70R15C | 104/102R | 8PR | 6J | 201 | 655 | 900/850 | 1984/1874 | 450/65 | BSW | √ | √ | √ |
| 205/70R15C | 106/104R | 8PR | 6J | 209 | 669 | 950/900 | 2094/1984 | 450/65 | BSW | √ | √ | √ |
| 215/65R15C | 104/102R | 6PR | 6 1/2J | 221 | 661 | 900/850 | 1984/1874 | 375/54 | BSW | √ | √ | √ |
| 215/70R15C | 109/107R | 8PR | 6 1/2J | 221 | 683 | 1030/975 | 2271/2149 | 450/65 | BSW | √ | √ | √ |
| 225/70R15C | 112/110R | 8PR | 6 1/2J | 228 | 697 | 1120/1060 | 2469/2337 | 450/65 | BSW | √ | √ | √ |
| 175/75R16C | 98/96R | 6PR | 5J | 177 | 668 | 750/710 | 1653/1565 | 375/54 | BSW | √ | √ | √ |
| 185/75R16C | 104/102R | 8PR | 5J | 184 | 684 | 900/850 | 1984/1874 | 475/69 | BSW | √ | √ | √ |
| 195/60R16C | 99/97H | 6PR | 6J | 201 | 640 | 775/730 | 1709/1609 | 375/54 | BSW | √ | √ | √ |
| 195/65R16C | 104/102R | 8PR | 6J | 201 | 660 | 900/850 | 1984/1874 | 475/69 | BSW | √ | √ | √ |
| 195/75R16C | 107/105R | 8PR | 5 1/2J | 196 | 698 | 975/925 | 2149/2039 | 475/69 | BSW | √ | √ | √ |
| 205/65R16C | 107/105R | 8PR | 6J | 209 | 672 | 975/925 | 2149/2039 | 475/69 | BSW | √ | √ | √ |
| 205/75R16C | 110/108R | 8PR | 5 1/2J | 203 | 714 | 1060/1000 | 2337/2204 | 475/69 | BSW | √ | √ | √ |
| 215/60R16C | 103/101T | 6PR | 6 1/2J | 221 | 664 | 875/825 | 1929/1819 | 375/54 | BSW | √ | √ | √ |
| 215/65R16C | 109/107R | 8PR | 6 1/2J | 221 | 686 | 1030/975 | 2271/2149 | 475/69 | BSW | √ | √ | √ |
| 215/75R16C | 113/111R | 8PR | 6J | 216 | 728 | 1150/1090 | 2535/2403 | 475/69 | BSW | √ | √ | √ |
| 225/65R16C | 112/110R | 8PR | 6 1/2J | 228 | 698 | 1120/1060 | 2469/2337 | 475/69 | BSW | √ | √ | √ |
| 225/75R16C | 116/114R | 8PR | 6J | 223 | 744 | 1250/1180 | 2756/2601 | 475/69 | BSW | √ | √ | √ |
| 235/65R16C | 115/113R | 8PR | 7J | 240 | 712 | 1215/1150 | 2679/2535 | 475/69 | BSW | √ | √ | √ |

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# WINTERPLUS STUD I


## Balanced design

The directional pattern design ensures the grip on ice and snow, while taking into account the wear, rolling resistance and silent design. It is a classic tire with balanced comprehensive performance.

## Wide driving surface plus square shoulder design

The tread area of the tire is increased, the stress is reduced, and the braking and starting performance of the tire is better.


## High stiffness shoulder design

The larger shoulder pattern block design matches the pattern block stiffness design, effectively improving the handling performance and wear performance.


## Design of continuous rib in crown center

It ensures the stability of straight line driving and the driving safety.


## Nail hole protection design

Strengthen the rigidity of the tread block around the nail to prevent the drop of the insert or the tear of the nail hole during the driving process of the tire. The snowflake logo design makes the appearance of the tire more eye-catching and beautiful.




WINTER

| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 155/70R13 | 75T | 4.50B | 157 | 548 | 387 | 853 | 300/44 | BSW | √ | √ | √ |
| 175/70R13 | 82T | 5.00B | 177 | 576 | 475 | 1047 | 300/44 | BSW | √ | √ | √ |
| 175/65R14 | 86T XL | 5J | 177 | 584 | 530 | 1168 | 340/50 | BSW | √ | √ | √ |
| 175/70R14 | 84T | 5J | 177 | 602 | 500 | 1102 | 300/44 | BSW | √ | √ | √ |
| 185/60R14 | 82T | 5 1/2J | 189 | 578 | 475 | 1047 | 300/44 | BSW | √ | √ | √ |
| 185/65R14 | 90T XL | 5 1/2J | 189 | 596 | 600 | 1323 | 340/50 | BSW | √ | √ | √ |
| 185/70R14 | 92T XL | 5 1/2J | 189 | 616 | 630 | 1389 | 340/50 | BSW | √ | √ | √ |
| 185/55R15 | 86T XL | 6J | 194 | 585 | 530 | 1168 | 340/50 | BSW | √ | √ | √ |
| 185/60R15 | 88T XL | 5 1/2J | 189 | 603 | 560 | 1235 | 340/50 | BSW | √ | √ | √ |
| 185/65R15 | 88T | 5 1/2J | 189 | 621 | 560 | 1235 | 300/44 | BSW | √ | √ | √ |
| 195/55R15 | 85H | 6J | 201 | 595 | 515 | 1135 | 300/44 | BSW | √ | √ | √ |
| 195/60R15 | 92T XL | 6J | 201 | 615 | 630 | 1389 | 340/50 | BSW | √ | √ | √ |
| 195/65R15 | 95TXL | 6J | 201 | 635 | 690 | 1521 | 340/50 | BSW | √ | √ | √ |
| 205/65R15 | 94T | 6J | 209 | 647 | 670 | 1477 | 300/44 | BSW | √ | √ | √ |
| 195/55R16 | 91T XL | 6J | 201 | 620 | 615 | 1356 | 340/50 | BSW | √ | √ | √ |
| 205/55R16 | 94T XL | 6 1/2J | 214 | 632 | 670 | 1477 | 340/50 | BSW | √ | √ | √ |
| 205/60R16 | 96T XL | 6J | 209 | 652 | 710 | 1565 | 340/50 | BSW | √ | √ | √ |
| 205/65R16 | 95T | 6 J | 209 | 672 | 690 | 1521 | 300/44 | BSW | √ | √ | √ |
| 215/55R16 | 97T XL | 7J | 226 | 642 | 730 | 1609 | 340/50 | BSW | √ | √ | √ |
| 215/60R16 | 99T XL | 6 1/2J | 221 | 664 | 775 | 1709 | 340/50 | BSW | √ | √ | √ |
| 215/65R16 | 102T XL | 6 1/2J | 221 | 686 | 850 | 1874 | 340/50 | BSW | √ | √ | √ |

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# WINTERPLUS STUD II


## Balanced design

The large V-shaped pattern design ensures the grip on ice and snow, while taking into account the wear, rolling resistance and silent design. It is a classic tire with balanced comprehensive performance.


## Wide driving surface plus square shoulder design

The tread area of the tire is increased, the stress is reduced, and the braking and starting performance of the tire is better.


## Widened guiding groove and serrated shoulder design

Effectively improve the tire snow removal ability under snow cover, and enhance the vehicle snow safety.


## AB composite pitch design

The computer pitch is arranged irregularly based on genetic algorithm, which effectively reduces the tire noise and improves the comfort of drivers and passengers.


## Nail hole protection design

Strengthen the rigidity of the tread block around the nail to prevent the drop of the insert nail or the tear of the nail hole during the driving process of the tire. The snowflake logo design makes the appearance of the tire more eye-catching and beautiful.


WINTER

| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 205/50R17 | 93T XL | 6 1/2J | 214 | 638 | 650 | 1433 | 340/50 | BSW | √ | √ | √ |
| NEW 205/55R17 | 95TXL | 6 1/2J | 214 | 658 | 690 | 1521 | 340/50 | BSW | √ | √ | √ |
| 215/45R17 | 91TXL | 7J | 213 | 626 | 615 | 1356 | 340/50 | BSW | √ | √ | √ |
| 215/50R17 | 95T XL | 7J | 226 | 648 | 690 | 1521 | 340/50 | BSW | √ | √ | √ |
| 215/55R17 | 98T XL | 7J | 226 | 668 | 750 | 1653 | 340/50 | BSW | √ | √ | √ |
| 225/45R17 | 94H XL | 7 1/2J | 225 | 634 | 670 | 1477 | 340/50 | BSW | √ | √ | √ |
| 225/50R17 | 98H XL | 7J | 233 | 658 | 750 | 1653 | 340/50 | BSW | √ | √ | √ |
| 225/55R17 | 101HXL | 7J | 233 | 680 | 825 | 1819 | 340/50 | BSW | √ | √ | √ |
| 235/45R17 | 97TXL | 8J | 236 | 644 | 730 | 1609 | 340/50 | BSW | √ | √ | √ |
| 235/55R17 | 103TXL | 7 1/2J | 245 | 690 | 875 | 1929 | 340/50 | BSW | √ | √ | √ |
| 215/55R18 | 95T | 7J | 226 | 693 | 690 | 1521 | 300/44 | BSW | √ | √ | √ |
| 225/40R18 | 92TXL | 8J | 230 | 637 | 630 | 1389 | 340/50 | BSW | √ | √ | √ |
| 225/45R18 | 95T XL | 7 1/2J | 225 | 659 | 690 | 1521 | 340/50 | BSW | √ | √ | √ |
| 225/50R18 | 99TXL | 7J | 233 | 683 | 775 | 1709 | 340/50 | BSW | √ | √ | √ |
| 225/55R18 | 102TXL | 7J | 233 | 705 | 850 | 1874 | 340/50 | BSW | √ | √ | √ |
| 235/45R18 | 98TXL | 8J | 236 | 669 | 750 | 1653 | 340/50 | BSW | √ | √ | √ |
| 235/50R18 | 101TXL | 7 1/2J | 245 | 693 | 825 | 1819 | 340/50 | BSW | √ | √ | √ |
| 245/40R18 | 97T XL | 8 1/2J | 248 | 653 | 730 | 1609 | 340/50 | BSW | √ | √ | √ |
| 245/45R18 | 100T XL | 8J | 243 | 677 | 800 | 1764 | 340/50 | BSW | √ | √ | √ |
| 255/35R18 | 94TXL | 9J | 260 | 635 | 670 | 1477 | 340/50 | BSW | √ | √ | √ |
| 255/40R18 | 99TXL | 9J | 260 | 661 | 775 | 1709 | 340/50 | BSW | √ | √ | √ |
| NEW 265/35R18 | 97TXL | 9 1/2J | 271 | 643 | 730 | 1609 | 340/50 | BSW | √ | √ | √ |
| 275/40R18 | 103TXL | 9 1/2J | 278 | 677 | 875 | 1929 | 340/50 | BSW | √ | √ | √ |
| NEW 225/40R19 | 93TXL | 8J | 230 | 663 | 650 | 1433 | 340/50 | BSW | √ | √ | √ |
| NEW 225/55R19 | 103TXL | 7J | 233 | 731 | 875 | 1929 | 340/50 | BSW | √ | √ | √ |
| 235/35R19 | 91TXL | 8 1/2J | 241 | 647 | 615 | 1356 | 340/50 | BSW | √ | √ | √ |
| NEW 235/40R19 | 96TXL | 8 1/2J | 241 | 671 | 710 | 1565 | 340/50 | BSW | √ | √ | √ |
| 235/50R19 | 103TXL | 7 1/2J | 245 | 719 | 875 | 1929 | 340/50 | BSW | √ | √ | √ |
| 245/40R19 | 98TXL | 8 1/2J | 248 | 679 | 750 | 1653 | 340/50 | BSW | √ | √ | √ |
| 245/45R19 | 98T | 8J | 243 | 703 | 750 | 1653 | 300/44 | BSW | √ | √ | √ |
| 255/35R19 | 96T XL | 9J | 260 | 661 | 710 | 1565 | 340/50 | BSW | √ | √ | √ |
| NEW 255/40R19 | 100TXL | 9J | 260 | 687 | 800 | 1764 | 340/50 | BSW | √ | √ | √ |
| 255/45R19 | 104T XL | 8 1/2J | 255 | 713 | 900 | 1984 | 340/50 | BSW | √ | √ | √ |
| 255/50R19 | 103T | 8J | 265 | 739 | 875 | 1929 | 300/44 | BSW | √ | √ | √ |
| NEW 265/55R19 | 113TXL | 8 1/2J | 277 | 775 | 1150 | 2535 | 340/50 | BSW | √ | √ | √ |
| NEW 275/35R19 | 100TXL | 9 1/2J | 278 | 675 | 800 | 1764 | 340/50 | BSW | √ | √ | √ |
| 275/40R19 | 105TXL | 9 1/2J | 278 | 703 | 925 | 2039 | 340/50 | BSW | √ | √ | √ |
| NEW 285/45R19 | 111TXL | 9 1/2J | 285 | 739 | 1090 | 2403 | 340/50 | BSW | √ | √ | √ |
| 235/55R20 | 102T | 7 1/2J | 245 | 766 | 850 | 1874 | 300/44 | BSW | √ | √ | √ |
| 245/40R20 | 99TXL | 8 1/2J | 248 | 704 | 775 | 1709 | 340/50 | BSW | √ | √ | √ |
| NEW 245/45R20 | 103TXL | 8J | 243 | 728 | 875 | 1929 | 340/50 | BSW | √ | √ | √ |
| NEW 245/50R20 | 105TXL | 7 1/2J | 253 | 754 | 925 | 2039 | 340/50 | BSW | √ | √ | √ |
| NEW 255/35R20 | 97TXL | 9J | 260 | 686 | 730 | 1609 | 340/50 | BSW | √ | √ | √ |
| NEW 255/40R20 | 101TXL | 9J | 260 | 712 | 825 | 1819 | 340/50 | BSW | √ | √ | √ |
| 255/45R20 | 101T | 8 1/2J | 255 | 738 | 825 | 1819 | 300/44 | BSW | √ | √ | √ |
| NEW 255/50R20 | 109TXL | 8J | 265 | 764 | 1030 | 2271 | 340/50 | BSW | √ | √ | √ |
| 255/55R20 | 110TXL | 8J | 265 | 788 | 1060 | 2337 | 340/50 | BSW | √ | √ | √ |
| NEW 265/45R20 | 108TXL | 9J | 266 | 746 | 1000 | 2205 | 340/50 | BSW | √ | √ | √ |
| NEW 265/50R20 | 107T | 8 1/2J | 277 | 774 | 975 | 2149 | 300/44 | BSW | √ | √ | √ |
| 275/35R20 | 102TXL | 9 1/2J | 278 | 700 | 850 | 1874 | 340/50 | BSW | √ | √ | √ |
| 275/40R20 | 102T | 9 1/2J | 278 | 728 | 850 | 1874 | 300/44 | BSW | √ | √ | √ |
| 275/45R20 | 110T XL | 9J | 273 | 756 | 1060 | 2337 | 340/50 | BSW | √ | √ | √ |
| 275/50R20 | 113TXL | 8 1/2J | 284 | 784 | 1150 | 2535 | 340/50 | BSW | √ | √ | √ |
| 285/50R20 | 112T | 9J | 297 | 794 | 1120 | 2469 | 300/44 | BSW | √ | √ | √ |
| NEW 305/40R20 | 112TXL | 11J | 313 | 752 | 1120 | 2469 | 340/50 | BSW | √ | √ | √ |
| 315/35R20 | 106T | 11J | 320 | 728 | 950 | 2094 | 300/44 | BSW | √ | √ | √ |
| NEW 255/40R21 | 102TXL | 9J | 260 | 737 | 850 | 1874 | 340/50 | BSW | √ | √ | √ |
| NEW 255/45R21 | 106TXL | 8 1/2J | 255 | 763 | 950 | 2094 | 340/50 | BSW | √ | √ | √ |
| NEW 265/45R21 | 108TXL | 9J | 266 | 771 | 1000 | 2205 | 340/50 | BSW | √ | √ | √ |
| NEW 275/35R21 | 103TXL | 9 1/2J | 278 | 725 | 875 | 1929 | 340/50 | BSW | √ | √ | √ |
| 275/40R21 | 107TXL | 9 1/2J | 278 | 753 | 975 | 2149 | 340/50 | BSW | √ | √ | √ |
| 275/45R21 | 110T XL | 9J | 273 | 781 | 1060 | 2337 | 340/50 | BSW | √ | √ | √ |
| NEW 285/35R21 | 105TXL | 10J | 290 | 733 | 925 | 2039 | 340/50 | BSW | √ | √ | √ |
| NEW 285/40R21 | 109TXL | 10J | 290 | 761 | 1030 | 2271 | 340/50 | BSW | √ | √ | √ |
| NEW 285/45R21 | 113TXL | 9 1/2J | 285 | 789 | 1150 | 2535 | 340/50 | BSW | √ | √ | √ |
| NEW 295/35R21 | 107TXL | 10 1/2J | 301 | 739 | 975 | 2149 | 340/50 | BSW | √ | √ | √ |
| 295/40R21 | 107T | 10 1/2J | 301 | 769 | 975 | 2149 | 300/44 | BSW | √ | √ | √ |
| NEW 315/30R21 | 105TXL | 11J | 320 | 723 | 925 | 2039 | 340/50 | BSW | √ | √ | √ |
| 315/35R21 | 111T XL | 11J | 320 | 753 | 1090 | 2403 | 340/50 | BSW | √ | √ | √ |
| NEW 315/40R21 | 111T | 11J | 320 | 785 | 1090 | 2403 | 300/44 | BSW | √ | √ | √ |
| NEW 265/40R22 | 106TXL | 9 1/2J | 271 | 771 | 950 | 2094 | 340/50 | BSW | √ | √ | √ |
| NEW 275/35R22 | 104TXL | 9 1/2J | 278 | 751 | 900 | 1984 | 340/50 | BSW | √ | √ | √ |
| 275/40R22 | 107TXL | 9 1/2J | 278 | 779 | 975 | 2149 | 340/50 | BSW | √ | √ | √ |
| NEW 275/50R22 | 115TXL | 8 1/2J | 284 | 835 | 1215 | 2679 | 340/50 | BSW | √ | √ | √ |
| NEW 285/35R22 | 106TXL | 10J | 290 | 759 | 950 | 2094 | 340/50 | BSW | √ | √ | √ |
| NEW 285/40R22 | 110TXL | 10J | 290 | 787 | 1060 | 2337 | 340/50 | BSW | √ | √ | √ |
| NEW 285/45R22 | 114TXL | 9 1/2J | 285 | 815 | 1180 | 2601 | 340/50 | BSW | √ | √ | √ |
| NEW 315/30R22 | 107TXL | 11J | 320 | 749 | 975 | 2149 | 340/50 | BSW | √ | √ | √ |
| 315/35R22 | 111TXL | 11J | 320 | 779 | 1090 | 2403 | 340/50 | BSW | √ | √ | √ |
| NEW 325/35R22 | 114TXL | 11 1/2J | 331 | 787 | 1180 | 2601 | 340/50 | BSW | √ | √ | √ |
| NEW 325/40R22 | 114T | 11 1/2J | 331 | 819 | 1180 | 2601 | 300/44 | BSW | √ | √ | √ |

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice

# WINTERPLUS STUD III


## Balanced design

It ensures the grip on ice and snow, and gives consideration to wear, rolling resistance and silent performance. It is a classic tire with balanced comprehensive performance.


## Wide driving surface plus square shoulder design

The tread area of the tire is increased, the stress is reduced, and the braking and starting performance of the tire is better.


## Optimized nail position design

The optimized layout of the whole circumference of the studs effectively improves the ultra-high and even ice grip of the tires during driving. The anti drop nail hole design can effectively prevent the risk of the tire from dropping the studs during driving.




## Pitch design of two in one composite design

The computer pitch arrangement based on genetic algorithm effectively reduces the tire noise and improves the comfort of drivers and passengers.


## Design of widened transverse and longitudinal ditches

Effectively improve the tire snow removal capacity under snow cover; The design of the central continuous pattern block and the high proportion of sea to land ratio maintain the rigidity of the tire and effectively improve the driving stability of the tire.


WINTER

| Size | LI/SI | Rim | S/W (mm) | O/D (mm) | load Index (kg) | load Index (Lbs) | Max Pressure (Kpa/Psi) | Sidewall | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 185/75R16C | 104/102R | 5J | 184 | 684 | 900/850 | 1985/1875 | 475/69 | BSW | √ | √ | √ |
| 195/75R16C | 107/105R | 5 1/2J | 196 | 698 | 975/925 | 2150/2040 | 475/69 | BSW | √ | √ | √ |
| 215/70R16 | 100T | 6 1/2J | 221 | 708 | 800 | 1764 | 300/44 | BSW | √ | √ | √ |
| 225/70R16 | 107TXL | 6 1/2J | 228 | 722 | 975 | 2149 | 340/50 | BSW | √ | √ | √ |
| 225/75R16C | 116/114R | 6J | 223 | 744 | 1250/1180 | 2755/2600 | 475/69 | BSW | √ | √ | √ |
| 235/65R16C | 121/119R | 7J | 240 | 712 | 1450/1360 | 3195/3000 | 575/83 | BSW | √ | √ | √ |
| NEW 235/70R16 | 106T | 7J | 240 | 736 | 950 | 2094 | 300/44 | BSW | √ | √ | √ |
| 245/70R16 | 111TXL | 7 J | 248 | 750 | 1090 | 2403 | 340/50 | BSW | √ | √ | √ |
| 245/75R16 | 111T | 7J | 248 | 774 | 1090 | 2403 | 300/44 | BSW | √ | √ | √ |
| LT225/75R16 | 115/112Q | 6J | 223 | 744 | 1215/1120 | 2680/2470 | 550/80 | BSW | √ | √ | √ |
| LT245/75R16 | 120/116Q | 7J | 248 | 774 | 1380/1260 | 3042/2778 | 550/80 | BSW | √ | √ | √ |
| 215/60R17 | 100TXL | 6 1/2J | 221 | 690 | 800 | 1764 | 340/50 | BSW | √ | √ | √ |
| 215/65R17 | 103TXL | 6 1/2J | 221 | 712 | 875 | 1929 | 340/50 | BSW | √ | √ | √ |
| 225/60R17 | 103T XL | 6 1/2J | 228 | 702 | 875 | 1929 | 340/50 | BSW | √ | √ | √ |
| 225/65R17 | 106TXL | 6 1/2J | 228 | 724 | 950 | 2094 | 340/50 | BSW | √ | √ | √ |
| 235/65R17 | 108TXL | 7J | 240 | 738 | 1000 | 2205 | 340/50 | BSW | √ | √ | √ |
| 265/65R17 | 112T | 8J | 272 | 776 | 1120 | 2469 | 300/44 | BSW | √ | √ | √ |
| 265/70R17 | 115T | 8J | 272 | 804 | 1215 | 2679 | 300/44 | BSW | √ | √ | √ |
| LT265/70R17 | 121/118Q | 8J | 272 | 804 | 1450/1320 | 3195/2910 | 550/80 | BSW | √ | √ | √ |
| 225/60R18 | 104TXL | 6 1/2J | 228 | 727 | 900 | 1984 | 340/50 | BSW | √ | √ | √ |
| 235/55R18 | 104TXL | 7 1/2J | 245 | 715 | 900 | 1984 | 340/50 | BSW | √ | √ | √ |
| 235/60R18 | 103T | 7J | 240 | 739 | 875 | 1929 | 300/44 | BSW | √ | √ | √ |
| NEW 235/65R18 | 106T | 7J | 240 | 763 | 950 | 2094 | 300/44 | BSW | √ | √ | √ |
| 245/60R18 | 109TXL | 7 J | 248 | 751 | 1030 | 2271 | 340/50 | BSW | √ | √ | √ |
| 255/55R18 | 109TXL | 8 J | 265 | 737 | 1030 | 2271 | 340/50 | BSW | √ | √ | √ |
| 265/60R18 | 114TXL | 8 J | 272 | 775 | 1180 | 2601 | 340/50 | BSW | √ | √ | √ |
| 275/65R18 | 116T | 8J | 279 | 815 | 1250 | 2756 | 300/44 | BSW | √ | √ | √ |
| NEW 285/60R18 | 116T | 8 1/2J | 292 | 799 | 1250 | 2756 | 300/44 | BSW | √ | √ | √ |
| LT275/65R18 | 119/116Q | 8J | 279 | 815 | 1360/1250 | 3000/2755 | 450/65 | BSW | √ | √ | √ |
| LT275/65R18 | 123/120Q | 8J | 279 | 815 | 1550/1400 | 3415/3085 | 550/80 | BSW | - | - | - |
| NEW LT275/70R18 | 125/122Q | 8J | 279 | 843 | 1650/1500 | 3640/3305 | 550/80 | BSW | - | - | - |
| NEW LT275/70R18 | 121/118Q | 8J | 279 | 843 | 1450/1320 | 3195/2910 | 450/65 | BSW | √ | √ | √ |
| 235/55R19 | 105TXL | 7 1/2J | 245 | 741 | 925 | 2039 | 340/50 | BSW | √ | √ | √ |
| 245/55R19 | 107TXL | 7 1/2J | 253 | 753 | 975 | 2149 | 340/50 | BSW | √ | √ | √ |
| 255/55R19 | 107T | 8J | 265 | 763 | 975 | 2149 | 300/44 | BSW | √ | √ | √ |
| 275/55R20 | 117TXL | 8 1/2J | 284 | 810 | 1285 | 2833 | 340/50 | BSW | √ | √ | √ |
| 275/60R20 | 115T | 8J | 279 | 838 | 1215 | 2679 | 300/44 | BSW | √ | √ | √ |
| LT275/60R20 | 119/116Q | 8J | 279 | 838 | 1360/1250 | 3000/2755 | 450/65 | BSW | √ | √ | √ |
| LT275/60R20 | 123/120Q | 8J | 279 | 838 | 1550/1400 | 3415/3085 | 550/80 | BSW | - | - | - |
| NEW LT275/65R20 | 126/123Q | 8J | 279 | 866 | 1700/1550 | 3750/3415 | 550/80 | BSW | - | - | - |
| NEW LT275/65R20 | 121/118Q | 8J | 279 | 866 | 1450/1320 | 3195/2910 | 450/65 | BSW | √ | √ | √ |

* New Developing Sizes / The Labeling Information are Subject to Change Without Notice