


TOWNHALL

Truck and Bus Tire Catalog

TOWNHALL



EJECUTIVO DE CUENTAS
Juan Carlos Burgos

 +57 312 8675625

Ver:23-1





ALL POSITION



HF916

Features

- Three groove design with lugs
- Special tread compound
- Shoulder design with lugs and sipes

Benefits

- Provide outstanding wet performance
- Provide outstanding resistance to abrasion
- Provide excellent heat dissipation



TH162

Features

- Four straight grooves design
- Tread surface with fine steel sipes design
- Stone ejectors set at the bottom of the side grooves

Benefits

- Provides excellent water drainage performance
- Provides good drainage and ensures good grip ability
- Protects the bottom of the grooves from hard gouges and cracks



TH162+

Features

- Four straight grooves design
- Tread surface with fine steel sipes design
- Stone ejectors set at the bottom of the side grooves
- Special tread compound formula for mid to long distance

Benefits

- Provides excellent water drainage performance
- Provides good drainage and ensures good grip ability
- Protects the bottom of the grooves from hard gouges and cracks
- Improves tyre wear mileage



TH356

Features

- Optimized void ratio and ground contact design
- Deeper grooves and strong block design
- Special tread compound formula for medium and long distance
- Optimized shoulder design

Benefits

- Delivers excellent ground footprint for improved wear performance
- Provides good driving, handling and wet grip performance
- Provides more mileage in a variety of conditions
- Improves tire crown anti-knock performance



Long Haul



Regional Haul



Operation:

- Highways and long distance / Regional highways and city streets
- Well paved road conditions / Mainly used on paved roads, occasionally run on unpaved roads
- Constant and high speed with minimal braking and accelerating / Frequent braking, accelerating and turning

Size	HF916	TH162	TH162+	TH356
12.00R20	156/153 K			
11R22.5		146/143 M		146/143 L
275/80R22.5			149/146 M	149/146 L
295/80R22.5		152/149 M	152/149 M	152/149 M
315/80R22.5		156/152 L (154/151 M)		156/152 L (154/151 M)
385/65R22.5		160 K		



STEER/TRAILER



Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance

TH905



Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance

TH160



Features

- Solid rib design combined with multiple sipes
- Four wide circumferential grooves
- Solid shoulder design

Benefits

- Provide excellent heat dissipation and improved regular wear with lower resistance
- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide outstanding resistance to abrasion

TH933



Features

- Four circumferential grooves
- Solid shoulder design
- Specially designed compound

Benefits

- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Provide outstanding resistance to abrasion
- Reduce rolling noise greatly
- Deliver lower rolling resistance

TH910

Size	TH905	TH160	TH933	TH910
7.50R16LT			122/118 M	
8.25R16LT				128/124 M
275/80R22.5	149/146 M			
385/65R22.5		160 K		



STEER/TRAILER



Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance

TH905



Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance

TH912



Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance

TH913



Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance

TH915

Size	TH905	TH912	TH913	TH915
11R22.5		146/143 M	146/143 M	
12R22.5				152/149 M
13R22.5	156/153 L			
295/80R22.5	152/149 M			
315/80R22.5	157/154 M			



STEER/TRAILER



Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance



Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance



Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance



Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance

Size	TH602	TH603	TH617	TH626
11R22.5		146/143 M	146/143 M	
295/80R22.5	152/149 M	152/149 M		152/149 M
315/80R22.5	156/152 L(154/151 M)	156/152 L(154/151 M)		



STEER/TRAILER



Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance



Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance



Features

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

Benefits

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide excellent heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance

Size	TH613	TH602	NTL660
12R22.5	152/149 M	152/149 M	152/149 M



Features

- Three circumferencial grooves
- Block pattern design
- Special tread compound
- Solid shoulder design

Benefits

- Ensure outstanding water evacuation, even pressure distribution and heat dissipation
- Provide excellent driving and braking force
- Provide outstanding resistance to puncture and tearing
- Provide outstanding resistance to abrasion



Features

- Block pattern design
- Extra wide footprint
- Deeper tread depth design

Benefits

- Provide excellent driving and braking force
- Enhanced stability and resistance to abrasion
- Improved mileage performance



Features

- Special tread compound
- Four circumferencial grooves
- Deeper tread depth design
- Block pattern design

Benefits

- Provide outstanding resistance to puncture and tearing
- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Improved mileage performance
- Provide excellent driving and braking force



Features

- Block pattern design
- Extra wide footprint
- Deeper tread depth design

Benefits

- Provide excellent driving and braking force
- Enhanced stability and resistance to abrasion
- Improved mileage performance

Size	TH935	TH921	TH668	TH607
12.00R24	160/157 K			
11R22.5				146/143 M
12R22.5		152/149 M		
275/80R22.5			149/146 L	
315/80R22.5				156/152 L(154/151 M)



Features

- Three circumferencial grooves
- Block pattern design
- Special tread compound
- Solid shoulder design

Benefits

- Ensure outstanding water evacuation, even pressure distribution and heat dissipation
- Provide excellent driving and braking force
- Provide outstanding resistance to puncture and tearing
- Provide outstanding resistance to abrasion



Features

- Block pattern design
- Extra wide footprint
- Deeper tread depth design

Benefits

- Provide excellent driving and braking force
- Enhanced stability and resistance to abrasion
- Improved mileage performance



Features

- Asymmetric lug design
- Block pattern design
- Four circumferencial grooves
- Reinforced carcass and bead design

Benefits

- Combine regular wear with excellent traction
- Provide excellent driving and braking force
- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Ensure excellent handling and safe performance and provide outstanding loading capacity



Features

- Three circumferencial grooves
- Block pattern design
- Special tread compound
- Solid shoulder design

Benefits

- Ensure outstanding water evacuation, even pressure distribution and heat dissipation
- Provide excellent driving and braking force
- Provide outstanding resistance to puncture and tearing
- Provide outstanding resistance to abrasion

Size	TH612	TH605	TH609	TH610
12R22.5	152/149 M			
295/80R22.5		152/149 M		
315/80R22.5		156/152 L(154/151 M)	156/152 L(154/151 M)	156/152 L(154/151 M)



Features

- Three circumferential grooves
- Block pattern design
- Special tread compound
- Solid shoulder design

Benefits

- Ensure outstanding water evacuation, even pressure distribution and heat dissipation
- Provide excellent driving and braking force
- Provide outstanding resistance to puncture and tearing
- Provide outstanding resistance to abrasion



Features

- Four zigzag grooves
- Extra wide footprint with square shoulder
- Special tread compound

Benefits

- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Enhanced stability and resistance to abrasion
- Provide outstanding resistance to abrasion



Features

- Four zigzag grooves
- Extra wide footprint with square shoulder
- Special tread compound

Benefits

- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Enhanced stability and resistance to abrasion
- Provide outstanding resistance to abrasion



Features

- Four zigzag grooves
- Extra wide footprint with square shoulder
- Special tread compound

Benefits

- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Enhanced stability and resistance to abrasion
- Provide outstanding resistance to abrasion



Features

- Four zigzag grooves
- Extra wide footprint with square shoulder
- Special tread compound

Benefits

- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Enhanced stability and resistance to abrasion
- Provide outstanding resistance to abrasion

Size	TH619
315/80R22.5	156/152 L(154/151 M)

Size	TH903	TH621	TH622	TH623
385/65R22.5	160 K	160 K	160 K	160 K



TRAILER



Features

- Special tread compound

Benefits

- Better mileage

TH615



Features

- Special tread compound

Benefits

- Better mileage

TH616



Features

- Four zigzag grooves
- Extra wide footprint with square shoulder
- Special tread compound

Benefits

- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Enhanced stability and resistance to abrasion
- Provide outstanding resistance to abrasion

TH625



Features

- Special tread compound

Benefits

- Better mileage

NTL362

Size	TH615	TH616	TH625	NTL362
12R22.5	152/149 M	152/149 M		152/149 M
385/65R22.5			160 K	



Mixed Service



Operation:

- Frequently used on and off roads
- Heavier loads
- Construction site



ALL POSITION



Features

- Three zigzag grooves
- Combination of rib and lug design
- Shoulder design with lugs

Benefits

- Provide excellent anti-sidesliping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Provide excellent heat dissipation

TH901



Features

- Three zigzag grooves
- Combination of rib and lug design
- Shoulder design with lugs

Benefits

- Provide excellent anti-sidesliping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Provide excellent heat dissipation

TH902



Features

- Three zigzag grooves
- Combination of rib and lug design
- Shoulder design with lugs

Benefits

- Provide excellent anti-sidesliping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Provide excellent heat dissipation

TH908



Features

- All position tread pattern design
- Special tread compound formula for Mid-Short distance
- Triple zigzag main grooves and shoulder cross grooves design
- Sipes design on tread surface

Benefits

- For a wide range of complex road conditions
- Provides good tear resistance and improves wear mileage
- Provides good grip on both dry and wet conditions
- Improves handling performance in wet conditions

TH572

Size	TH901	TH902	TH908	TH572
7.00R16LT	118/114 M			
7.50R16LT	122/118 M			
8.25R16LT	128/124 M			
8.25R20	139/137 L			
9.00R20	144/142 K			
10.00R20	149/146 K			
12.00R20	156/153 K			156/153 K
12.00R24	160/157 K			160/157 K
11R22.5	146/143 M			146/143 M
12R22.5	152/149 M			
13R22.5	156/153 L			
275/80R22.5				149/146 L
295/80R22.5		152/149 M		
315/80R22.5	157/154 M		157/154 M	156/152L(154/151 M)



DRIVE



Features

- Three zigzag grooves
- Combination of rib and lug design
- Shoulder design with lugs

Benefits

- Provide excellent anti-sidesliping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Provide excellent heat dissipation

TH601



Features

- Three zigzag grooves
- Combination of rib and lug design
- Shoulder design with lugs

Benefits

- Provide excellent anti-sidesliping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Provide excellent heat dissipation

TH620



Features

- Three zigzag grooves
- Combination of rib and lug design
- Shoulder design with lugs

Benefits

- Provide excellent anti-sidesliping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Provide excellent heat dissipation

HF901



Features

- Three zigzag grooves
- Combination of rib and lug design
- Shoulder design with lugs

Benefits

- Provide excellent anti-sidesliping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Provide excellent heat dissipation

NTL702

Size	TH601	TH620	HF901	NTL702
12.00R20			156/153 K	
11R22.5	146/143 M	146/143 M		
12R22.5	152/149 M			152/149 M
315/80R22.5	156/152 L(154/151 M)			



TH375

Features

- Large block & Deep groove design
- Open shoulder design
- Optimized tread compound
- Special horizontal small groove design

Benefits

- Provides excellent traction and braking force
- Provides good traction and self-cleaning performance
- Provides excellent tear resistance, cut resistance and snow traction
- Improve snow traction performance



TH608

Features

- Special tread compound
- Block pattern design
- Extra wide footprint with square shoulder
- Reinforced carcass and bead design

Benefits

- Provide outstanding resistance to puncture and tearing
- Provide excellent driving and braking force
- Enhanced stability and resistance to abrasion
- Ensure excellent handling and safe performance and provide outstanding loading capacity



HF917

Features

- Lug and block pattern design
- Special groove design
- Special tread compound
- Open shoulder design

Benefits

- Improved traction, driving and braking performance
- Deliver stone-ejecting property
- Provide outstanding resistance to puncture and tearing
- Provide excellent heat dissipation



HF918

Features

- Lug and block pattern design
- Special groove design
- Special tread compound
- Open shoulder design

Benefits

- Improved traction, driving and braking performance
- Deliver stone-ejecting property
- Provide outstanding resistance to puncture and tearing
- Provide excellent heat dissipation

Size	TH375	TH608	HF917	HF918
12.00R20			156/153 K	156/153 K
315/80R22.5	156/152 L(154/151 M)	156/152 L(154/151 M)		



Operation:

- Mostly used on rugged terrain like mining or heavy construction
- Heavier loads
- High risk of damage from road conditions



Features

- Special tread compound
- Lug and special block pattern design

Benefits

- Provide outstanding resistance to puncture and tearing
- Improved traction, driving and braking performance



Features

- ▶ Lug and block pattern design
- ▶ Special tread compound
- ▶ Reinforced carcass and bead design

Benefits

- Improved traction, driving and braking performance
- Provide outstanding resistance to puncture and tearing
- Ensure excellent handling and safe performance and provide outstanding loading capacity

Size	HF919	HF920
12.00R20	156/153 D	156/153 D